

Release ZERO.0.1 of package RefereeToolbox

Frédéric Dambreville
<http://email.fredericdambreville.com>

March 16, 2010

1 Description

RefereeToolbox is a java package implementing combination operators for fusing evidences. It is downloadable from:

<http://refereefunction.fredericdambreville.com/releases>

RefereeToolbox is based on an interpretation of the fusion rules by means of Referee Functions (refer to 2). This approach implies a dissociation between the definition of the combination and its actual implementation, which is common to all referee-based combinations. As a result, RefereeToolbox is designed with the aim to be generic and evolutive. It is composed of three distinct classes of objects:

- A class for the logical representation of the information; this class is generic and incremental; are yet implemented structures as:
 - Powerset,
 - Free Boolean algebra,
 - Superpowerset,
 - Open/closed hyperpowerset,
 - ... → make yours!
- A class for defining the referee functions; this class is generic and incremental; are yet defined referee functions for:
 - Dempster-Shafer combination,
 - Disjunctive combination,
 - Dubois&Prade combination,
 - PCR6 combination,
 - PCR# combination,
 - ... → make yours!
- A class defining the Basic Belief Assignment, and related processes; this class is generic and incremental; two referee-based approaches are implemented for computing combinations:
 - An exact approach associated with a relaxation of the focal elements, so as to handle the combinatorics,

– A sampling-based approach.

The generic implementation of RefereeToolbox makes possible to combine these three classes and their instances without restriction.

2 What is a referee function?

For an introduction to the theory of referee function, please refer to [3].

2.1 Basic Belief Assignment

Let G^Θ be a *complete distributive lattice*. A *basic belief assignment* [1, 2] is a mapping m from elements of G^Θ onto $[0, 1]$ such that:

$$\sum_{X \in G^\Theta} m(X) = 1 \quad \text{and} \quad m(\emptyset) = 0. \quad (1)$$

2.2 Referee function

Definition. A referee function over G^Θ for s sources of information and with context γ is a mapping $X, Y_{1:s} \mapsto F(X|Y_{1:s}; \gamma)$ defined on propositions $X, Y_{1:s} \in G^\Theta$, which satisfies for any $X, Y_{1:s} \in G^\Theta$:

$$F(X|Y_{1:s}; \gamma) \geq 0 \quad \text{and} \quad \sum_{X \in G^\Theta} F(X|Y_{1:s}; \gamma) = 1,$$

A referee function for s sources of information is also called a s -ary referee function. The quantity $F(X|Y_{1:s}; \gamma)$ is called a *conditional arbitrament* between $Y_{1:s}$ in favor of X . Notice that X is not necessary one of the propositions $Y_{1:s}$; typically, it could be a combination of them. The case $X = \emptyset$ is called the *rejection case*.

Fusion rule. Let be given s basic belief assignments (bba) $m_{1:s}$ and a s -ary referee function F with context $m_{1:s}$. Then, the fused bba $m_1 \oplus \dots \oplus m_s[F] \stackrel{\Delta}{=} \oplus[m_{1:s}|F]$ based on the referee F is constructed as follows:

$$\begin{aligned} \oplus[m_{1:s}|F](X) &= \frac{I[X \neq \emptyset]}{1 - z} \sum_{Y_{1:s} \in G^\Theta} F(X|Y_{1:s}; m_{1:s}) \prod_{i=1}^s m_i(Y_i), \\ \text{where } z &= \sum_{Y_{1:s} \in G^\Theta} F(\emptyset|Y_{1:s}; m_{1:s}) \prod_{i=1}^s m_i(Y_i), \\ I[X \neq \emptyset] &= 1 \text{ if } X \neq \emptyset, \text{ and } I[X \neq \emptyset] = 0 \text{ if } X = \emptyset. \end{aligned} \quad (2)$$

The value z is called the *rejection rate*.

2.3 Examples of referee functions

Dempster-shafer rule. Let be given s sources of information characterized by their bbas $m_{1:s}$. The fused bba m_{DST} obtained from $m_{1:s}$ by means of *Dempster-Shafer* fusion rule [1, 2]

is defined by:

$$\begin{cases} m_{\text{DST}}(\emptyset) = 0, \\ m_{\text{DST}}(X) = \frac{m_c(X)}{1 - m_c(\emptyset)} \text{ for any } X \in G^\Theta \setminus \{\emptyset\}, \end{cases}$$

where $m_c(\cdot)$ corresponds to the conjunctive consensus:

$$m_c(X) \triangleq \sum_{\substack{Y_1 \cap \dots \cap Y_s = X \\ Y_1, \dots, Y_s \in G^\Theta}} \prod_{i=1}^s m_i(Y_i).$$

Definition by referee function. The definition of a referee function for Dempster-Shafer is immediate:

$$m_{\text{DST}} = \oplus[m_{1:s}|F_{\text{DST}}],$$

$$\text{where } F_{\text{DST}}(X|Y_{1:s}; m_{1:s}) = I \left[X = \bigcap_{k=1}^s Y_k \right].$$

References

- [1] Dempster A.P., *Upper and Lower probabilities induced by a multivalued mapping*, Annals of Mathematical Statistics, vol. 83, pp. 325–339, 1967.
- [2] Shafer G., *A mathematical theory of evidence*, Princeton University Press, 1976.
- [3] Frédéric Dambreville, *Chap. 6: Definition of evidence fusion rules based on referee functions*, in Smarandache F. & Dezert J., Editors, *Applications and Advances on DSMT for Information Fusion (Collected Works)*, Vol. 3, American Research Press, 2009.

3 Code

Source Code: ArrayBoolean.java

```
1  /*
2  *   ArrayBoolean.java : part of package RefereeToolbox; Implementation of
3  *   Boolean algebra .
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * Implementation of a Boolean structure by means of an array of {@code long}.
30 * The AND and OR operators are inherited from the operators {@code &} and {@code ←
31 * | }
32 * working on {@code long}.
33 * <i>zero</i> is defined by zeroing all bits. <i>one</i> is defined by setting to
34 * 1 all active bits; the right bits of the {@code long } vector may be inactive ,
35 * depending on the size of the Lattice.
36 * The complement/cocomplement operators are inherited from the operators {@code ~←
37 * }
38 * working on {@code long}; exceeding bits are masked by a AND with <i>one</i>.
39 *
40 * @author   <A href="http://email.fredericdambreville.com">Frédéric ←
41 *   Dambreville</A>
42 *
43 *
44 * <BR><BR><table border='1' cellPadding='4'><tr><td>
45 * <font color="#008000" style="font-family: georgia">
46 *   Copyright (c) 2010 Frédéric Dambreville<BR>
47 * <BR>
48 *   RefereeToolbox is free software: you can redistribute it and/or modify
49 *   it under the terms of the GNU General Public License as published by
50 *   the Free Software Foundation, either version 3 of the License, or
51 *   (at your option) any later version.<BR>
52 * <BR>
53 *   RefereeToolbox is distributed in the hope that it will be useful,
54 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
55 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
56 *   GNU General Public License for more details.<BR>
57 * <BR>
58 *   You should have received a copy of the GNU General Public License
59 *   along with RefereeToolbox. If not, see
60 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
61 * </font></td></tr></table><BR>
62 *
63 */
64 public class ArrayBoolean<L extends ArrayBoolean<L>>
65     extends ArrayLattice<L> implements ComplementedLattice<L> {
```

```

65
66 ///////////////////////////////////////////////////:
67 // public part
68 //////////////////////////////////////////////////
69
70 /**
71  * Compute the <b>complement</b> of <i>aProposition</i> and store the result ←
72  * within
73  * <i>this</i>.
74  * The complement/cocomplement operators are inherited from the operators {←
75  * @code ~ }
76  * working on { @code long }; exceeding bits are masked by a AND with <i>one</i>←
77  * >.
78  * The complement and cocomplement are the same for { @link ArrayBoolean }
79  * <BR><BR>
80  * <b>Documentation inherited from { @link ComplementedLattice }:</b><BR>
81  * { @inheritDoc }
82  */
83 public L complement(L aProposition) {
84     long[] rightmem=aProposition._memory;
85     int i;
86     for (i=0;i<=size_mem_1;i++) _memory[i]=~rightmem[i];
87     _memory[size_mem_1]&=highest_long_one;
88     return (L) this;
89 }
90
91 /**
92  * Compute the <b>complement</b> of <i>aProposition</i> and store the result ←
93  * within
94  * <i>this</i>.
95  * The complement/cocomplement operators are inherited from the operators {←
96  * @code ~ }
97  * working on { @code long }; exceeding bits are masked by a AND with <i>one</i>←
98  * >.
99  * The complement and cocomplement are the same for { @link ArrayBoolean }
100  * <BR><BR>
101  * <b>Documentation inherited from { @link ComplementedLattice }:</b><BR>
102  * { @inheritDoc }
103  */
104 public L complement() {
105     int i;
106     for (i=0;i<=size_mem_1;i++) _memory[i]=~_memory[i];
107     _memory[size_mem_1]&=highest_long_one;
108     return (L) this;
109 }
110
111 /**
112  * Compute the <b>complement</b> of <i>aProposition</i> and store the result ←
113  * within
114  * <i>this</i>.
115  * The complement/cocomplement operators are inherited from the operators {←
116  * @code ~ }
117  * working on { @code long }; exceeding bits are masked by a AND with <i>one</i>←
118  * >.
119  * The complement and cocomplement are the same for { @link ArrayBoolean }
120  * <BR><BR>
121  * <b>Documentation inherited from { @link ComplementedLattice }:</b><BR>
122  * { @inheritDoc }
123  */
124 public L cocomplement(L aProposition) {
125     return complement(aProposition);
126 }
127
128 /**
129  * Compute the <b>complement</b> of <i>aProposition</i> and store the result ←
130  * within
131  * <i>this</i>.
132  * The complement/cocomplement operators are inherited from the operators {←
133  * @code ~ }
134  * working on { @code long }; exceeding bits are masked by a AND with <i>one</i>←
135  * >.

```

```

127     * The complement and cocomplement are the same for {@link ArrayBoolean }
128     * <BR><BR>
129     * <b>Documentation inherited from {@link ComplementedLattice }:</b><BR>
130     * {@inheritDoc}
131     *
132     */
133     public L cocomplement() {
134         return complement();
135     }
136
137 }

```

Source Code: ArrayLattice.java

```

1  /*
2  *   ArrayLattice.java : part of package RefereeToolbox; Implementation of
3  *   Lattice.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * Implementation of a Lattice structure by means of an array of {@code long}.
30 * The AND and OR operators are inherited from the operators {@code & } and {@code ←
31 * | }
32 * working on {@code long}.
33 * zero is defined by zeroing all bits. one is defined by setting to
34 * 1 all active bits; the right bits of the {@code long } vector may be inactive,
35 * depending on the size of the Lattice.
36 * @author   <A href="http://email.fredericdambreville.com">Frédéric ←
37 *           Dambreville</A>
38 *
39 *
40 * <BR><BR><table border='1' cellPadding='4'><tr><td>
41 * <font color="#008000" style="font-family: georgia">
42 * Copyright (c) 2010 Frédéric Dambreville<BR>
43 * <BR>
44 * RefereeToolbox is free software: you can redistribute it and/or modify
45 * it under the terms of the GNU General Public License as published by
46 * the Free Software Foundation, either version 3 of the License, or
47 * (at your option) any later version.<BR>
48 * <BR>
49 * RefereeToolbox is distributed in the hope that it will be useful,
50 * but WITHOUT ANY WARRANTY; without even the implied warranty of
51 * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
52 * GNU General Public License for more details.<BR>
53 * <BR>
54 * You should have received a copy of the GNU General Public License
55 * along with RefereeToolbox. If not, see
56 * <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
57 * </font></td></tr></table><BR>
58 *
59 */
60 public class ArrayLattice<L extends ArrayLattice<L>>
61     extends LatticeCommon<L> {
62
63     protected long[] _memory=null;
64
65     protected int size_mem_1=-1; // undefined, by default
66     protected long highest_long_one;
67
68
69     ///////////////////////////////////////////:
70     // public part

```

```

71 ///////////////
72
73 /**
74 * Return a representation of the state of <i>this</i> printed as a String. States
75 * of this class are printed as the concatenation of the Hexadecimal ↵
76 * representation
77 * of the <i>long</i> array.
78 */
79 @Override
80 public String state() {
81     String theState="";
82     String tmp;
83     int i;
84     for(i=size_mem_1;i>=0;i--) {
85         tmp=Long.toHexString(_memory[i]);
86         theState+="x"+"0000000000000000".substring(0, 16-tmp.length())+tmp;
87     }
88     return theState;
89 }
90
91 /**
92 * Set <i>this</i> to zero, the neutral element for
93 * {@link Lattice#or(java.lang.Object, java.lang.Object) }.
94 * N.B. It is necessary to call {@link Lattice#size } or
95 * {@link Lattice#size(java.lang.Object) } before any first use of this
96 * method.
97 */
98 @Override
99 public L zero() {
100     int i;
101     for(i=0;i<=size_mem_1;i++) _memory[i]=0;
102     return (L) this;
103 }
104
105 /**
106 * Set <i>this</i> to one, the neutral element for
107 * {@link Lattice#and(java.lang.Object, java.lang.Object) }.
108 * N.B. It is necessary to call {@link Lattice#size } or
109 * {@link Lattice#size(java.lang.Object) } before any first use of this method.
110 */
111 @Override
112 public L one() {
113     int i;
114     for(i=0;i<size_mem_1;i++) _memory[i]=0xFFFFFFFFFFFFFFFFL;
115     _memory[i]=highest_long_one;
116     return (L) this;
117 }
118
119 /**
120 * Compute the AND of <i>left</i> and <i>right</i> and store the result within <i>↵
121 * this</i>.
122 */
123 @Override
124 public L and(L left, L right) {
125     long[] leftmem=left._memory;
126     long[] rightmem=right._memory;
127     int i;
128     for(i=0;i<=size_mem_1;i++) _memory[i]=leftmem[i]&rightmem[i];
129     return (L) this;
130 }
131
132 /**
133 * Compute the OR of <i>left</i> and <i>right</i> and store the result within <i>↵
134 * this</i>.
135 */
136 @Override
137 public L or(L left, L right) {
138     long[] leftmem=left._memory;
139     long[] rightmem=right._memory;

```

```

142         int i;
143         for(i=0;i<=size_mem_1;i++) _memory[i]=leftmem[i]|rightmem[i];
144         return (L) this;
145     }
146
147 /**
148  * Answer <i>true</i> if the proposition stored within <i>this</i> intersects the
149  * proposition contained within <i>aProposition</i> (<i>i.e.</i> the intersection
150  * of both propositions is not <i>zero</i>). Answer <i>>false</i> otherwise.
151  *
152  */
153     @Override
154     public boolean intersects(L aProposition) {
155         long[] rightmem=aProposition._memory;
156         int i;
157         for(i=0;i<=size_mem_1;i++) {
158             if((_memory[i]&rightmem[i])!=0) return true;
159         }
160         return false;
161     }
162
163 /**
164  * Answer <i>true</i> if the proposition stored within <i>this</i> contains the
165  * proposition contained within <i>aProposition</i>. Answer <i>>false</i> otherwise←
166  *
167  */
168     @Override
169     public boolean contains(L aProposition) {
170         long[] rightmem=aProposition._memory;
171         int i;
172         for(i=0;i<=size_mem_1;i++) {
173             if((_memory[i]&rightmem[i])!=rightmem[i]) return false;
174         }
175         return true;
176     }
177
178 /**
179  * Compare <i>this</i> to <i>aProposition</i> and answer negative integer, zero,
180  * positive integer as <i>this</i> is less than, equal to, or greater than
181  * <i>aProposition</i>.
182  * This comparison is related to a total ordering of the proposition; <em>it is ↔
183  * not
184  * related to the partial order implied by the logical operators AND and OR.</em>
185  *
186  */
187     @Override
188     public int compareTo(L aProposition) {
189         long[] rightmem=aProposition._memory;
190         int i;
191         long delta;
192         for(i=0;i<=size_mem_1;i++) {
193             delta=_memory[i]-rightmem[i];
194             if(delta>0) return 1;
195             if(delta<0) return -1;
196         }
197         return 0;
198     }
199
200 /**
201  * Resize <i>this</i> at the same size than <i>input</i>.
202  *
203  */
204     @Override
205     public L size(L input) {
206         size_mem_1=input.size_mem_1;
207         highest_long_one=input.highest_long_one;
208         _memory=new long[size_mem_1+1];
209         return (L) this;
210     }
211
212 /**
213  * Do an exact copy of input into <i>this</i>.

```

```
214  *
215  */
216  @Override
217  public L duplicate(L input) {
218      size(input);
219      int i;
220      for(i=0;i<=size_mem_1;i++) _memory[i]=input._memory[i];
221      return (L) this;
222  }
223
224 }
```

Source Code: Assignment.java

```

1  /*
2  *   Assignment.java : part of package RefereeToolbox; Class encoding an
3  *   assignment of a basic belief to a proposition.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * Container instrumental to all classes implementing {@link minAssignment } and
30 * to class RefereeFunctionDefault and its subclasses;
31 * a structure encoding an assignment of a basic belief to a proposition.
32 *
33 * @author      <A href="http://email.fredericdambreville.com">Frédéric ↵
34 *              Dambreville</A>
35 *
36 *
37 * <BR><BR><table border='1' cellPadding='4'><tr><td>
38 * <font color="#008000" style="font-family: georgia">
39 *   Copyright (c) 2010 Frédéric Dambreville<BR>
40 * <BR>
41 *   RefereeToolbox is free software: you can redistribute it and/or modify
42 *   it under the terms of the GNU General Public License as published by
43 *   the Free Software Foundation, either version 3 of the License, or
44 *   (at your option) any later version.<BR>
45 * <BR>
46 *   RefereeToolbox is distributed in the hope that it will be useful,
47 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
48 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
49 *   GNU General Public License for more details.<BR>
50 * <BR>
51 *   You should have received a copy of the GNU General Public License
52 *   along with RefereeToolbox. If not, see
53 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
54 * </font></td></tr></table><BR>
55 *
56 */
57 public class Assignment<Prop> {
58 /**
59 * This subfield stores the proposition of the assignment typed {@link Assignment ↵
60 *   }.
61 */
62     public Prop attribute;
63 /**
64 * This subfield stores the value of the assignment.
65 *
66 */
67     public Double value;
68 }

```

Source Code: BasicBeliefAssignment.java

```

1  /*
2  *   BasicBeliefAssignment.java : part of package RefereeToolbox; Interface for
3  *   Basic Belief Assignments.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 import java.util.*;
29
30 /**
31 * Contains the minimal declaration for classes managing belief assignment
32 * structures, belief assignment processes and fusers.
33 * This interface is implemented by all the these classes.
34 *
35 * @author   <A href="http://email.fredericdambreville.com">Frédéric ↵
36 *           Dambreville</A>
37 *
38 *
39 * <BR><BR><table border='1' cellPadding='4'><tr><td>
40 * <font color="#008000" style="font-family: georgia">
41 *   Copyright (c) 2010 Frédéric Dambreville<BR>
42 * <BR>
43 *   RefereeToolbox is free software: you can redistribute it and/or modify
44 *   it under the terms of the GNU General Public License as published by
45 *   the Free Software Foundation, either version 3 of the License, or
46 *   (at your option) any later version.<BR>
47 * <BR>
48 *   RefereeToolbox is distributed in the hope that it will be useful,
49 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
50 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
51 *   GNU General Public License for more details.<BR>
52 * <BR>
53 *   You should have received a copy of the GNU General Public License
54 *   along with RefereeToolbox. If not, see
55 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
56 * </font></td></tr></table><BR>
57 *
58 */
59 public interface BasicBeliefAssignment<Prop extends Lattice<Prop>,
60                                     B extends BasicBeliefAssignment<Prop,B> >
61                                     extends minAssignment<Prop> , Cloneable {
62
63 /**
64 * Clear the assignments stored within {@link BasicBeliefAssignment }, and
65 * store new assignments from the collection of assignment, <i>anAssignmentTab</i>↵
66 *   >.
67 *
68 */
69     boolean load(Collection<Assignment<Prop>> anAssignmentTab);
70
71 /**

```

```

71  * Do an exact copy of input into <i>this</i>.
72  *
73  */
74  B duplicate(B input); // make this a duplicate of input
75
76  /**
77  * Create and return an instance of <i>this</i> (i.e. work like a <b>new</b> on
78  * the Class of <i>this</i>).
79  * N.B. {@link BasicBeliefAssignment#instance()} cannot be defined for generic
80  * classes but <u>is necessary</u> for some methods. <u>It has to be defined with
81  * the non generic (typically final) sub-classes</u>.
82  * <br><br>
83  * For a given non generic sub-class <i>myNonGenericSubclass</i>, a typical
84  * definition of {@link BasicBeliefAssignment#instance()} is as follows:
85  * <br><br>
86  * <font color="#004488"><code>
87  *   {@code @Override}
88  *   <br>
89  *   public myNonGenericSubclass instance() { return new myNonGenericSubclass(); }
90  * </code></font>
91  *
92  */
93  B instance();
94
95  /**
96  * Create a clone of <i>this</i>.
97  *
98  */
99  B clone();
100
101  /**
102  * Make a mix of the basic belief assignments stored within the entry, <i>bbaIn</i>
103  * according to their respective weight <i>weight</i>. This mix is stored into <i>←
104  * this</i>.
105  *
106  */
107  B mix(ArrayList<B> bbaIn, double[] weight);
108
109  /**
110  * Called each time a change is done to <i>this</i>. This is usefull for processes ←
111  * which need an
112  * initialization after each change of the assignments. Typically, the
113  * sampling methods require an action of {@link BasicBeliefAssignment#←
114  * update_notification()}
115  * in order to decide for a new computation of the sampling tables, which are made
116  * necessary by a change of the assignments.
117  *
118  */
119  void update_notification(); //
120
121  /**
122  * Return a representation of the state of <i>this</i> printed as
123  * a String. Typically, this state is the list of all stored assignments (←
124  * proposition
125  * and value). Depending on the parameter <i>choix</i> in entry, the ←
126  * representation
127  * is modified as folllows:<br><br>
128  * <i>choix==0</i> — Nothing is printed.
129  * <br>
130  * <i>choix==1</i> — Assignments are printed in increasing order of their
131  * propositions,
132  * <br>
133  * <i>choix==2</i> — Assignments are printed in decreasing order of their
134  * value,
135  * <br>
136  * <i>choix==3</i> — Do both print in that order.
137  * <br>
138  *
139  */
140  String state(int choix); // a string representing the state of the BBA
141
142  /**
143  * Remove all assignments from <i>this</i>. The class instance is cleared.

```

```

139  *
140  */
141  void clear();
142
143  /**
144  * Add an assignment characterized by a proposition <i>aProposition</i> and a  $\leftrightarrow$ 
145  * value
146  * <i>anAssignmentValue</i> to <i>this</i>.
147  * If an assignment already exists for <i>aProposition</i>, say with value <i> $\leftrightarrow$ 
148  * theOldValue</i>,
149  * then the new assignment of <i>aProposition</i> is stored with value
150  * <i>theOldValue+anAssignmentValue</i>.
151  */
152  boolean add(Prop aProposition, double anAssignmentValue);
153
154  /**
155  * Do exactly as {@link BasicBeliefAssignment#add(RefereeToolbox.Lattice, double)}  $\leftrightarrow$ 
156  * }
157  * but takes an entry of type {@link Assignment }, which is actually
158  * equivalent.
159  */
160  boolean add(Assignment<Prop> anAssignment);
161
162  /**
163  * Add all assignments of collection <i>assignTab</i> to <i>this</i>.
164  * This method is equivalent to applying
165  * {@link BasicBeliefAssignment#add(RefereeToolbox.Assignment) }
166  * to each assignment of collection <i>assignTab</i>.
167  */
168  boolean addAll(Collection<Assignment<Prop>> assignTab);
169
170  /**
171  * Remove the assignment related to proposition <i>aProposition</i>, if there is
172  * such assignment stored within <i>this</i>.
173  * Return the value assigned to the proposition.
174  */
175  double remove(Prop aProposition);
176
177  }

```

Source Code: BBACCommon.java

```

1  /*
2  *   BBACCommon.java : part of package RefereeToolbox; Basical implementation of
3  *   the Basic Belief Assignment.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 import java.util.*;
29
30 /**
31 * Basical implementation of the Basic Belief Assignment structure.
32 *
33 * @author      <A href="http://email.fredericdambreville.com">Frédéric ↵
34 *               Dambreville</A>
35 *
36 *
37 * <BR><BR><table border='1' cellPadding='4'><tr><td>
38 * <font color="#008000" style="font-family: georgia">
39 *   Copyright (c) 2010 Frédéric Dambreville<BR>
40 * <BR>
41 *   RefereeToolbox is free software: you can redistribute it and/or modify
42 *   it under the terms of the GNU General Public License as published by
43 *   the Free Software Foundation, either version 3 of the License, or
44 *   (at your option) any later version.<BR>
45 * <BR>
46 *   RefereeToolbox is distributed in the hope that it will be useful,
47 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
48 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
49 *   GNU General Public License for more details.<BR>
50 * <BR>
51 *   You should have received a copy of the GNU General Public License
52 *   along with RefereeToolbox. If not, see
53 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
54 * </font></td></tr></table><BR>
55 *
56 */
57 public class BBACCommon <Prop extends Lattice<Prop>,
58                               B extends BBACCommon<Prop,B> >
59                               implements BasicBeliefAssignment<Prop,↵
60                                   B> {
61
62     ///////////////////////////////////////////:
63     // public part
64     //////////////////////////////////////
65
66     /**
67     * This method is not defined for class {@link BBACCommon} and generates an ↵
68     * error
69     * report and a code exit.
70     * <BR><BR>

```

```

70      * <b>Documentation inherited from {@link BasicBeliefAssignment }:</b><BR>
71      * {@inheritDoc}
72      */
73      public B duplicate(B input) {
74          System.err.println("Error :: "+this.getClass().getName() +
75              ".duplicate(B) is not implemented!");
76          System.err.println("Please implement clone() in your class with @Override"↵
77              );
78          System.exit(0);
79          return null;
80      }
81      @Override
82      public B clone() {
83          return instance().duplicate((B) this);
84      }
85
86      /**
87       * This method is not defined for class {@link BBACCommon } and generates an ↵
88       * error
89       * report and a code exit.
90       * <BR><BR>
91       * <b>Documentation inherited from {@link BasicBeliefAssignment }:</b><BR>
92       * {@inheritDoc}
93       */
94      public B instance() {
95          System.err.println("Error :: "+this.getClass().getName() +
96              ".clone() is not implemented!");
97          System.err.println("Please implement clone() in your class with @Override"↵
98              );
99          System.exit(0);
100          return null;
101      }
102
103      /**
104       * This method is not defined for class {@link BBACCommon } and produces the ↵
105       * String
106       * {@code "UNDEFINED" }.
107       * <BR><BR>
108       * <b>Documentation inherited from {@link BasicBeliefAssignment }:</b><BR>
109       * {@inheritDoc}
110       */
111      public String state(int choix) {
112          return "UNDEFINED";
113      }
114
115      /**
116       * This method is not defined for class {@link BBACCommon } and generates an ↵
117       * error
118       * report and a code exit.
119       * <BR><BR>
120       * <b>Documentation inherited from {@link BasicBeliefAssignment }:</b><BR>
121       * {@inheritDoc}
122       */
123      public ArrayList<Assignment<Prop>> toArray() {
124          System.err.println("Error :: "+this.getClass().getName() +
125              ".toArray() is not implemented!");
126          System.err.println("Please implement toArray() in your class with ↵
127              @Override");
128          System.exit(0);
129          return null;
130      }
131
132      public boolean load(Collection<Assignment<Prop>> anAssignmentTab) {
133          clear();
134          addAll(anAssignmentTab);
135          return true;
136      }
137
138      /**
139       * This method is not defined for class {@link BBACCommon } and generates an ↵
140       * error
141       * report and a code exit.
142       * <BR><BR>

```

```

137 * <b>Documentation inherited from {@link BasicBeliefAssignment }:</b><BR>
138 * {@inheritDoc}
139 */
140 public void clear() {
141     System.err.println("Error :: "+this.getClass().getName() +
142         ".clear() is not implemented!");
143     System.err.println("Please implement clear() in your class with @Override"↵
144         );
145     System.exit(0);
146 }
147 /**
148  * This method is not defined for class {@link BBACCommon } and generates an ↵
149     error
150     report and a code exit.
151     <BR><BR>
152     * <b>Documentation inherited from {@link BasicBeliefAssignment }:</b><BR>
153     * {@inheritDoc}
154     */
155 public boolean add(Prop aProposition, double anAssignmentValue) {
156     System.err.println("Error :: "+this.getClass().getName() +
157         ".add() is not implemented!");
158     System.err.println("Please implement add() in your class with @Override");
159     System.exit(0);
160     return true;
161 }
162 public boolean add(Assignment<Prop> anAssignment) {
163     return add(anAssignment.attribute, anAssignment.value);
164 }
165 public boolean addAll(Collection<Assignment<Prop>> assignTab) {
166     //bbaTree;
167     boolean test=true;
168     for (Iterator<Assignment<Prop>> it = assignTab.iterator();
169         it.hasNext(); ) {
170         test=test&&add(it.next());
171     }
172     return test;
173 }
174 }
175 /**
176  * This method is not defined for class {@link BBACCommon } and generates an ↵
177     error
178     report and a code exit.
179     <BR><BR>
180     * <b>Documentation inherited from {@link BasicBeliefAssignment }:</b><BR>
181     * {@inheritDoc}
182     */
183 public Assignment<Prop> findProposition(Assignment<Prop> anAssignment) {
184     System.err.println("Error :: "+this.getClass().getName() +
185         ".findProposition(Assignment<Prop>) is not implemented!");
186     System.err.println("Please implement findProposition(Assignment<Prop>)" +
187         " in your class with @Override");
188     System.exit(0);
189     return null;
190 }
191 public Assignment<Prop> findProposition(Prop aProposition) {
192     Assignment<Prop> searchAssign = new Assignment<Prop>();
193     searchAssign.attribute=aProposition;
194     return findProposition(searchAssign);
195 }
196 public double m(Prop aProposition) {
197     Assignment<Prop> foundPair=findProposition(aProposition);
198     if(foundPair!=null) {
199         return foundPair.value;
200     }
201     return 0.;
202 }
203 /**

```

```

208     * This method is not defined for class {@link BBACCommon } and generates an ↵
209     error
210     * report and a code exit.
211     * <BR><BR>
212     * <b>Documentation inherited from {@link BasicBeliefAssignment }:</b><BR>
213     * {@inheritDoc}
214     */
215     public double Bel(Prop aProposition) {
216         System.err.println("Error :: "+this.getClass().getName() +
217             ".Bel(Prop) is not implemented!");
218         System.err.println("Please implement Bel(Prop) in your class with ↵
219             @Override");
220         System.exit(0);
221         return -1;
222     }
223
224     /**
225     * This method is not defined for class {@link BBACCommon } and generates an ↵
226     error
227     * report and a code exit.
228     * <BR><BR>
229     * <b>Documentation inherited from {@link BasicBeliefAssignment }:</b><BR>
230     * {@inheritDoc}
231     */
232     public double Pl(Prop aProposition) {
233         System.err.println("Error :: "+this.getClass().getName() +
234             ".Pl(Prop) is not implemented!");
235         System.err.println("Please implement Pl(Prop) in your class with @Override↵
236             ");
237         System.exit(0);
238         return -1;
239     }
240
241     /**
242     * This method is not defined for class {@link BBACCommon } and generates an ↵
243     error
244     * report and a code exit.
245     * <BR><BR>
246     * <b>Documentation inherited from {@link BasicBeliefAssignment }:</b><BR>
247     * {@inheritDoc}
248     */
249     public double remove(Prop aProposition) {
250         System.err.println("Error :: "+this.getClass().getName() +
251             ".remove(Prop) is not implemented!");
252         System.err.println("Please implement remove(Prop) in your class with ↵
253             @Override");
254         System.exit(0);
255         return -1.;
256     }
257
258     /**
259     * This method is not defined for class {@link BBACCommon } and generates an ↵
260     error
261     * report and a code exit.
262     * <BR><BR>
263     * <b>Documentation inherited from {@link BasicBeliefAssignment }:</b><BR>
264     * {@inheritDoc}
265     */
266     public B mix(ArrayList<B> bbaIn, double[] weight) {
267         System.err.println("Error :: "+this.getClass().getName() +
268             ".mix(ArrayList<B>, double[]) is not implemented!");
269         System.err.println("Please implement mix(ArrayList<B>, double[]) in your ↵
270             +
271             " class with @Override");
272         System.exit(0);
273         return null;
274     }
275
276     public void update_notification() { // called each time a change is done
277     }

```

Source Code: BBAFuser.java

```

1  /*
2  *   BBAFuser.java : part of package RefereeToolbox; Interface for the fusion of
3  *   Basic Belief Assignments.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 import java.util.*;
29
30 /**
31 * Methods for fusing Basic Belief Assignments. This interface concerns direct
32 * rule implementations. It does not concern referee-based fusers, for which there
33 * are dedicated interfaces {@link BBARefereeFuser}, {@link SampledBBARefereeFuser}.
34 */
35 * @see          BBARefereeFuser
36 * @see          SampledBBARefereeFuser
37 * @author        <A href="http://email.fredericdambreville.com">Frédéric ↵
38 *               Dambreville</A>
39 *
40 *
41 * <BR><BR><table border='1' cellPadding='4'><tr><td>
42 * <font color="#008000" style="font-family: georgia">
43 *   Copyright (c) 2010 Frédéric Dambreville<BR>
44 * <BR>
45 *   RefereeToolbox is free software: you can redistribute it and/or modify
46 *   it under the terms of the GNU General Public License as published by
47 *   the Free Software Foundation, either version 3 of the License, or
48 *   (at your option) any later version.<BR>
49 * <BR>
50 *   RefereeToolbox is distributed in the hope that it will be useful,
51 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
52 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
53 *   GNU General Public License for more details.<BR>
54 * <BR>
55 *   You should have received a copy of the GNU General Public License
56 *   along with RefereeToolbox. If not, see
57 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
58 * </font></td></tr></table><BR>
59 *
60 */
61 public interface BBAFuser<Prop extends Lattice<Prop>, B extends BBAFuser<Prop,B> >
62 *               extends BasicBeliefAssignment<Prop,B> {
63
64 /**
65 * Compute the combination (fusion) of basic belief assignments <i>left</i> and
66 * <i>right</i> and store the result within <i>this</i>.
67 *
68 */
69 *   B fuse(B left, B right);
70

```

```
71 /**
72  * Compute the combination (fusion) of the basic belief assignments within array
73  * <i>bbaIn</i> and store the result within <i>this</i>.
74  *
75  */
76  B fuse(ArrayList<B> bbaIn);
77
78 /**
79  * Return the conflict of the last combination.
80  *
81  */
82  B conflict();
83
84 }
```

Source Code: BBARefereeFuser.java

```

1  /*
2  *   BBARefereeFuser.java : part of package RefereeToolbox; Interface for fuser
3  *   based on referee function.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 import java.util.*;
29
30 /**
31 * Methods for fusing Basic Belief Assignments by the means of referee functions
32 * and on the basis of an exact computation. This interface does not concern ←
33 *   direct
34 * rule implementations, {@link BBAFuser}, or implementations based on referee
35 * sampling, {@link SampledBBARefereeFuser}.
36 *
37 * @see      BBAFuser
38 * @see      SampledBBARefereeFuser
39 * @author    <A href="http://email.fredericdambreville.com">Frédéric ←
40 *           Dambreville</A>
41 *
42 * <BR><BR><table border='1' cellPadding='4'><tr><td>
43 * <font color="#008000" style="font-family: georgia">
44 *   Copyright (c) 2010 Frédéric Dambreville<BR>
45 * <BR>
46 *   RefereeToolbox is free software: you can redistribute it and/or modify
47 *   it under the terms of the GNU General Public License as published by
48 *   the Free Software Foundation, either version 3 of the License, or
49 *   (at your option) any later version.<BR>
50 * <BR>
51 *   RefereeToolbox is distributed in the hope that it will be useful,
52 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
53 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
54 *   GNU General Public License for more details.<BR>
55 * <BR>
56 *   You should have received a copy of the GNU General Public License
57 *   along with RefereeToolbox. If not, see
58 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
59 * </font></td></tr></table><BR>
60 *
61 */
62 public interface BBARefereeFuser<Prop extends Lattice<Prop>, B extends ←
63     BBARefereeFuser<Prop,B>>
64     extends BasicBeliefAssignment<Prop,B> {
65
66 /**
67 * Compute the combination (fusion) of basic belief assignments <i>left</i> and
68 * <i>right</i> by means of the referee function <i>theRefereeFunction</i> and
69 * store the result within <i>this</i>.

```

```

70  */
71  B fuse(B left, B right, RefereeFunctionDefault<Prop> theRefereeFunction);
72
73  /**
74   * Compute the combination (fusion) of basic belief assignments within array
75   * <i>bbaIn</i> by means of the referee function <i>theRefereeFunction</i> and
76   * store the result within <i>this</i>.
77   *
78   */
79   B fuse(ArrayList<B> bbaIn, RefereeFunctionDefault<Prop> theRefereeFunction);
80
81  /**
82   * Return the conflict of the last combination.
83   *
84   */
85   double conflict();
86
87  }

```

Source Code: Closedhyperpowerset.java

```

1  /*
2  *   Closedhyperpowerset.java : part of package RefereeToolbox; Implementation
3  *   of closed hyperpowerset.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * Implementation of a closed hyperpowerset structure. A closed hyperpowerset is
30 * an hyperpowerset defined on the basis of a superpowerset: it is generated
31 * from the atomic propositions of the superpowerset but without the use of
32 * the complement operator of the superpowerset.
33 * <BR><BR>
34 * The closed hyperpowerset implies a closed world hypothesis, that is:
35 * <BR><BR>
36 * <i> <b>OR</b><sub>0 ≤ i < sizeFrame</sub> atomic(i) == one</i>
37 * <BR><BR>
38 * Although generated without the complement of the superpowerset, the closed
39 * hyperpowerset actually has proper complement and cocomplement operators.
40 * The complement and cocomplement are distinct operators for the closed ↵
41 * hyperpowerset.
42 * @author   <A href="http://email.fredericdambreville.com">Frédéric ↵
43 *           Dambreville</A>
44 *
45 *
46 * <BR><BR><table border='1' cellPadding='4'><tr><td>
47 * <font color="#008000" style="font-family: georgia">
48 * Copyright (c) 2010 Frédéric Dambreville<BR>
49 * <BR>
50 * RefereeToolbox is free software: you can redistribute it and/or modify
51 * it under the terms of the GNU General Public License as published by
52 * the Free Software Foundation, either version 3 of the License, or
53 * (at your option) any later version.<BR>
54 * <BR>
55 * RefereeToolbox is distributed in the hope that it will be useful,
56 * but WITHOUT ANY WARRANTY; without even the implied warranty of
57 * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
58 * GNU General Public License for more details.<BR>
59 * <BR>
60 * You should have received a copy of the GNU General Public License
61 * along with RefereeToolbox. If not, see
62 * <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
63 * </font></td></tr></table><BR>
64 *
65 */
66 public class Closedhyperpowerset<L extends Closedhyperpowerset<L>> extends ↵
67     Superpowerset<L> {
68     protected L theZero = null;
69     protected L theOne = null;

```

```

70  /**
71  * Compute the <b>complement</b> of <i>aProposition</i> and store the result
72  * within <i>this</i>.
73  * The complement operator for the closed hyperpowerset is defined by:
74  * <BR><BR>
75  * <i> complement(zero) = one</i>
76  * <BR>
77  * <i> complement(X) = zero</i> if <i>X != zero</i>
78  *
79  */
80  @Override
81  public L complement(L aProposition) {
82      if (theZero==null) {
83          theZero = instanceNsize().zero();
84          theOne = instanceNsize().one();
85      }
86      if (aProposition.compareTo(theZero)==0) one();
87      else zero();
88      return (L) this;
89  }
90
91  /**
92  * Compute the <b>complement</b> of <i>this</i> and store the result within
93  * <i>this</i>.
94  * The complement operator for the closed hyperpowerset is defined by:
95  * <BR><BR>
96  * <i> complement(zero) = one</i>
97  * <BR>
98  * <i> complement(X) = zero</i> if <i>X != zero</i>
99  *
100  */
101  @Override
102  public L complement() {
103      if (theZero==null) {
104          theZero = instanceNsize().zero();
105          theOne = instanceNsize().one();
106      }
107      if (compareTo(theZero)==0) one();
108      else zero();
109      return (L) this;
110  }
111
112  /**
113  * Compute the <b>cocomplement</b> of <i>aProposition</i> and store the result
114  * within <i>this</i>.
115  * The cocomplement operator for the closed hyperpowerset is defined by:
116  * <BR><BR>
117  * <i> cocomplement(X) = <b>OR</b><sub>Z</sub> AND X != Z</sub> Z</i>
118  *
119  */
120  @Override
121  public L cocomplement(L aProposition) {
122      if (theZero==null) {
123          theZero = instanceNsize().zero();
124          theOne = instanceNsize().one();
125      }
126      L tmpProposition = instanceNsize();
127      L finalProposition = instanceNsize();
128      finalProposition.zero();
129      int i;
130      for (i=0; i<size(-1); i++) {
131          tmpProposition.atomic(i);
132          if (!aProposition.contains(tmpProposition))
133              finalProposition.or(finalProposition, tmpProposition);
134      }
135      return duplicate(finalProposition);
136  }
137
138  /**
139  * Compute the <b>cocomplement</b> of <i>this</i> and store the result
140  * within <i>this</i>.
141  * The cocomplement operator for the closed hyperpowerset is defined by:
142  * <BR><BR>
143  * <i> cocomplement(X) = <b>OR</b><sub>Z</sub> AND X != Z</sub> Z</i>

```

```

144      *
145      */
146      @Override
147      public L cocomplement() {
148          if (theZero == null) {
149              theZero = instanceNsize().zero();
150              theOne = instanceNsize().one();
151          }
152          L tmpProposition = instanceNsize();
153          L finalProposition = instanceNsize();
154          finalProposition.zero();
155          int i;
156          for (i = 0; i < size(-1); i++) {
157              tmpProposition.atomic(i);
158              if (!contains(tmpProposition))
159                  finalProposition.or(finalProposition, tmpProposition);
160          }
161          return duplicate(finalProposition);
162      }
163  }
164 }

```

Source Code: ComplementedLattice.java

```

1  /*
2  *   ComplementedLattice.java : part of package RefereeToolbox; Interface
3  *   for complemented Lattice.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * Contains the methods for a class implementing a Lattice structure with a
30 * complement or a pseudo-complement operator.
31 * Boolean algebra, powerset, as well as Heyting algebra or closed/open  $\leftrightarrow$ 
32 * Hyperpowersets
33 * are examples of complemented lattices.
34 *
35 * @author   <A href="http://email.fredericdambreville.com">Frédéric Dambreville</A>  $\leftrightarrow$ 
36 *           Dambreville</A>
37 *
38 * <BR><BR><table border='1' cellPadding='4'><tr><td>
39 * <font color="#008000" style="font-family: georgia">
40 *   Copyright (c) 2010 Frédéric Dambreville<BR>
41 * <BR>
42 *   RefereeToolbox is free software: you can redistribute it and/or modify
43 *   it under the terms of the GNU General Public License as published by
44 *   the Free Software Foundation, either version 3 of the License, or
45 *   (at your option) any later version.<BR>
46 * <BR>
47 *   RefereeToolbox is distributed in the hope that it will be useful,
48 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
49 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
50 *   GNU General Public License for more details.<BR>
51 * <BR>
52 *   You should have received a copy of the GNU General Public License
53 *   along with RefereeToolbox. If not, see
54 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
55 * </font></td></tr></table><BR>
56 *
57 */
58 public interface ComplementedLattice<L> extends Lattice<L> {
59
60 /**
61 * Compute the <b>complement</b> of <i>aProposition</i> and store the result  $\leftrightarrow$ 
62 *   within
63 *   <i>this</i>.
64 * <BR><BR>
65 * <b>Definition.</b> The complement of a proposition <i>X</i> of a lattice <i>L</i>  $\leftrightarrow$ 
66 *   is: <i>comp(X) = <b>OR</b><sub>Y : Y AND X = zero</sub> Y</i>
67 * <BR><BR>
68 * <b>Theorem 1.</b> If the lattice is a boolean algebra, then complement and  $\leftrightarrow$ 
69 *   cocomplement

```

```

68 * are identical, <i>comp(X) =cocomp(X)</i>
69 * <BR>
70 * <b>Theorem 2.</b> <i>cocomp(X)</i> contains <i>comp(X)</i>
71 *
72 * @see ComplementedLattice#cocomplement(java.lang.Object)
73 */
74 L complement(L aProposition);
75
76 /**
77 * Compute the <b>complement</b> of <i>this</i> and store the result within
78 * <i>this</i>.
79 * <BR><BR>
80 * <b>Definition.</b> The complement of a proposition <i>X</i> of a lattice <i>L</i>
81 * is: <i>comp(X) = <b>OR</b><sub>Y : Y AND X = zero</sub> Y</i>
82 * <BR><BR>
83 * <b>Theorem 1.</b> If the lattice is a boolean algebra, then complement and
84 * cocomplement
85 * are identical, <i>comp(X) =cocomp(X)</i>
86 * <BR>
87 * <b>Theorem 2.</b> <i>cocomp(X)</i> contains <i>comp(X)</i>
88 *
89 * @see ComplementedLattice#cocomplement()
90 */
91 L complement();
92
93 /**
94 * Compute the <b>cocomplement</b> of <i>aProposition</i> and store the result
95 * within <i>this</i>.
96 *
97 * <BR><BR>
98 * <b>Definition.</b> The cocomplement of a proposition <i>X</i> of a lattice <i>L</i>
99 * is: <i>cocomp(X) = <b>AND</b><sub>Z : Z OR X = one</sub> Z</i>
100 * <BR><BR>
101 * <b>Theorem 1.</b> If the lattice is a boolean algebra, then complement and
102 * cocomplement
103 * are identical, <i>comp(X) =cocomp(X)</i>
104 * <BR>
105 * <b>Theorem 2.</b> <i>cocomp(X)</i> contains <i>comp(X)</i>
106 *
107 * @see ComplementedLattice#complement(java.lang.Object)
108 */
109 L cocomplement(L aProposition);
110
111 /**
112 * Compute the <b>cocomplement</b> of <i>this</i> and store the result
113 * within <i>this</i>.
114 *
115 * <BR><BR>
116 * <b>Definition.</b> The cocomplement of a proposition <i>X</i> of a lattice <i>L</i>
117 * is: <i>cocomp(X) = <b>AND</b><sub>Z : Z OR X = one</sub> Z</i>
118 * <BR><BR>
119 * <b>Theorem 1.</b> If the lattice is a boolean algebra, then complement and
120 * cocomplement
121 * are identical, <i>comp(X) =cocomp(X)</i>
122 * <BR>
123 * <b>Theorem 2.</b> <i>cocomp(X)</i> contains <i>comp(X)</i>
124 *
125 * @see ComplementedLattice#complement()
126 */
127 L cocomplement();
128 }

```

Source Code: finalClosedhyperpowerset.java

```

1  /*
2  *   finalClosedhyperpowerset.java : part of package RefereeToolbox;
3  *   Implementation of closed hyperpowerset.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29  * Final implementation of class {@link Closedhyperpowerset }. This class is not ←
30  * generic, and
31  * thus, allows and needs instantiation. The method {@link ←
32  *   finalClosedhyperpowerset#instance() }
33  * is implemented.
34  *
35  * @author   <A href="http://email.fredericdambreville.com">Frédéric ←
36  *   Dambreville</A>
37  *
38  *
39  * <BR><BR><table border='1' cellPadding='4'><tr><td>
40  * <font color="#008000" style="font-family: georgia">
41  *   Copyright (c) 2010 Frédéric Dambreville<BR>
42  * <BR>
43  *   RefereeToolbox is free software: you can redistribute it and/or modify
44  *   it under the terms of the GNU General Public License as published by
45  *   the Free Software Foundation, either version 3 of the License, or
46  *   (at your option) any later version.<BR>
47  * <BR>
48  *   RefereeToolbox is distributed in the hope that it will be useful,
49  *   but WITHOUT ANY WARRANTY; without even the implied warranty of
50  *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
51  *   GNU General Public License for more details.<BR>
52  * <BR>
53  *   You should have received a copy of the GNU General Public License
54  *   along with RefereeToolbox. If not, see
55  *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
56  * </font></td></tr></table><BR>
57  *
58  */
59
60 public final class finalClosedhyperpowerset extends Closedhyperpowerset<←
61   finalClosedhyperpowerset> {
62
63   ///////////////////////////////////////////:
64   // public part
65   //////////////////////////////////////
66
67   /**
68    * Create and return an instance of <i>this</i> (i.e. work like a <b>new</b> on
69    * the Class of <i>this</i>).
70    * N.B. {@link Lattice#instance() } cannot be defined
71    * for generic classes but <u>is necessary</u> for some methods. <u>It has to be

```

```

69 * defined with the non generic (typically final) sub-classes </u>.
70 * <br><br>
71 * For a given non generic sub-class <i>myNonGenericSubclass</i>, a typical
72 * definition of {@link Lattice#instance\(\) } is as follows:
73 * <br><br>
74 * <font color="#004488"><code>
75 * {@code @Override}
76 * <br>
77 * public myNonGenericSubclass instance() { return new myNonGenericSubclass(); }
78 * </code></font>
79 *
80 */
81 @Override
82 public final ClosedHyperpowerset instance() { return new ↵
      finalClosedHyperpowerset(); }
83 }

```

Source Code: finalFreeboolean.java

```

1  /*
2  *   finalFreeboolean.java : part of package RefereeToolbox; Implementation of
3  *   free Boolean algebra.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29  * Final implementation of class {@link Freeboolean }. This class is not generic, ←
30  * and
31  * thus, allows and needs instantiation. The method {@link finalFreeboolean#←
32  * instance() }
33  * is implemented.
34  *
35  * @author   <A href="http://email.fredericdambreville.com">Frédéric ←
36  *           Dambreville</A>
37  *
38  *
39  * <BR><BR><table border='1' cellPadding='4'><tr><td>
40  * <font color="#008000" style="font-family: georgia">
41  *   Copyright (c) 2010 Frédéric Dambreville<BR>
42  * <BR>
43  *   RefereeToolbox is free software: you can redistribute it and/or modify
44  *   it under the terms of the GNU General Public License as published by
45  *   the Free Software Foundation, either version 3 of the License, or
46  *   (at your option) any later version.<BR>
47  * <BR>
48  *   RefereeToolbox is distributed in the hope that it will be useful,
49  *   but WITHOUT ANY WARRANTY; without even the implied warranty of
50  *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
51  *   GNU General Public License for more details.<BR>
52  * <BR>
53  *   You should have received a copy of the GNU General Public License
54  *   along with RefereeToolbox. If not, see
55  *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
56  * </font></td></tr></table><BR>
57  *
58  */
59
60 public final class finalFreeboolean extends Freeboolean<finalFreeboolean> {
61
62     //////////////////////////////////////////:
63     // public part
64     //////////////////////////////////////////
65
66     /**
67      * Create and return an instance of <i>this</i> (i.e. work like a <b>new</b> on
68      * the Class of <i>this</i>).
69      * N.B. {@link Lattice#instance() } cannot be defined
70      * for generic classes but <u>is necessary</u> for some methods. <u>It has to be
71      * defined with the non generic (typically final) sub-classes</u>.

```

```

70 * <br><br>
71 * For a given non generic sub-class <i>myNonGenericSubclass</i>, a typical
72 * definition of {@link Lattice#instance\(\) } is as follows:
73 * <br><br>
74 * <font color="#004488"><code>
75 * {@code @Override}
76 * <br>
77 * public myNonGenericSubclass instance() { return new myNonGenericSubclass(); }
78 * </code></font>
79 *
80 */
81 @Override
82 public finalFreeboolean instance() { return new finalFreeboolean(); }
83 }

```

Source Code: finalOpenhyperpowerset.java

```

1  /*
2  *   finalOpenhyperpowerset.java : part of package RefereeToolbox;
3  *   Implementation of open hyperpowerset.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * Final implementation of class {@link Openhyperpowerset }. This class is not ←
30 * generic, and
31 * thus, allows and needs instantiation. The method {@link finalOpenhyperpowerset#←
32 * instance() }
33 * is implemented.
34 *
35 * @author   <A href="http://email.fredericdambreville.com">Frédéric ←
36 *           Dambreville</A>
37 *
38 *
39 * <BR><BR><table border='1' cellPadding='4'><tr><td>
40 * <font color="#008000" style="font-family: georgia">
41 *   Copyright (c) 2010 Frédéric Dambreville<BR>
42 * <BR>
43 *   RefereeToolbox is free software: you can redistribute it and/or modify
44 *   it under the terms of the GNU General Public License as published by
45 *   the Free Software Foundation, either version 3 of the License, or
46 *   (at your option) any later version.<BR>
47 * <BR>
48 *   RefereeToolbox is distributed in the hope that it will be useful,
49 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
50 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
51 *   GNU General Public License for more details.<BR>
52 * <BR>
53 *   You should have received a copy of the GNU General Public License
54 *   along with RefereeToolbox. If not, see
55 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
56 * </font></td></tr></table><BR>
57 *
58 */
59
60 public final class finalOpenhyperpowerset extends Openhyperpowerset<←
61     finalOpenhyperpowerset> {
62
63     ///////////////////////////////////////////:
64     // public part
65     //////////////////////////////////////
66
67 /**
68 * Create and return an instance of <i>this</i> (i.e. work like a <b>new</b> on
69 * the Class of <i>this</i>).
70 * N.B. {@link Lattice#instance() } cannot be defined
71 * for generic classes but <u>is necessary</u> for some methods. <u>It has to be

```

```

69 * defined with the non generic (typically final) sub-classes </u>.
70 * <br><br>
71 * For a given non generic sub-class <i>myNonGenericSubclass</i>, a typical
72 * definition of {<a href="#">@link Lattice#instance()</a>} is as follows:
73 * <br><br>
74 * <font color="#004488"><code>
75 * {<a href="#">@code @Override</a>
76 * <br>
77 * public myNonGenericSubclass instance() { return new myNonGenericSubclass(); }
78 * </code></font>
79 *
80 */
81 @Override
82 public finalOpenhyperpowerset instance() { return new finalOpenhyperpowerset()←
83 }

```

Source Code: finalPowerset.java

```

1  /*
2  *   finalPowerset.java : part of package RefereeToolbox; Implementation of
3  *   powerset .
4  *   ****
5  *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville
6  *
7  *   Author:   FrÃ©dÃ©ric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * Final implementation of class {@link Powerset }. This class is not generic, and
30 * thus, allows and needs instantiation. The method {@link finalPowerset#instance() }
31 * is implemented.
32 *
33 * @author   <A href="http://email.fredericdambreville.com">FrÃ©dÃ©ric ↵
34 *           Dambreville</A>
35 *
36 *
37 * <BR><BR><table border='1' cellPadding='4'><tr><td>
38 * <font color="#008000" style="font-family: georgia">
39 *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville<BR>
40 * <BR>
41 *   RefereeToolbox is free software: you can redistribute it and/or modify
42 *   it under the terms of the GNU General Public License as published by
43 *   the Free Software Foundation, either version 3 of the License, or
44 *   (at your option) any later version.<BR>
45 * <BR>
46 *   RefereeToolbox is distributed in the hope that it will be useful,
47 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
48 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
49 *   GNU General Public License for more details.<BR>
50 * <BR>
51 *   You should have received a copy of the GNU General Public License
52 *   along with RefereeToolbox. If not, see
53 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
54 * </font></td></tr></table><BR>
55 *
56 */
57 public final class finalPowerset extends Powerset<finalPowerset> {
58
59     ///////////////////////////////////////////:
60     // public part
61     //////////////////////////////////////
62
63
64 /**
65 * Create and return an instance of <i>this</i> (i.e. work like a <b>new</b> on
66 * the Class of <i>this</i>).
67 * N.B. {@link Lattice#instance() } cannot be defined
68 * for generic classes but <u>is necessary</u> for some methods. <u>It has to be
69 * defined with the non generic (typically final) sub-classes</u>.
70 * <br><br>

```

```

71 * For a given non generic sub-class <i>myNonGenericSubclass</i>, a typical
72 * definition of {@link Lattice#instance\(\) } is as follows:
73 * <br><br>
74 * <font color="#004488"><code>
75 * {@code @Override}
76 * <br>
77 * public myNonGenericSubclass instance() { return new myNonGenericSubclass(); }
78 * </code></font>
79 *
80 */
81 @Override
82 public final Powerset instance() { return new finalPowerset(); }
83 }

```

Source Code: finalRefereeFuserRTS_Closedhyperpowerset.java

```

1  /*
2  *   finalRefereeFuserRTS_Closedhyperpowerset.java : part of package
3  *   RefereeToolbox; Implementation of fuser based on referee function.
4  *   ****
5  *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville
6  *
7  *   Author:   FrÃ©dÃ©ric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * A final instance of {@link RefereeFuserRTS } specialized for
30 * Lattice structures typed {@link finalClosedhyperpowerset }.
31 * An instantiation method {@link finalRefereeFuserRTS_Closedhyperpowerset#instance()} is
32 * implemented for this non generic class.
33 *
34 * @author      <A href="http://email.fredericdambreville.com">FrÃ©dÃ©ric ↵
35 *              Dambreville</A>
36 *
37 *
38 * <BR><BR><table border='1' cellPadding='4'><tr><td>
39 * <font color="#008000" style="font-family: georgia">
40 *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville<BR>
41 * <BR>
42 *   RefereeToolbox is free software: you can redistribute it and/or modify
43 *   it under the terms of the GNU General Public License as published by
44 *   the Free Software Foundation, either version 3 of the License, or
45 *   (at your option) any later version.<BR>
46 * <BR>
47 *   RefereeToolbox is distributed in the hope that it will be useful,
48 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
49 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
50 *   GNU General Public License for more details.<BR>
51 * <BR>
52 *   You should have received a copy of the GNU General Public License
53 *   along with RefereeToolbox. If not, see
54 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
55 * </font></td></tr></table><BR>
56 *
57 */
58 public class finalRefereeFuserRTS_Closedhyperpowerset extends RefereeFuserRTS<↵
59     finalClosedhyperpowerset ,
60                                     finalRefereeFuserRTS_Closedhyperpowerset ↵
61     > {
62
63     ///////////////////////////////////////////:
64     // public part
65     //////////////////////////////////////
66
67 /**
68 * Create and return an instance of <i>this</i> (i.e. work like a <b>new</b> on
69 * the Class of <i>this</i>).
70 * N.B. {@link BasicBeliefAssignment#instance()} cannot be defined for generic

```

```

69 * classes but <u>is necessary</u> for some methods. <u>It has to be defined with
70 * the non generic (typically final) sub-classes</u>.
71 * <br><br>
72 * For a given non generic sub-class <i>myNonGenericSubclass</i>, a typical
73 * definition of {<a href="#">@link BasicBeliefAssignment#instance()</a> } is as follows:
74 * <br><br>
75 * <font color="#004488"><code>
76 * {<code> @Override}
77 * <br>
78 * public myNonGenericSubclass instance() { return new myNonGenericSubclass(); }
79 * </code></font>
80 *
81 */
82 @Override
83 public final RefereeFuserRTS_Closedhyperpowerset instance() { return new ↵
      final RefereeFuserRTS_Closedhyperpowerset(); }
84
85 }

```

Source Code: finalRefereeFuserRTS_Freeboolean.java

```

1  /*
2  *   finalRefereeFuserRTS_Freeboolean.java : part of package RefereeToolbox;
3  *   Implementation of fuser based on referee function.
4  *   ****
5  *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville
6  *
7  *   Author:   FrÃ©dÃ©ric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * A final instance of {@link RefereeFuserRTS } specialized for
30 * Lattice structures typed {@link finalFreeboolean }.
31 * An instantiation method {@link finalRefereeFuserRTS_Freeboolean#instance() } is
32 * implemented for this non generic class.
33 *
34 * @author   <A href="http://email.fredericdambreville.com">FrÃ©dÃ©ric ↵
35 *           Dambreville</A>
36 *
37 *
38 * <BR><BR><table border='1' cellPadding='4'><tr><td>
39 * <font color="#008000" style="font-family: georgia">
40 *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville<BR>
41 * <BR>
42 *   RefereeToolbox is free software: you can redistribute it and/or modify
43 *   it under the terms of the GNU General Public License as published by
44 *   the Free Software Foundation, either version 3 of the License, or
45 *   (at your option) any later version.<BR>
46 * <BR>
47 *   RefereeToolbox is distributed in the hope that it will be useful,
48 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
49 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
50 *   GNU General Public License for more details.<BR>
51 * <BR>
52 *   You should have received a copy of the GNU General Public License
53 *   along with RefereeToolbox. If not, see
54 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
55 * </font></td></tr></table><BR>
56 *
57 */
58 public class finalRefereeFuserRTS_Freeboolean extends RefereeFuserRTS<↵
59     finalFreeboolean,
60                                     finalRefereeFuserRTS_Freeboolean ↵
61     > {
62
63     ///////////////////////////////////////////:
64     // public part
65     //////////////////////////////////////
66
67 /**
68 * Create and return an instance of <i>this</i> (i.e. work like a <b>new</b> on
69 * the Class of <i>this</i>).
70 * N.B. {@link BasicBeliefAssignment#instance() } cannot be defined for generic
71 * classes but <u>is necessary</u> for some methods. <u>It has to be defined with

```

```

70 * the non generic (typically final) sub-classes</u>.
71 * <br><br>
72 * For a given non generic sub-class <i>myNonGenericSubclass</i>, a typical
73 * definition of {@link BasicBeliefAssignment#instance\(\) } is as follows:
74 * <br><br>
75 * <font color="#004488"><code>
76 * {@code @Override}
77 * <br>
78 * public myNonGenericSubclass instance() { return new myNonGenericSubclass(); }
79 * </code></font>
80 *
81 */
82 @Override
83 public finalRefereeFuserRTS_Freeboolean instance() { return new ↵
84     finalRefereeFuserRTS_Freeboolean(); }

```

Source Code: finalRefereeFuserRTS_Openhyperpowerset.java

```

1  /*
2  *   finalRefereeFuserRTS_Openhyperpowerset.java : part of package
3  *   RefereeToolbox; Implementation of fuser based on referee function.
4  *   ****
5  *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville
6  *
7  *   Author:   FrÃ©dÃ©ric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * A final instance of {@link RefereeFuserRTS } specialized for
30 * Lattice structures typed {@link finalOpenhyperpowerset }.
31 * An instantiation method {@link finalRefereeFuserRTS_Openhyperpowerset#instance}
32 * () } is
33 * implemented for this non generic class.
34 *
35 * @author   <A href="http://email.fredericdambreville.com">FrÃ©dÃ©ric ↵
36 *           Dambreville</A>
37 *
38 * <BR><BR><table border='1' cellPadding='4'><tr><td>
39 * <font color="#008000" style="font-family: georgia">
40 *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville<BR>
41 * <BR>
42 *   RefereeToolbox is free software: you can redistribute it and/or modify
43 *   it under the terms of the GNU General Public License as published by
44 *   the Free Software Foundation, either version 3 of the License, or
45 *   (at your option) any later version.<BR>
46 * <BR>
47 *   RefereeToolbox is distributed in the hope that it will be useful,
48 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
49 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
50 *   GNU General Public License for more details.<BR>
51 * <BR>
52 *   You should have received a copy of the GNU General Public License
53 *   along with RefereeToolbox. If not, see
54 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
55 * </font></td></tr></table><BR>
56 *
57 */
58 public class finalRefereeFuserRTS_Openhyperpowerset extends RefereeFuserRTS<↵
59     finalOpenhyperpowerset ,
60                                     finalRefereeFuserRTS_Openhyperpowerset ↵
61     > {
62
63     ///////////////////////////////////////////:
64     // public part
65     //////////////////////////////////////
66
67 /**
68 * Create and return an instance of <i>this</i> (i.e. work like a <b>new</b> on
69 * the Class of <i>this</i>).
70 * N.B. {@link BasicBeliefAssignment#instance()} cannot be defined for generic

```

```

69 * classes but <u>is necessary</u> for some methods. <u>It has to be defined with
70 * the non generic (typically final) sub-classes</u>.
71 * <br><br>
72 * For a given non generic sub-class <i>myNonGenericSubclass</i>, a typical
73 * definition of {<a href="#">@link BasicBeliefAssignment#instance()</a> } is as follows:
74 * <br><br>
75 * <font color="#004488"><code>
76 * {<code> @Override
77 * <br>
78 * public myNonGenericSubclass instance() { return new myNonGenericSubclass(); }
79 * </code></font>
80 *
81 */
82 @Override
83 public final RefereeFuserRTS_Openhyperpowerset instance() { return new ↵
84     final RefereeFuserRTS_Openhyperpowerset(); }

```

Source Code: finalRefereeFuserRTS_Powerset.java

```

1  /*
2  *   finalRefereeFuserRTS_Powerset.java : part of package RefereeToolbox;
3  *   Implementation of fuser based on referee function.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * A final instance of {@link RefereeFuserRTS } specialized for
30 * Lattice structures typed {@link finalPowerset }.
31 * An instantiation method {@link finalRefereeFuserRTS_Powerset#instance() } is
32 * implemented for this non generic class.
33 *
34 * @author   <A href="http://email.fredericdambreville.com">Frédéric ↵
35 *           Dambreville</A>
36 *
37 *
38 * <BR><BR><table border='1' cellPadding='4'><tr><td>
39 * <font color="#008000" style="font-family: georgia">
40 * Copyright (c) 2010 Frédéric Dambreville<BR>
41 * <BR>
42 * RefereeToolbox is free software: you can redistribute it and/or modify
43 * it under the terms of the GNU General Public License as published by
44 * the Free Software Foundation, either version 3 of the License, or
45 * (at your option) any later version.<BR>
46 * <BR>
47 * RefereeToolbox is distributed in the hope that it will be useful,
48 * but WITHOUT ANY WARRANTY; without even the implied warranty of
49 * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
50 * GNU General Public License for more details.<BR>
51 * <BR>
52 * You should have received a copy of the GNU General Public License
53 * along with RefereeToolbox. If not, see
54 * <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
55 * </font></td></tr></table><BR>
56 *
57 */
58 public class finalRefereeFuserRTS_Powerset extends RefereeFuserRTS<finalPowerset ,
59                                                     finalRefereeFuserRTS_Powerset ↵
60                                                     > {
61
62     ///////////////////////////////////////////:
63     // public part
64     //////////////////////////////////////////
65
66 /**
67 * Create and return an instance of <i>this</i> (i.e. work like a <b>new</b> on
68 * the Class of <i>this</i>).
69 * N.B. {@link BasicBeliefAssignment#instance() } cannot be defined for generic
70 * classes but <u>is necessary</u> for some methods. <u>It has to be defined with
71 * the non generic (typically final) sub-classes</u>.

```

```

71 * <br><br>
72 * For a given non generic sub-class <i>myNonGenericSubclass</i>, a typical
73 * definition of { @link BasicBeliefAssignment#instance() } is as follows:
74 * <br><br>
75 * <font color="#004488"><code>
76 * { @code @Override}
77 * <br>
78 * public myNonGenericSubclass instance() { return new myNonGenericSubclass(); }
79 * </code></font>
80 *
81 */
82 @Override
83 public finalRefereeFuserRTS_Powerset instance() { return new ←
      finalRefereeFuserRTS_Powerset(); }
84 }

```

Source Code: finalRefereeFuserRTS_Superpowerset.java

```

1  /*
2  *   finalRefereeFuserRTS_Superpowerset.java : part of package RefereeToolbox;
3  *   Implementation of fuser based on referee function.
4  *   ****
5  *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville
6  *
7  *   Author:   FrÃ©dÃ©ric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * A final instance of {@link RefereeFuserRTS } specialized for
30 * Lattice structures typed {@link finalSuperpowerset }.
31 * An instantiation method {@link finalRefereeFuserRTS_Superpowerset#instance() } ←
32 * is
33 * implemented for this non generic class.
34 *
35 * @author   <A href="http://email.fredericdambreville.com">FrÃ©dÃ©ric ←
36 *           Dambreville</A>
37 *
38 * <BR><BR><table border='1' cellPadding='4'><tr><td>
39 * <font color="#008000" style="font-family: georgia">
40 *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville<BR>
41 * <BR>
42 *   RefereeToolbox is free software: you can redistribute it and/or modify
43 *   it under the terms of the GNU General Public License as published by
44 *   the Free Software Foundation, either version 3 of the License, or
45 *   (at your option) any later version.<BR>
46 * <BR>
47 *   RefereeToolbox is distributed in the hope that it will be useful,
48 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
49 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
50 *   GNU General Public License for more details.<BR>
51 * <BR>
52 *   You should have received a copy of the GNU General Public License
53 *   along with RefereeToolbox. If not, see
54 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
55 * </font></td></tr></table><BR>
56 *
57 */
58 public class finalRefereeFuserRTS_Superpowerset extends RefereeFuserRTS<←
59     finalSuperpowerset ,
60                                     finalRefereeFuserRTS_Superpowerset ←
61                                     > {
62
63     ///////////////////////////////////////////:
64     // public part
65     //////////////////////////////////////////
66
67 /**
68 * Create and return an instance of <i>this</i> (i.e. work like a <b>new</b> on
69 * the Class of <i>this</i>).

```

```

69 * N.B. {@link BasicBeliefAssignment#instance() } cannot be defined for generic
70 * classes but <u>is necessary</u> for some methods. <u>It has to be defined with
71 * the non generic (typically final) sub-classes</u>.
72 * <br><br>
73 * For a given non generic sub-class <i>myNonGenericSubclass</i>, a typical
74 * definition of {@link BasicBeliefAssignment#instance() } is as follows:
75 * <br><br>
76 * <font color="#004488"><code>
77 * {@code @Override}
78 * <br>
79 * public myNonGenericSubclass instance() { return new myNonGenericSubclass(); }
80 * </code></font>
81 *
82 */
83 @Override
84 public finalRefereeFuserRTS_Superpowerset instance() { return new ↵
85     finalRefereeFuserRTS_Superpowerset(); }

```

Source Code: finalRefereeSampler_Closedhyperpowerset.java

```

1  /*
2  *   finalRefereeSampler_Closedhyperpowerset.java : part of package
3  *   RefereeToolbox; Implement sampled fuser based on referee function.
4  *   ****
5  *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville
6  *
7  *   Author:   FrÃ©dÃ©ric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * A final instance of {@link RefereeSampler} specialized for
30 * Lattice structures typed {@link finalClosedhyperpowerset}.
31 * An instantiation method {@link finalRefereeSampler_Closedhyperpowerset#instance() ←
32 *   ()} is
33 * implemented for this non generic class.
34 *
35 * @author   <A href="http://email.fredericdambreville.com">FrÃ©dÃ©ric ←
36 *   Dambreville</A>
37 *
38 * <BR><BR><table border='1' cellPadding='4'><tr><td>
39 * <font color="#008000" style="font-family: georgia">
40 *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville<BR>
41 * <BR>
42 *   RefereeToolbox is free software: you can redistribute it and/or modify
43 *   it under the terms of the GNU General Public License as published by
44 *   the Free Software Foundation, either version 3 of the License, or
45 *   (at your option) any later version.<BR>
46 * <BR>
47 *   RefereeToolbox is distributed in the hope that it will be useful,
48 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
49 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
50 *   GNU General Public License for more details.<BR>
51 * <BR>
52 *   You should have received a copy of the GNU General Public License
53 *   along with RefereeToolbox. If not, see
54 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
55 * </font></td></tr></table><BR>
56 *
57 */
58 public class finalRefereeSampler_Closedhyperpowerset extends RefereeSampler<←
59     finalClosedhyperpowerset,
60                                     finalRefereeSampler_Closedhyperpowerset ←
61                                     >{
62
63     ///////////////////////////////////////////:
64     // public part
65     //////////////////////////////////////
66
67 /**
68 * Create and return an instance of <i>this</i> (i.e. work like a <b>new</b> on
69 * the Class of <i>this</i>).
70 * N.B. {@link BasicBeliefAssignment#instance()} cannot be defined for generic

```

```

69 * classes but <u>is necessary</u> for some methods. <u>It has to be defined with
70 * the non generic (typically final) sub-classes</u>.
71 * <br><br>
72 * For a given non generic sub-class <i>myNonGenericSubclass</i>, a typical
73 * definition of {<a href="#">BasicBeliefAssignment#instance()</a> } is as follows:
74 * <br><br>
75 * <font color="#004488"><code>
76 * {<code> @Override
77 * <br>
78 * public myNonGenericSubclass instance() { return new myNonGenericSubclass(); }
79 * </code></font>
80 *
81 */
82 @Override
83 public finalRefereeSampler_Closedhyperpowerset instance() { return new ↵
      finalRefereeSampler_Closedhyperpowerset(); }
84
85 }

```

Source Code: finalRefereeSampler_Freeboolean.java

```

1  /*
2  *   finalRefereeSampler_Freeboolean.java : part of package RefereeToolbox;
3  *   Implement sampled fuser based on referee function.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * A final instance of {@link RefereeSampler} specialized for
30 * Lattice structures typed {@link finalFreeboolean}.
31 * An instantiation method {@link finalRefereeSampler_Freeboolean#instance()} is
32 * implemented for this non generic class.
33 *
34 * @author   <A href="http://email.fredericdambreville.com">Frédéric ↵
35 *           Dambreville</A>
36 *
37 *
38 * <BR><BR><table border='1' cellPadding='4'><tr><td>
39 * <font color="#008000" style="font-family: georgia">
40 *   Copyright (c) 2010 Frédéric Dambreville<BR>
41 * <BR>
42 *   RefereeToolbox is free software: you can redistribute it and/or modify
43 *   it under the terms of the GNU General Public License as published by
44 *   the Free Software Foundation, either version 3 of the License, or
45 *   (at your option) any later version.<BR>
46 * <BR>
47 *   RefereeToolbox is distributed in the hope that it will be useful,
48 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
49 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
50 *   GNU General Public License for more details.<BR>
51 * <BR>
52 *   You should have received a copy of the GNU General Public License
53 *   along with RefereeToolbox. If not, see
54 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
55 * </font></td></tr></table><BR>
56 *
57 */
58 public class finalRefereeSampler_Freeboolean extends RefereeSampler<↵
59     finalFreeboolean,
60                                     finalRefereeSampler_Freeboolean>↵
61     {
62         //////////////////////////////////////////:
63         // public part
64         //////////////////////////////////////////
65
66 /**
67 * Create and return an instance of <i>this</i> (i.e. work like a <b>new</b> on
68 * the Class of <i>this</i>).
69 * N.B. {@link BasicBeliefAssignment#instance()} cannot be defined for generic
70 * classes but <u>is necessary</u> for some methods. <u>It has to be defined with

```

```

70 * the non generic (typically final) sub-classes</u>.
71 * <br><br>
72 * For a given non generic sub-class <i>myNonGenericSubclass</i>, a typical
73 * definition of {@link BasicBeliefAssignment#instance\(\) } is as follows:
74 * <br><br>
75 * <font color="#004488"><code>
76 * {@code @Override}
77 * <br>
78 * public myNonGenericSubclass instance() { return new myNonGenericSubclass(); }
79 * </code></font>
80 *
81 */
82 @Override
83 public finalRefereeSampler_Freeboolean instance() { return new ←
      finalRefereeSampler_Freeboolean(); }
84 }

```

Source Code: finalRefereeSampler_Openhyperpowerset.java

```

1  /*
2  *   finalRefereeSampler_Openhyperpowerset.java : part of package
3  *   RefereeToolbox; Implement sampled fuser based on referee function.
4  *   ****
5  *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville
6  *
7  *   Author:   FrÃ©dÃ©ric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * A final instance of {@link RefereeSampler} specialized for
30 * Lattice structures typed {@link finalOpenhyperpowerset}.
31 * An instantiation method {@link finalRefereeSampler_Openhyperpowerset#instance()} ←
32 *   is
33 * implemented for this non generic class.
34 *
35 * @author   <A href="http://email.fredericdambreville.com">FrÃ©dÃ©ric ←
36 *   Dambreville</A>
37 *
38 * <BR><BR><table border='1' cellPadding='4'><tr><td>
39 * <font color="#008000" style="font-family: georgia">
40 *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville<BR>
41 * <BR>
42 *   RefereeToolbox is free software: you can redistribute it and/or modify
43 *   it under the terms of the GNU General Public License as published by
44 *   the Free Software Foundation, either version 3 of the License, or
45 *   (at your option) any later version.<BR>
46 * <BR>
47 *   RefereeToolbox is distributed in the hope that it will be useful,
48 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
49 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
50 *   GNU General Public License for more details.<BR>
51 * <BR>
52 *   You should have received a copy of the GNU General Public License
53 *   along with RefereeToolbox. If not, see
54 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
55 * </font></td></tr></table><BR>
56 *
57 */
58 public class finalRefereeSampler_Openhyperpowerset extends RefereeSampler<←
59     finalOpenhyperpowerset,
60                                     finalRefereeSampler_Openhyperpowerset ←
61                                     >{
62
63     ///////////////////////////////////////////:
64     // public part
65     //////////////////////////////////////
66
67 /**
68 * Create and return an instance of <i>this</i> (i.e. work like a <b>new</b> on
69 * the Class of <i>this</i>).
70 * N.B. {@link BasicBeliefAssignment#instance()} cannot be defined for generic

```

```

69 * classes but <u>is necessary</u> for some methods. <u>It has to be defined with
70 * the non generic (typically final) sub-classes</u>.
71 * <br><br>
72 * For a given non generic sub-class <i>myNonGenericSubclass</i>, a typical
73 * definition of {<a href="#">BasicBeliefAssignment#instance()</a> } is as follows:
74 * <br><br>
75 * <font color="#004488"><code>
76 * {<code> @Override}
77 * <br>
78 * public myNonGenericSubclass instance() { return new myNonGenericSubclass(); }
79 * </code></font>
80 *
81 */
82 @Override
83 public final RefereeSampler_Openhyperpowerset instance() { return new ↵
84     finalRefereeSampler_Openhyperpowerset(); }
85 }

```

Source Code: finalRefereeSampler_Powerset.java

```

1  /*
2  *   finalRefereeSampler_Powerset.java : part of package RefereeToolbox;
3  *   Implement sampled fuser based on referee function.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * A final instance of {@link RefereeSampler} specialized for
30 * Lattice structures typed {@link finalPowerset}.
31 * An instantiation method {@link finalRefereeSampler_Powerset#instance()} is
32 * implemented for this non generic class.
33 *
34 * @author   <A href="http://email.fredericdambreville.com">Frédéric ↵
35 *           Dambreville</A>
36 *
37 *
38 * <BR><BR><table border='1' cellPadding='4'><tr><td>
39 * <font color="#008000" style="font-family: georgia">
40 *   Copyright (c) 2010 Frédéric Dambreville<BR>
41 * <BR>
42 *   RefereeToolbox is free software: you can redistribute it and/or modify
43 *   it under the terms of the GNU General Public License as published by
44 *   the Free Software Foundation, either version 3 of the License, or
45 *   (at your option) any later version.<BR>
46 * <BR>
47 *   RefereeToolbox is distributed in the hope that it will be useful,
48 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
49 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
50 *   GNU General Public License for more details.<BR>
51 * <BR>
52 *   You should have received a copy of the GNU General Public License
53 *   along with RefereeToolbox. If not, see
54 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
55 * </font></td></tr></table><BR>
56 *
57 */
58 public class finalRefereeSampler_Powerset extends RefereeSampler<finalPowerset,
59                                           finalRefereeSampler_Powerset>{
60
61     ///////////////////////////////////////////:
62     // public part
63     //////////////////////////////////////
64
65 /**
66 * Create and return an instance of <i>this</i> (i.e. work like a <b>new</b> on
67 * the Class of <i>this</i>).
68 * N.B. {@link BasicBeliefAssignment#instance()} cannot be defined for generic
69 * classes but <u>is necessary</u> for some methods. <u>It has to be defined with
70 * the non generic (typically final) sub-classes</u>.
71 * <br><br>

```

```

72 * For a given non generic sub-class <i>myNonGenericSubclass</i>, a typical
73 * definition of {@link BasicBeliefAssignment#instance\(\) } is as follows:
74 * <br><br>
75 * <font color="#004488"><code>
76 * {@code @Override}
77 * <br>
78 * public myNonGenericSubclass instance() { return new myNonGenericSubclass(); }
79 * </code></font>
80 *
81 */
82 @Override
83 public finalRefereeSampler_Powerset instance() { return new ↵
      finalRefereeSampler_Powerset(); }
84
85 }

```

Source Code: finalRefereeSampler_Superpowerset.java

```

1  /*
2  *   finalRefereeSampler_Superpowerset.java : part of package RefereeToolbox;
3  *   Implement sampled fuser based on referee function.
4  *   ****
5  *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville
6  *
7  *   Author:   FrÃ©dÃ©ric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * A final instance of {@link RefereeSampler} specialized for
30 * Lattice structures typed {@link finalSuperpowerset}.
31 * An instantiation method {@link finalRefereeSampler_Superpowerset#instance()} ←
32 * is
33 * implemented for this non generic class.
34 *
35 * @author   <A href="http://email.fredericdambreville.com">FrÃ©dÃ©ric ←
36 *           Dambreville</A>
37 *
38 * <BR><table border='1' cellPadding='4'><tr><td>
39 * <font color="#008000" style="font-family: georgia">
40 *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville<BR>
41 * <BR>
42 *   RefereeToolbox is free software: you can redistribute it and/or modify
43 *   it under the terms of the GNU General Public License as published by
44 *   the Free Software Foundation, either version 3 of the License, or
45 *   (at your option) any later version.<BR>
46 * <BR>
47 *   RefereeToolbox is distributed in the hope that it will be useful,
48 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
49 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
50 *   GNU General Public License for more details.<BR>
51 * <BR>
52 *   You should have received a copy of the GNU General Public License
53 *   along with RefereeToolbox. If not, see
54 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
55 * </font></td></tr></table><BR>
56 *
57 */
58 public class finalRefereeSampler_Superpowerset extends RefereeSampler<←
59     finalSuperpowerset,
60                                     finalRefereeSampler_Superpowerset ←
61                                     >{
62
63     //////////////////////////////////////:
64     // public part
65     //////////////////////////////////////
66
67 /**
68 * Create and return an instance of <i>this</i> (i.e. work like a <b>new</b> on
69 * the Class of <i>this</i>).

```

```

69 * N.B. {@link BasicBeliefAssignment#instance() } cannot be defined for generic
70 * classes but <u>is necessary</u> for some methods. <u>It has to be defined with
71 * the non generic (typically final) sub-classes</u>.
72 * <br><br>
73 * For a given non generic sub-class <i>myNonGenericSubclass</i>, a typical
74 * definition of {@link BasicBeliefAssignment#instance() } is as follows:
75 * <br><br>
76 * <font color="#004488"><code>
77 * {@code @Override}
78 * <br>
79 * public myNonGenericSubclass instance() { return new myNonGenericSubclass(); }
80 * </code></font>
81 *
82 */
83 @Override
84 public finalRefereeSampler_Superpowerset instance() { return new ↵
85     finalRefereeSampler_Superpowerset(); }
86 }

```

Source Code: finalSuperpowerset.java

```

1  /*
2  *   finalSuperpowerset.java : part of package RefereeToolbox; Implementation
3  *   of superpowerset.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * Final implementation of class {@link Superpowerset }. This class is not generic ←
30 * , and
31 * thus, allows and needs instantiation. The method {@link finalSuperpowerset# ←
32 * instance() }
33 * is implemented.
34 *
35 * @author   <A href="http://email.fredericdambreville.com">Frédéric ←
36 *           Dambreville</A>
37 *
38 *
39 * <BR><BR><table border='1' cellPadding='4'><tr><td>
40 * <font color="#008000" style="font-family: georgia">
41 *   Copyright (c) 2010 Frédéric Dambreville<BR>
42 * <BR>
43 *   RefereeToolbox is free software: you can redistribute it and/or modify
44 *   it under the terms of the GNU General Public License as published by
45 *   the Free Software Foundation, either version 3 of the License, or
46 *   (at your option) any later version.<BR>
47 * <BR>
48 *   RefereeToolbox is distributed in the hope that it will be useful,
49 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
50 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
51 *   GNU General Public License for more details.<BR>
52 * <BR>
53 *   You should have received a copy of the GNU General Public License
54 *   along with RefereeToolbox. If not, see
55 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
56 * </font></td></tr></table><BR>
57 *
58 */
59
60 public final class finalSuperpowerset extends Superpowerset<finalSuperpowerset> {
61
62     ///////////////////////////////////////////:
63     // public part
64     //////////////////////////////////////////
65
66 /**
67 * Create and return an instance of <i>this</i> (i.e. work like a <b>new</b> on
68 * the Class of <i>this</i>).
69 * N.B. {@link Lattice#instance() } cannot be defined
70 * for generic classes but <u>is necessary</u> for some methods. <u>It has to be
71 * defined with the non generic (typically final) sub-classes</u>.

```

```

70 * <br><br>
71 * For a given non generic sub-class <i>myNonGenericSubclass</i>, a typical
72 * definition of {@link Lattice#instance\(\) } is as follows:
73 * <br><br>
74 * <font color="#004488"><code>
75 * {@code @Override}
76 * <br>
77 * public myNonGenericSubclass instance() { return new myNonGenericSubclass(); }
78 * </code></font>
79 *
80 */
81 @Override
82 public final Superpowerset instance() { return new finalSuperpowerset(); }
83 }

```

Source Code: Freeboolean.java

```

1  /*
2  *   Freeboolean.java : part of package RefereeToolbox; Implementation of Free
3  *   Boolean algebra.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * Implementation of a Free Boolean structure by means of an array of {@code long}
30 *   }.
31 * Structural methods are redefined, {@link Freeboolean#size(int) } and
32 *   {@link Freeboolean#size(RefereeToolbox.Freeboolean) },
33 * and the atomic are defined {@link Freeboolean#atomic(int) }.
34 * The AND and OR operators are inherited from the operators {@code & } and {@code ←
35 *   | }
36 * working on {@code long}.
37 * zero is defined by zeroing all bits. one is defined by setting to
38 * 1 all active bits; the right bits of the {@code long } vector may be inactive,
39 * depending on the size of the Lattice.
40 * The complement/cocomplement operators are inherited from the operators {@code ~←
41 *   }
42 * working on {@code long}; exceeding bits are masked by a AND with one.
43 *
44 * @author   <A href="http://email.fredericdambreville.com">Frédéric ←
45 *   Dambreville</A>
46 *
47 *
48 * <BR><table border='1' cellPadding='4'><tr><td>
49 * <font color="#008000" style="font-family: georgia">
50 *   Copyright (c) 2010 Frédéric Dambreville<BR>
51 * <BR>
52 *   RefereeToolbox is free software: you can redistribute it and/or modify
53 *   it under the terms of the GNU General Public License as published by
54 *   the Free Software Foundation, either version 3 of the License, or
55 *   (at your option) any later version.<BR>
56 * <BR>
57 *   RefereeToolbox is distributed in the hope that it will be useful,
58 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
59 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
60 *   GNU General Public License for more details.<BR>
61 * <BR>
62 *   You should have received a copy of the GNU General Public License
63 *   along with RefereeToolbox. If not, see
64 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
65 * </font></td></tr></table><BR>
66 *
67 */
68 public class Freeboolean<L extends Freeboolean<L>> extends ArrayBoolean<L>
69     implements GeneratedLattice<L> {

```

```

69     protected static int sizeMax=16;
70
71     protected int sizeFrame = -1; // undefined by default
72     protected int sizeSet=-1;
73
74
75     ///////////////////////////////////////////:
76     // public part
77     //////////////////////////////////////
78
79 /**
80  * Return the  $\langle i \rangle$  atomic proposition.
81  * For class {@link Freeboolean }, the  $\langle i \rangle$  atomic proposition
82  * is constituted by all  $\langle j \rangle$  bit stored in the
83  *  $\langle \text{long} \rangle$  array such that {@literal j & ( 1 << i ) } is non nul.
84  * <BR><BR>
85  * return  $\langle i \rangle$  null if  $\langle i \rangle$  is out of bounds.
86  */
87     public L atomic(int i) {
88         if ((i>=sizeFrame) || (i<0)) {
89             return null;
90         }
91         int j , index;
92         switch(i) {
93             case 0: for(index=0;index<=size_mem_1;index++)
94                 _memory[index]=0xaaaaaaaaaaaaaaaaal; break;
95             case 1: for(index=0;index<=size_mem_1;index++)
96                 _memory[index]=0xcccccccccccccccl; break;
97             case 2: for(index=0;index<=size_mem_1;index++)
98                 _memory[index]=0xf0f0f0f0f0f0f0f0l; break;
99             case 3: for(index=0;index<=size_mem_1;index++)
100                 _memory[index]=0xff00ff00ff00ff00l; break;
101             case 4: for(index=0;index<=size_mem_1;index++)
102                 _memory[index]=0xffff0000ffff0000l; break;
103             case 5: for(index=0;index<=size_mem_1;index++)
104                 _memory[index]=0xffffffff00000000l; break;
105             default: j=1<<(i-6);
106                     for(index=0;index<=size_mem_1;index++) {
107                         if ((index&j)!=0) _memory[index]=0xfffffffffffffl;
108                         else _memory[index]=0x0000000000000000l;
109                     }
110                     break;
111         }
112         if (sizeFrame<6) _memory[0]&=highest_long_one;
113         return (L) this;
114     }
115
116 /**
117  * Set or return the size of  $\langle i \rangle$  this.
118  * Diffeerent cases are considered:
119  * <br><br>
120  *  $\langle i \rangle$  newSize<0 — The size of  $\langle i \rangle$  this is kept unchanged, and this size
121  * is returned by the method.
122  * <br>
123  *  $\langle i \rangle$  newSize>=0 — If  $\langle i \rangle$  newSize is a valid new size, then the size of
124  *  $\langle i \rangle$  this is changed to  $\langle i \rangle$  newSize, and this size is returned by the  $\leftarrow$ 
125  * method.
126  * <br><br>
127  * Valid new size is such that  $\langle i \rangle 0 \leq \text{newSize} \leq \text{sizeMax}$ . By default,
128  *  $\langle i \rangle \{ \text{@link Freeboolean\#sizeMax} \} = 16$ .
129  * <br>
130  * For class {@link Freeboolean },  $\langle i \rangle$  newSize is stored in protected variable
131  *  $\langle i \rangle$  sizeFrame and is equals to the number of atomic propositions (possibly  $\leftarrow$ 
132  * 0).
133  * The number of activated bits stored in the  $\langle i \rangle$  long array is equal to  $\langle i \rangle 2^{\text{newSize}}$ .
134  * <br><br>
135  * N.B. 1. By default, this method is not implemented by {@link Lattice } directly  $\leftarrow$ 
136  * ,
137  * but by its subclasses.
138  * <br>
139  * N.B. 2. The size is not necessarily the cardinal of the lattice, but may be
140  * instead the number of atomic propositions of the lattice.

```

```

140  *
141  */
142  @Override
143  public int size(int newSize) { // if newSize is possible, then change size to ←
    newSize
144      if ((newSize >= 0) && (newSize <= sizeMax)) {
145          sizeFrame = newSize;
146          sizeSet = (1 << sizeFrame);
147          size_mem_1 = (sizeSet - 1) / 64;
148          highest_long_one = sizeSet - 64 * size_mem_1;
149          highest_long_one = (((1L << (highest_long_one - 1)) - 1) << 1) + 1;
150          _memory = new long[size_mem_1 + 1];
151      }
152      return sizeFrame;
153  }
154
155  @Override
156  public L size(L input) {
157      size(input.size(-1));
158      return (L) this;
159  }
160
161  }

```

Source Code: GeneratedLattice.java

```

1  /*
2  *   GeneratedLattice.java : part of package RefereeToolbox; Interface for
3  *   generated lattice.
4  *   ****
5  *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville
6  *
7  *   Author:   FrÃ©dÃ©ric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * Contains methods for classes implementing Lattice structures with atomic
30 * elements, {@link #atomic(int) }. Atomics elements are generating elements wich ←
31 * are
32 * addressable by means of an index.
33 *
34 * @author   <A href="http://email.fredericdambreville.com">FrÃ©dÃ©ric ←
35 *           Dambreville</A>
36 *
37 * <BR><BR><table border='1' cellPadding='4'><tr><td>
38 * <font color="#008000" style="font-family: georgia">
39 * Copyright (c) 2010 FrÃ©dÃ©ric Dambreville<BR>
40 * <BR>
41 * RefereeToolbox is free software: you can redistribute it and/or modify
42 * it under the terms of the GNU General Public License as published by
43 * the Free Software Foundation, either version 3 of the License, or
44 * (at your option) any later version.<BR>
45 * <BR>
46 * RefereeToolbox is distributed in the hope that it will be useful,
47 * but WITHOUT ANY WARRANTY; without even the implied warranty of
48 * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
49 * GNU General Public License for more details.<BR>
50 * <BR>
51 * You should have received a copy of the GNU General Public License
52 * along with RefereeToolbox. If not, see
53 * <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
54 * </font></td></tr></table><BR>
55 *
56 */
57 interface GeneratedLattice<L> extends Lattice<L> {
58
59 /**
60 * Set <i>this</i> to the atomic proposition of index <i>i</i>.
61 * Index <i>i</i> ranges from first value <i>0</i>.
62 * <BR>
63 * N.B. It is necessary to call {@link Lattice#size } or
64 * {@link Lattice#size(java.lang.Object) } before any first use of this method.
65 *
66 */
67     L atomic(int i);
68
69 }

```

Source Code: Lattice.java

```

1  /*
2  *   Lattice.java : part of package RefereeToolbox; Interface for lattice.
3  *   ****
4  *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville
5  *
6  *   Author:   FrÃ©dÃ©ric Dambreville <http://email.fredericdambreville.com>
7  *
8  *   This file is part of RefereeToolbox.
9  *
10 *   RefereeToolbox is free software: you can redistribute it and/or modify
11 *   it under the terms of the GNU General Public License as published by
12 *   the Free Software Foundation, either version 3 of the License, or
13 *   (at your option) any later version.
14 *
15 *   RefereeToolbox is distributed in the hope that it will be useful,
16 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
17 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
18 *   GNU General Public License for more details.
19 *
20 *   You should have received a copy of the GNU General Public License
21 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
22 *   ****
23 */
24
25 package RefereeToolbox;
26
27 /**
28 * Contains the minimal methods for a class implementing a Lattice structure.
29 *
30 * @author      <A href="http://email.fredericdambreville.com">FrÃ©dÃ©ric ↵
31 *      Dambreville</A>
32 *
33 *
34 * <BR><BR><table border='1' cellPadding='4'><tr><td>
35 * <font color="#008000" style="font-family: georgia">
36 *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville<BR>
37 * <BR>
38 *   RefereeToolbox is free software: you can redistribute it and/or modify
39 *   it under the terms of the GNU General Public License as published by
40 *   the Free Software Foundation, either version 3 of the License, or
41 *   (at your option) any later version.<BR>
42 * <BR>
43 *   RefereeToolbox is distributed in the hope that it will be useful,
44 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
45 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
46 *   GNU General Public License for more details.<BR>
47 * <BR>
48 *   You should have received a copy of the GNU General Public License
49 *   along with RefereeToolbox. If not, see
50 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
51 * </font></td></tr></table><BR>
52 *
53 */
54 public interface Lattice<L> extends Comparable<L>, Cloneable {
55
56 /**
57 * Return a representation of the state of <i>this</i> printed as
58 * a String.
59 *
60 */
61 String state();
62
63 /**
64 * Set or return the size of <i>this</i>.
65 * Different cases are considered:
66 * <br><br>
67 * <i>newSize</i><0</i> — The size of <i>this</i> is kept unchanged, and this size
68 * is returned by the method.
69 * <br>
70 * <i>newSize>=0</i> — If <i>newSize</i> is a valid new size, then the size of
71 * <i>this</i> is changed to <i>newSize</i>, and this size is returned by the ↵

```

```

        method.
72 * <br><br>
73 * N.B. 1. By default, this method is not implemented by {@link Lattice } directly ←
74 * but by its subclasses.
75 * <br>
76 * N.B. 2. The size is not necessarily the cardinal of the lattice, but may be
77 * instead the number of atomic propositions of the lattice.
78 *
79 */
80 int size(int newSize);
81
82 /**
83 * Resize <i>this</i> at the same size than <i>input</i>.
84 *
85 */
86 L size(L input);
87
88 /**
89 * Do an exact copy of input into <i>this</i>.
90 *
91 */
92 L duplicate(L input);
93
94 /**
95 * Create and return an instance of <i>this</i> (i.e. work like a <b>new</b> on
96 * the Class of <i>this</i>). N.B. {@link Lattice#instance() } cannot be defined
97 * for generic classes but <u>is necessary</u> for some methods. <u>It has to be
98 * defined with the non generic (typically final) sub-classes</u>.
99 * <br><br>
100 * For a given non generic sub-class <i>myNonGenericSubclass</i>, a typical
101 * definition of {@link Lattice#instance() } is as follows:
102 * <br><br>
103 * <font color="#004488"><code>
104 * { @code @Override}
105 * <br>
106 * public myNonGenericSubclass instance() { return new myNonGenericSubclass(); }
107 * </code></font>
108 *
109 */
110 L instance();
111
112 /**
113 * Create and return an instance of <i>this</i> and resize it at the same size ←
114 * than <i>this</i>.
115 * This method is actually defined and make a call of {@link Lattice#instance() }.
116 * It does not need to be defined with the non generic sub-classes.
117 *
118 * @see Lattice#instance()
119 *
120 */
121 L instanceNsize();
122
123 /**
124 * Create a clone of <i>this</i>.
125 *
126 */
127 L clone();
128
129 /**
130 * Set <i>this</i> to zero, the neutral element for
131 * {@link Lattice#or(java.lang.Object, java.lang.Object) }.
132 * N.B. It is necessary to call {@link Lattice#size } or
133 * {@link Lattice#size(java.lang.Object) } before any first use of this
134 * method.
135 *
136 */
137 L zero();
138
139 /**
140 * Set <i>this</i> to one, the neutral element for
141 * {@link Lattice#and(java.lang.Object, java.lang.Object) }.
142 * N.B. It is necessary to call {@link Lattice#size } or
143 * {@link Lattice#size(java.lang.Object) } before any first use of this method.

```

```

143  *
144  */
145  L one();
146
147  /**
148  * Answer <i>true</i> if the proposition stored within <i>this</i> contains the
149  * proposition contained within <i>aProposition</i>. Answer <i>>false</i> otherwise↵
150  *
151  */
152  boolean contains(L aProposition);
153
154  /**
155  * Answer <i>true</i> if the proposition stored within <i>this</i> intersects the
156  * proposition contained within <i>aProposition</i> (<i>i.e.</i> the intersection
157  * of both propositions is not <i>zero</i>). Answer <i>>false</i> otherwise.
158  *
159  */
160  boolean intersects(L aProposition);
161
162  /**
163  * Compute the AND of <i>left</i> and <i>right</i> and store the result within <i>↵
    this</i>.
164  *
165  */
166  L and(L left, L right);
167
168  /**
169  * Compute the OR of <i>left</i> and <i>right</i> and store the result within <i>↵
    this</i>.
170  *
171  */
172  L or(L left, L right);
173
174  /**
175  * Compare <i>this</i> to <i>aProposition</i> and answer negative integer, zero,
176  * positive integer as <i>this</i> is less than, equal to, or greater than
177  * <i>aProposition</i>.
178  * This comparison is related to a total ordering of the proposition; <em>it is ↵
    not
179  * related to the partial order implied by the logical operators AND and OR.</em>
180  *
181  */
182  int compareTo(L aProposition);
183  }

```

Source Code: LatticeCommon.java

```

1  /*
2  *   LatticeCommon.java : part of package RefereeToolbox; Basical implementation
3  *   of lattice.
4  *   ****
5  *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville
6  *
7  *   Author:   FrÃ©dÃ©ric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * Basical implementation of the Latice structure
30 *
31 * @author   <A href="http://email.fredericdambreville.com">FrÃ©dÃ©ric ↵
32 *           Dambreville</A>
33 *
34 *
35 * <BR><BR><table border='1' cellPadding='4'><tr><td>
36 * <font color="#008000" style="font-family: georgia">
37 *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville<BR>
38 * <BR>
39 *   RefereeToolbox is free software: you can redistribute it and/or modify
40 *   it under the terms of the GNU General Public License as published by
41 *   the Free Software Foundation, either version 3 of the License, or
42 *   (at your option) any later version.<BR>
43 * <BR>
44 *   RefereeToolbox is distributed in the hope that it will be useful,
45 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
46 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
47 *   GNU General Public License for more details.<BR>
48 * <BR>
49 *   You should have received a copy of the GNU General Public License
50 *   along with RefereeToolbox. If not, see
51 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
52 * </font></td></tr></table><BR>
53 *
54 */
55 public class LatticeCommon<L extends LatticeCommon<L>>
56     implements Lattice<L> {
57
58     ///////////////////////////////////////////:
59     // public part
60     //////////////////////////////////////////
61
62     /**
63      * This method is not defined for class {@link LatticeCommon} and produces
64      * the String {@code "UNDEFINED" }.
65      * <BR><BR>
66      * <b>Documentation inherited from {@link Lattice }:</b><BR>
67      * {@inheritDoc}
68      */
69     public String state() {
70         return "UNDEFINED";
71     }

```

```

72
73
74 /**
75  * This method is not defined for class {@link LatticeCommon } and generates
76  * an error report and a code exit.
77  * <BR><BR>
78  * <b>Documentation inherited from {@link Lattice }:</b><BR>
79  * {@inheritDoc}
80  */
81 public L zero() {
82     System.err.println("Error :: "+this.getClass().getName() +
83         ".zero() is not implemented!");
84     System.err.println("Please implement instance() in your class with ↵
85         @Override");
86     System.exit(0);
87     return null;
88 }
89
90 /**
91  * This method is not defined for class {@link LatticeCommon } and generates
92  * an error report and a code exit.
93  * <BR><BR>
94  * <b>Documentation inherited from {@link Lattice }:</b><BR>
95  * {@inheritDoc}
96  */
97 public L one() {
98     System.err.println("Error :: "+this.getClass().getName() +
99         ".one() is not implemented!");
100     System.err.println("Please implement instance() in your class with ↵
101         @Override");
102     System.exit(0);
103     return null;
104 }
105
106 /**
107  * This method is not defined for class {@link LatticeCommon } and generates
108  * an error report and a code exit.
109  * <BR><BR>
110  * <b>Documentation inherited from {@link Lattice }:</b><BR>
111  * {@inheritDoc}
112  */
113 public L and(L left, L right) {
114     System.err.println("Error :: "+this.getClass().getName() +
115         ".and(L,L) is not implemented!");
116     System.err.println("Please implement instance() in your class with ↵
117         @Override");
118     System.exit(0);
119     return null;
120 }
121
122 /**
123  * This method is not defined for class {@link LatticeCommon } and generates
124  * an error report and a code exit.
125  * <BR><BR>
126  * <b>Documentation inherited from {@link Lattice }:</b><BR>
127  * {@inheritDoc}
128  */
129 public L or(L left, L right) {
130     System.err.println("Error :: "+this.getClass().getName() +
131         ".or(L,L) is not implemented!");
132     System.err.println("Please implement instance() in your class with ↵
133         @Override");
134     System.exit(0);
135     return null;
136 }
137
138 /**
139  * This method is not defined for class {@link LatticeCommon } and generates
140  * an error report and a code exit.
141  * <BR><BR>
142  * <b>Documentation inherited from {@link Lattice }:</b><BR>
143  * {@inheritDoc}
144  */
145 public boolean intersects(L aProposition) {
146     System.err.println("Error :: "+this.getClass().getName() +

```

```

142         ".intersects(L) is not implemented!");
143     System.err.println("Please implement instance() in your class with ↵
        @Override");
144     System.exit(0);
145     return false;
146 }
147
148 /**
149  * This method is not defined for class {@link LatticeCommon } and generates
150  * an error report and a code exit.
151  * <BR><BR>
152  * <b>Documentation inherited from {@link Lattice }:</b><BR>
153  * {@inheritDoc}
154  */
155 public boolean contains(L aProposition) {
156     System.err.println("Error :: "+this.getClass().getName() +
157         ".contains(L) is not implemented!");
158     System.err.println("Please implement instance() in your class with ↵
        @Override");
159     System.exit(0);
160     return true;
161 }
162
163 /**
164  * This method is not defined for class {@link LatticeCommon } and generates
165  * an error report and a code exit.
166  * <BR><BR>
167  * <b>Documentation inherited from {@link Lattice }:</b><BR>
168  * {@inheritDoc}
169  */
170 public int compareTo(L aProposition) {
171     System.err.println("Error :: "+this.getClass().getName() +
172         ".compareTo(L) is not implemented!");
173     System.err.println("Please implement instance() in your class with ↵
        @Override");
174     System.exit(0);
175     return 0;
176 }
177
178 /**
179  * This method is not defined for class {@link LatticeCommon } and generates
180  * an error report and a code exit.
181  * <BR><BR>
182  * <b>Documentation inherited from {@link Lattice }:</b><BR>
183  * {@inheritDoc}
184  */
185 public L size(L input) {
186     System.err.println("Error :: "+this.getClass().getName() +
187         ".size(L) is not implemented!");
188     System.err.println("Please implement instance() in your class with ↵
        @Override");
189     System.exit(0);
190     return null;
191 }
192
193 /**
194  * This method is not defined for class {@link LatticeCommon } and generates
195  * an error report and a code exit.
196  * <BR><BR>
197  * <b>Documentation inherited from {@link Lattice }:</b><BR>
198  * {@inheritDoc}
199  */
200 public int size(int newSize) {
201     System.err.println("Error :: "+this.getClass().getName() +
202         ".size(int) is not implemented!");
203     System.err.println("Please implement instance() in your class with ↵
        @Override");
204     System.exit(0);
205     return -1;
206 }
207
208 /**
209  * This method is not defined for class {@link LatticeCommon } and generates
210  * an error report and a code exit.

```

```

211 * <BR><BR>
212 * <b>Documentation inherited from {@link Lattice }:</b><BR>
213 * {@inheritDoc}
214 */
215 public L duplicate(L input) {
216     System.err.println("Error :: "+this.getClass().getName() +
217         ".duplicate(L) is not implemented!");
218     System.err.println("Please implement instance() in your class with ↵
        @Override");
219     System.exit(0);
220     return null;
221 }
222
223 /**
224 * This method is not defined for class {@link LatticeCommon } and generates
225 * an error report and a code exit.
226 * <BR><BR>
227 * <b>Documentation inherited from {@link Lattice }:</b><BR>
228 * {@inheritDoc}
229 */
230 public L instance() {
231     System.err.println("Error :: "+this.getClass().getName() +
232         ".instance() is not implemented!");
233     System.err.println("Please implement instance() in your class with ↵
        @Override");
234     System.exit(0);
235     return null;
236 }
237
238 public L instanceNsize() { // create an instance with the same size
239     return instance().size((L) this);
240 }
241
242 @Override
243 public L clone() {
244     return instance().duplicate((L) this);
245 }
246
247 }

```

Source Code: minAssignment.java

```

1  /*
2  *   minAssignment.java : part of package RefereeToolbox; Interface for
3  *   minimal implementation of Basic Belief Assignment.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 import java.util.*;
29
30 /**
31 * Contains the minimal declaration for classes managing belief assignments.
32 * This interface is implemented by all these classes.
33 *
34 * @see      BasicBeliefAssignment
35 * @see      RefereeFunctionDefault
36 * @author    <A href="http://email.fredericdambreville.com">Frédéric Dambreville</A>
37 *
38 *
39 *
40 * <BR><BR><table border='1' cellPadding='4'><tr><td>
41 * <font color="#008000" style="font-family: georgia">
42 *   Copyright (c) 2010 Frédéric Dambreville<BR>
43 * <BR>
44 *   RefereeToolbox is free software: you can redistribute it and/or modify
45 *   it under the terms of the GNU General Public License as published by
46 *   the Free Software Foundation, either version 3 of the License, or
47 *   (at your option) any later version.<BR>
48 * <BR>
49 *   RefereeToolbox is distributed in the hope that it will be useful,
50 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
51 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
52 *   GNU General Public License for more details.<BR>
53 * <BR>
54 *   You should have received a copy of the GNU General Public License
55 *   along with RefereeToolbox. If not, see
56 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
57 * </font></td></tr></table><BR>
58 *
59 */
60 public interface minAssignment<Prop extends Lattice<Prop>> {
61
62 /**
63 * Create an array of the assignments stored within the class. These assignments ←
64 *   not
65 *   necessary sum to 1. Notice that the assignments should be positively valued
66 *   (focal elements), although <i>this</i> is not a strict requirement.
67 *
68 *   ArrayList<Assignment<Prop>> toArray();
69
70 /**

```

```

71  * Get the basic belief assigned to <i>aProposition</i>. May be zero.
72  *
73  */
74  double m(Prop aProposition);
75
76  /**
77  * Get the belief of <i>aProposition</i>. Although not required, it is assumed  $\leftrightarrow$ 
78  * that
79  * the assignments sum to 1.
80  */
81  double Bel(Prop aProposition);
82
83  /**
84  * Get the plausibility of <i>aProposition</i>. Although not required, it is  $\leftrightarrow$ 
85  * assumed that
86  * the assignments sum to 1.
87  */
88  double Pl(Prop aProposition);
89
90
91  /**
92  * Search if there is an assignment stored within the class, and which attribute
93  * is equal to the attribute of <i>anAssignment</i>.
94  * Return the found assignment, if there is one. Otherwise, return <i>null</i>.
95  */
96  public Assignment<Prop> findProposition(Assignment<Prop> anAssignment);
97
98  /**
99  * Search if there is an assignment stored within the class, and which attribute
100  * is equal to the proposition <i>aProposition</i>.
101  * Return the found assignment, if there is one. Otherwise, return <i>null</i>.
102  */
103  public Assignment<Prop> findProposition(Prop aProposition);
104
105  }
106
107

```

Source Code: Openhyperpowerset.java

```

1  /*
2  *   Openhyperpowerset.java : part of package RefereeToolbox; Implementation
3  *   of open hyperpowerset.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * Implementation of an open hyperpowerset structure. An open hyperpowerset is an
30 * hyperpowerset defined on the basis of a free boolean algebra: it is generated
31 * from the atomic propositions of the free boolean algebra but without the use of
32 * the complement operator of the free boolean algebra.
33 * <BR><BR>
34 * The open hyperpowerset implies an open world hypothesis, that is:
35 * <BR><BR>
36 * <i> <b>OR</b><sub>0 ≤ i < sizeFrame</sub> atomic(i) != one</i>
37 * <BR><BR>
38 * Although generated without the complement of the free Boolean algebra, the open
39 * hyperpowerset actually has proper complement and cocomplement operators.
40 * The complement and cocomplement are distinct operators for the open ←
41 * hyperpowerset.
42 *
43 * @author   <A href="http://email.fredericdambreville.com">Frédéric ←
44 *           Dambreville</A>
45 *
46 * <BR><BR><table border='1' cellPadding='4'><tr><td>
47 * <font color="#008000" style="font-family: georgia">
48 *   Copyright (c) 2010 Frédéric Dambreville<BR>
49 * <BR>
50 *   RefereeToolbox is free software: you can redistribute it and/or modify
51 *   it under the terms of the GNU General Public License as published by
52 *   the Free Software Foundation, either version 3 of the License, or
53 *   (at your option) any later version.<BR>
54 * <BR>
55 *   RefereeToolbox is distributed in the hope that it will be useful,
56 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
57 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
58 *   GNU General Public License for more details.<BR>
59 * <BR>
60 *   You should have received a copy of the GNU General Public License
61 *   along with RefereeToolbox. If not, see
62 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
63 * </font></td></tr></table><BR>
64 *
65 */
66 public class Openhyperpowerset<L extends Openhyperpowerset<L>> extends Freeboolean←
67     <L> {
68     protected L theZero = null;
69     protected L theOne = null;

```

```

70  /**
71  * Compute the <b>complement</b> of <i>aProposition</i> and store the result
72  * within <i>this</i>.
73  * The complement operator for the open hyperpowerset is defined by:
74  * <BR><BR>
75  * <i> complement(zero) = one</i>
76  * <BR>
77  * <i> complement(X) = zero</i> if <i>X != zero</i>
78  *
79  */
80  @Override
81  public L complement(L aProposition) {
82      if (theZero==null) {
83          theZero = instanceNsize().zero();
84          theOne = instanceNsize().one();
85      }
86      if (aProposition.compareTo(theZero)==0) one();
87      else zero();
88      return (L) this;
89  }
90
91  /**
92  * Compute the <b>complement</b> of <i>this</i> and store the result within
93  * <i>this</i>.
94  * The complement operator for the open hyperpowerset is defined by:
95  * <BR><BR>
96  * <i> complement(zero) = one</i>
97  * <BR>
98  * <i> complement(X) = zero</i> if <i>X != zero</i>
99  *
100  */
101  @Override
102  public L complement() {
103      if (theZero==null) {
104          theZero = instanceNsize().zero();
105          theOne = instanceNsize().one();
106      }
107      if (compareTo(theZero)==0) one();
108      else zero();
109      return (L) this;
110  }
111
112  /**
113  * Compute the <b>cocomplement</b> of <i>aProposition</i> and store the result
114  * within <i>this</i>.
115  * The cocomplement operator for the open hyperpowerset is defined by:
116  * <BR><BR>
117  * <i> cocomplement(one) = zero</i>
118  * <BR>
119  * <i> cocomplement(X) = one</i> if <i>X != one</i>
120  *
121  */
122  @Override
123  public L cocomplement(L aProposition) {
124      if (theZero==null) {
125          theZero = instanceNsize().zero();
126          theOne = instanceNsize().one();
127      }
128      if (aProposition.compareTo(theOne)==0) zero();
129      else one();
130      return (L) this;
131  }
132
133  /**
134  * Compute the <b>cocomplement</b> of <i>this</i> and store the result
135  * within <i>this</i>.
136  * The cocomplement operator for the open hyperpowerset is defined by:
137  * <BR><BR>
138  * <i> cocomplement(one) = zero</i>
139  * <BR>
140  * <i> cocomplement(X) = one</i> if <i>X != one</i>
141  *
142  */
143  @Override

```

```
144     public L cocomplement() {
145         if(theZero==null) {
146             theZero = instanceNsize().zero();
147             theOne = instanceNsize().one();
148         }
149         if(compareTo(theOne)==0) zero();
150         else one();
151         return (L) this;
152     }
153
154 }
```

Source Code: Powerset.java

```

1  /*
2  *   Powerset.java : part of package RefereeToolbox; Implementation of powerset.
3  *   ****
4  *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville
5  *
6  *   Author:      FrÃ©dÃ©ric Dambreville <http://email.fredericdambreville.com>
7  *
8  *   This file is part of RefereeToolbox.
9  *
10 *   RefereeToolbox is free software: you can redistribute it and/or modify
11 *   it under the terms of the GNU General Public License as published by
12 *   the Free Software Foundation, either version 3 of the License, or
13 *   (at your option) any later version.
14 *
15 *   RefereeToolbox is distributed in the hope that it will be useful,
16 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
17 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
18 *   GNU General Public License for more details.
19 *
20 *   You should have received a copy of the GNU General Public License
21 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
22 *   ****
23 */
24
25 package RefereeToolbox;
26
27 /**
28 * Implementation of a Powerset structure by means of an array of {@code long}.
29 * Structural methods are redefined, {@link Freeboolean#size(int) } and
30 * {@link Freeboolean#size(RefereeToolbox.Freeboolean) },
31 * and the atomic are defined {@link Freeboolean#atomic(int) }.
32 * The AND and OR operators are inherited from the operators {@code & } and {@code ←
33 | }
34 * working on {@code long}.
35 * <i>zero</i> is defined by zeroing all bits. <i>one</i> is defined by setting to
36 * 1 all active bits; the right bits of the {@code long } vector may be inactive,
37 * depending on the size of the Lattice.
38 * The complement/cocomplement operators are inherited from the operators {@code ~←
39 | }
40 * working on {@code long}; exceeding bits are masked by a AND with <i>one</i>.
41 *
42 * @author      <A href="http://email.fredericdambreville.com">FrÃ©dÃ©ric ↵
43 | Dambreville</A>
44 *
45 *
46 * <BR><BR><table border='1' cellPadding='4'><tr><td>
47 * <font color="#008000" style="font-family: georgia">
48 * Copyright (c) 2010 FrÃ©dÃ©ric Dambreville<BR>
49 * <BR>
50 * RefereeToolbox is free software: you can redistribute it and/or modify
51 * it under the terms of the GNU General Public License as published by
52 * the Free Software Foundation, either version 3 of the License, or
53 * (at your option) any later version.<BR>
54 * <BR>
55 * RefereeToolbox is distributed in the hope that it will be useful,
56 * but WITHOUT ANY WARRANTY; without even the implied warranty of
57 * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
58 * GNU General Public License for more details.<BR>
59 * <BR>
60 * You should have received a copy of the GNU General Public License
61 * along with RefereeToolbox. If not, see
62 * <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
63 * </font></td></tr></table><BR>
64 *
65 */
66
67 public class Powerset<L extends Powerset<L>> extends ArrayBoolean<L>
68 | implements GeneratedLattice<L> {
69
70     protected static int sizeMax=1<<16;
71
72     protected int sizeFrame = -1; // Frame of discernment is undefined by default

```

```

70
71
72 ///////////////////////////////////////////////////:
73 // public part
74 //////////////////////////////////////////////////
75
76 /**
77 * Return the  $\langle i \rangle$  atomic proposition.
78 * For class {@link Powerset }, the  $\langle i \rangle$  atomic proposition is
79 * constituted by the  $\langle i \rangle$  bit stored in the
80 *  $\langle i \rangle$  long array.
81 * <BR><BR>
82 * return null if  $i$  is out of bounds.
83 */
84 public L atomic(int i) {
85     if((i>=sizeFrame)|| (i<0)) {
86         return null;
87     }
88     zero();
89     int offset = i%64;
90     int index = i/64;
91     _memory[index]=( 1L << offset);
92     return (L) this;
93 }
94
95 /**
96 * Set or return the size of  $\langle i \rangle$ .
97 * Different cases are considered:
98 * <br><br>
99 *  $\langle i \rangle$ newSize<0 — The size of  $\langle i \rangle$  is kept unchanged, and this size
100 * is returned by the method.
101 * <br>
102 *  $\langle i \rangle$ newSize=0 — If  $\langle i \rangle$ newSize is a valid new size, then the size of
103 *  $\langle i \rangle$  is changed to  $\langle i \rangle$ newSize, and this size is returned by the
104 * method.
105 * <br><br>
106 * Valid new size is such that  $\langle i \rangle$ 1<=newSize<=sizeMax. By default,
107 *  $\langle i \rangle$ {@link Powerset#sizeMax }=1<16.
108 * <br>
109 * For class {@link Powerset },  $\langle i \rangle$ newSize is stored in protected variable
110 *  $\langle i \rangle$ sizeFrame and is equals to the number  $\langle i \rangle$ (has to be >1) of
111 * bits stored in the  $\langle i \rangle$  long array.
112 * Moreover, each activated bit constitute an atomic proposition.
113 * <br><br>
114 * N.B. 1. By default, this method is not implemented by {@link Lattice } directly
115 * but by its subclasses.
116 * <br>
117 * N.B. 2. The size is not necessarily the cardinal of the lattice, but may be
118 * instead the number of atomic propositions of the lattice.
119 *
120 */
121 @Override
122 public int size(int newSize) { // if newSize is possible, then change size to
123     newSize
124     if((newSize>0)&&(newSize<=sizeMax)) {
125         sizeFrame=newSize;
126         size_mem_1=(sizeFrame-1)/64;
127         highest_long_one=sizeFrame-64*size_mem_1;
128         highest_long_one=((1L<<(highest_long_one - 1))-1)<<1)+1;
129         //
130         _memory= new long [size_mem_1+1];
131     }
132     return sizeFrame;
133 }
134
135 @Override
136 public L size(L input) {
137     size(input.size(-1));
138     return (L) this;
139 }

```


Source Code: RefereeFunctionDefault.java

```

1  /*
2  *   RefereeFunctionDefault.java : part of package RefereeToolbox; Default
3  *   implementation of referee function.
4  *   ****
5  *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville
6  *
7  *   Author:   FrÃ©dÃ©ric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 import java.util.*;
29
30 /**
31 * This class implements the default Referee Function.
32 * This default Referee Function actually encodes the combination rule of Dempster←
33 *   Shafer.
34 *
35 * @author   <A href="http://email.fredericdambreville.com">FrÃ©dÃ©ric ←
36 *           Dambreville</A>
37 *
38 * <BR><BR><table border='1' cellPadding='4'><tr><td>
39 * <font color="#008000" style="font-family: georgia">
40 *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville<BR>
41 * <BR>
42 *   RefereeToolbox is free software: you can redistribute it and/or modify
43 *   it under the terms of the GNU General Public License as published by
44 *   the Free Software Foundation, either version 3 of the License, or
45 *   (at your option) any later version.<BR>
46 * <BR>
47 *   RefereeToolbox is distributed in the hope that it will be useful,
48 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
49 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
50 *   GNU General Public License for more details.<BR>
51 * <BR>
52 *   You should have received a copy of the GNU General Public License
53 *   along with RefereeToolbox. If not, see
54 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
55 * </font></td></tr></table><BR>
56 *
57 */
58 public class RefereeFunctionDefault<Prop extends Lattice<Prop>> {
59
60
61     ///////////////////////////////////////////:
62     // public part
63     //////////////////////////////////////////
64
65 /**
66 * Implement the Referee Function of the class.
67 * The referee function takes as context:
68 * <BR><BR>
69 * (a) The list of the propositions proposed by each source of information,
70 * <BR>

```

```

71 * (b) The list of basic belief assigned by each sources to their respective ↵
72 * proposal,
73 * <BR>
74 * (c) The list of Basic Belief Assignment of the sources. This last information,
75 * which constitutes a more general and global information of context, is rarely
76 * used in practice, but is provided for the sack of the generality of the ↵
77 * implementation.
78 * <BR><BR>
79 * Information (a) and (b) are provided by variable <i>assignIn</i>.
80 * Information (c) are provided by variable <i>bbaIn</i>.
81 * <BR><BR>
82 * The referee function returns a list of assignments which sum to 1 and models a
83 * probabilistic final decision.
84 *
85 * @param assignIn
86 * The list of propositions proposed by the sources together with ↵
87 * their
88 * @param bbaIn
89 * The list of Basic Belief Assignment of the sources
90 * assigned basic belief
91 * @return A list of assignments modelling a probabilistic decision
92 *
93 */
94 public ArrayList<Assignment<Prop>> refereeFunction(ArrayList<Assignment<Prop>>↵
95 assignIn,
96 ArrayList<minAssignment<↵
97 Prop>> bbaIn) {
98
99     if(assignIn==null) {
100         System.err.println("Error :: "+this.getClass().getName() +
101             ".refereeFunction(ArrayList<Assignment<Prop>>,ArrayList<B>)");
102         System.err.println("Error :: assignIn is null");
103         System.exit(0);
104     }
105     if(assignIn.size()<1) {
106         System.err.println("Error :: "+this.getClass().getName() +
107             ".refereeFunction(ArrayList<Assignment<Prop>>,ArrayList<B>)");
108         System.err.println("Error :: assignIn is empty");
109         System.exit(0);
110     }
111
112     int i;
113     ArrayList<Assignment<Prop>> arbitrament=new ArrayList<Assignment<Prop>>();
114     Assignment<Prop> finalAssignment = new Assignment<Prop>();
115     Prop fusedProp=assignIn.get(0).attribute.clone();
116     finalAssignment.attribute=fusedProp;
117     finalAssignment.value=1.;
118     arbitrament.add(finalAssignment);
119
120     for(i=1;i<assignIn.size();i++) {
121         fusedProp.and(fusedProp,assignIn.get(i).attribute);
122     }
123     return arbitrament;
124 }

```

Source Code: RefereeFunctionDempster.java

```

1  /*
2  *   RefereeFunctionDempster.java : part of package RefereeToolbox;
3  *   Implementation of referee function.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * This class implements the Referee Function encoding the combination rule of
30 * Dempster-Shafer.
31 *
32 * @author   <A href="http://email.fredericdambreville.com">Frédéric ↵
33 *           Dambreville</A>
34 *
35 *
36 * <BR><BR><table border='1' cellPadding='4'><tr><td>
37 * <font color="#008000" style="font-family: georgia">
38 *   Copyright (c) 2010 Frédéric Dambreville<BR>
39 * <BR>
40 *   RefereeToolbox is free software: you can redistribute it and/or modify
41 *   it under the terms of the GNU General Public License as published by
42 *   the Free Software Foundation, either version 3 of the License, or
43 *   (at your option) any later version.<BR>
44 * <BR>
45 *   RefereeToolbox is distributed in the hope that it will be useful,
46 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
47 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
48 *   GNU General Public License for more details.<BR>
49 * <BR>
50 *   You should have received a copy of the GNU General Public License
51 *   along with RefereeToolbox. If not, see
52 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
53 * </font></td></tr></table><BR>
54 *
55 */
56 public class RefereeFunctionDempster<Prop extends Lattice<Prop> >
57         extends RefereeFunctionDefault<Prop> {
58     // Nothing to do; Dempster is by default!
59 }

```

Source Code: RefereeFunctionDisjunctive.java

```

1  /*
2  *   RefereeFunctionDisjunctive.java : part of package RefereeToolbox;
3  *   Implementation of referee function.
4  *   ****
5  *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville
6  *
7  *   Author:   FrÃ©dÃ©ric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 import java.util.*;
29 /**
30 * This class implements the Referee Function encoding the disjunctive combination
31 * rule.
32 *
33 * @author      <A href="http://email.fredericdambreville.com">FrÃ©dÃ©ric ↵
34 *               Dambreville</A>
35 *
36 *
37 * <BR><BR><table border='1' cellPadding='4'><tr><td>
38 * <font color="#008000" style="font-family: georgia">
39 * Copyright (c) 2010 FrÃ©dÃ©ric Dambreville<BR>
40 * <BR>
41 * RefereeToolbox is free software: you can redistribute it and/or modify
42 * it under the terms of the GNU General Public License as published by
43 * the Free Software Foundation, either version 3 of the License, or
44 * (at your option) any later version.<BR>
45 * <BR>
46 * RefereeToolbox is distributed in the hope that it will be useful,
47 * but WITHOUT ANY WARRANTY; without even the implied warranty of
48 * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
49 * GNU General Public License for more details.<BR>
50 * <BR>
51 * You should have received a copy of the GNU General Public License
52 * along with RefereeToolbox. If not, see
53 * <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
54 * </font></td></tr></table><BR>
55 *
56 */
57 public class RefereeFunctionDisjunctive<Prop extends Lattice<Prop>>
58         extends RefereeFunctionDefault<Prop> {
59
60
61     ///////////////////////////////////////////:
62     // public part
63     //////////////////////////////////////
64
65     @Override
66     public ArrayList<Assignment<Prop>> refereeFunction(ArrayList<Assignment<Prop>>↵
67         assignIn,
68                                     ArrayList<minAssignment<Prop>>↵
69                                     bbaIn) {
68
69         if(assignIn==null) {
70             System.err.println("Error :: "+this.getClass().getName() +

```

```

70         ".refereeFunction(ArrayList<Assignment<Prop>>,ArrayList<B>)" );
71         System.err.println("Error :: assignIn is null");
72         System.exit(0);
73     }
74     if(assignIn.size()<1) {
75         System.err.println("Error :: "+this.getClass().getName() +
76             ".refereeFunction(ArrayList<Assignment<Prop>>,ArrayList<B>)" );
77         System.err.println("Error :: assignIn is empty");
78         System.exit(0);
79     }
80
81     int i;
82     ArrayList<Assignment<Prop>> arbitrament=new ArrayList<Assignment<Prop>>();
83     Assignment<Prop> finalAssignment = new Assignment<Prop>();
84     Prop fusedProp=assignIn.get(0).attribute.clone();
85     finalAssignment.attribute=fusedProp;
86     finalAssignment.value=1.;
87     arbitrament.add(finalAssignment);
88
89     for(i=1;i<assignIn.size();i++) {
90         fusedProp.or(fusedProp, assignIn.get(i).attribute);
91     }
92     return arbitrament;
93 }
94
95 }

```

Source Code: RefereeFunctionDuboisPrade.java

```

1  /*
2  *   RefereeFunctionDuboisPrade.java : part of package RefereeToolbox;
3  *   Implementation of referee function.
4  *   ****
5  *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville
6  *
7  *   Author:   FrÃ©dÃ©ric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 import java.util.*;
29 /**
30 * This class implements the Referee Function encoding the combination rule of ↵
31 *   Dubois
32 *   & Prade.
33 *   @author   <A href="http://email.fredericdambreville.com">FrÃ©dÃ©ric ↵
34 *             Dambreville</A>
35 *
36 *
37 *   <BR><BR><table border='1' cellPadding='4'><tr><td>
38 *   <font color="#008000" style="font-family: georgia">
39 *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville<BR>
40 *   <BR>
41 *   RefereeToolbox is free software: you can redistribute it and/or modify
42 *   it under the terms of the GNU General Public License as published by
43 *   the Free Software Foundation, either version 3 of the License, or
44 *   (at your option) any later version.<BR>
45 *   <BR>
46 *   RefereeToolbox is distributed in the hope that it will be useful,
47 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
48 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
49 *   GNU General Public License for more details.<BR>
50 *   <BR>
51 *   You should have received a copy of the GNU General Public License
52 *   along with RefereeToolbox. If not, see
53 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
54 *   </font></td></tr></table><BR>
55 *
56 */
57 public class RefereeFunctionDuboisPrade<Prop extends Lattice<Prop>>
58         extends RefereeFunctionDefault<Prop> {
59
60
61     ///////////////////////////////////////////:
62     // public part
63     //////////////////////////////////////////
64
65     @Override
66     public ArrayList<Assignment<Prop>> refereeFunction(ArrayList<Assignment<Prop>>↵
67         assignIn,                                     ArrayList<minAssignment<Prop>>↵
68                                                         bbaIn) {
69         if(assignIn==null) {

```

```

69         System.err.println("Error :: "+this.getClass().getName() +
70             ".refereeFunction(ArrayList<Assignment<Prop>>,ArrayList<B>)" );
71         System.err.println("Error :: assignIn is null");
72         System.exit(0);
73     }
74     if(assignIn.size()<1) {
75         System.err.println("Error :: "+this.getClass().getName() +
76             ".refereeFunction(ArrayList<Assignment<Prop>>,ArrayList<B>)" );
77         System.err.println("Error :: assignIn is empty");
78         System.exit(0);
79     }
80
81     int i;
82     ArrayList<Assignment<Prop>> arbitrament=new ArrayList<Assignment<Prop>>();
83     Assignment<Prop> finalAssignment = new Assignment<Prop>();
84     Prop fusedPropConj=assignIn.get(0).attribute.clone();
85     Prop fusedPropDisj=fusedPropConj.instanceNsize().zero();
86     finalAssignment.value=1.;
87     for(i=1;i<assignIn.size();i++) fusedPropConj.and(fusedPropConj, assignIn.get(i).attribute);
88     if(fusedPropConj.compareTo(fusedPropDisj)==0) {
89         for(i=0;i<assignIn.size();i++) fusedPropDisj.or(fusedPropDisj, assignIn.get(i).attribute);
90         finalAssignment.attribute=fusedPropDisj;
91     } else finalAssignment.attribute=fusedPropConj;
92     arbitrament.add(finalAssignment);
93     return arbitrament;
94 }
95
96 }

```

Source Code: RefereeFunctionPCR6.java

```

1  /*
2  *   RefereeFunctionPCR6.java : part of package RefereeToolbox; Implementation
3  *   of referee function.
4  *   ****
5  *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville
6  *
7  *   Author:   FrÃ©dÃ©ric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 import java.util.*;
29
30 /**
31 * This class implements the Referee Function encoding the PCR6 combination rule.
32 *
33 * @author   <A href="http://email.fredericdambreville.com">FrÃ©dÃ©ric ↵
34 *           Dambreville</A>
35 *
36 * <BR><BR><table border='1' cellPadding='4'><tr><td>
37 * <font color="#008000" style="font-family: georgia">
38 *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville<BR>
39 * <BR>
40 *   RefereeToolbox is free software: you can redistribute it and/or modify
41 *   it under the terms of the GNU General Public License as published by
42 *   the Free Software Foundation, either version 3 of the License, or
43 *   (at your option) any later version.<BR>
44 * <BR>
45 *   RefereeToolbox is distributed in the hope that it will be useful,
46 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
47 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
48 *   GNU General Public License for more details.<BR>
49 * <BR>
50 *   You should have received a copy of the GNU General Public License
51 *   along with RefereeToolbox. If not, see
52 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
53 * </font></td></tr></table><BR>
54 *
55 */
56 public class RefereeFunctionPCR6<Prop extends Lattice<Prop> >
57     extends RefereeFunctionDefault<Prop> {
58
59
60     ///////////////////////////////////////////:
61     // public part
62     //////////////////////////////////////////
63
64     @Override
65     public ArrayList<Assignment<Prop>> refereeFunction(ArrayList<Assignment<Prop>>↵
66         assignIn,
67                                     ArrayList<minAssignment<↵
68                                     Prop>> bbaIn) {
69
70         if(assignIn==null) {
71             System.err.println("Error :: "+this.getClass().getName() +
72                 ".refereeFunction(ArrayList<Assignment<Prop>>,ArrayList<B>)");
73         }
74     }
75 }

```

```

70         System.err.println("Error :: assignIn is null");
71         System.exit(0);
72     }
73     if (assignIn.size() < 1) {
74         System.err.println("Error :: "+this.getClass().getName() +
75             ".refereeFunction(ArrayList<Assignment<Prop>>,ArrayList<B>)" );
76         System.err.println("Error :: assignIn is empty");
77         System.exit(0);
78     }
79
80     int i;
81     double Norm;
82     ArrayList<Assignment<Prop>> arbitrament=new ArrayList<Assignment<Prop>>();
83     Assignment<Prop> finalAssignment;
84     Prop fusedProp=assignIn.get(0).attribute.clone();
85     Prop zero=fusedProp.instanceNsize().zero();
86     Norm=0.;
87     for(i=1;i<assignIn.size();i++) {
88         fusedProp.and(fusedProp, assignIn.get(i).attribute);
89     }
90     if (fusedProp.compareTo(zero)==0) {
91         for(i=0;i<assignIn.size();i++) {
92             Norm+=assignIn.get(i).value;
93         }
94         for(i=0;i<assignIn.size();i++) {
95             finalAssignment = new Assignment<Prop>();
96             finalAssignment.value=assignIn.get(i).value/Norm;
97             finalAssignment.attribute=assignIn.get(i).attribute.clone();
98             arbitrament.add(finalAssignment);
99         }
100     } else {
101         finalAssignment = new Assignment<Prop>();
102         finalAssignment.value=1.;
103         finalAssignment.attribute=fusedProp;
104         arbitrament.add(finalAssignment);
105     }
106     return arbitrament;
107 }
108
109 }

```

Source Code: RefereeFunctionPCRSharp.java

```

1  /*
2  *   RefereeFunctionPCRSharp.java : part of package RefereeToolbox;
3  *   Implementation of referee function.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 import java.util.*;
29
30 /**
31  * This class implements the Referee Function encoding the PCRSharp combination ←
32  * rule.
33  *
34  * @author   <A href="http://email.fredericdambreville.com">Frédéric ←
35  *           Dambreville</A>
36  *
37  * <BR><BR><table border='1' cellPadding='4'><tr><td>
38  * <font color="#008000" style="font-family: georgia">
39  * Copyright (c) 2010 Frédéric Dambreville<BR>
40  * <BR>
41  * RefereeToolbox is free software: you can redistribute it and/or modify
42  * it under the terms of the GNU General Public License as published by
43  * the Free Software Foundation, either version 3 of the License, or
44  * (at your option) any later version.<BR>
45  * <BR>
46  * RefereeToolbox is distributed in the hope that it will be useful,
47  * but WITHOUT ANY WARRANTY; without even the implied warranty of
48  * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
49  * GNU General Public License for more details.<BR>
50  * <BR>
51  * You should have received a copy of the GNU General Public License
52  * along with RefereeToolbox. If not, see
53  * <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
54  * </font></td></tr></table><BR>
55  *
56  */
57 public class RefereeFunctionPCRSharp<Prop extends Lattice<Prop>>
58         extends RefereeFunctionDefault<Prop> {
59     protected int theEntrySize=-1;
60     protected Prop theDefault=null;
61     protected Prop theZero=null;
62     protected Prop theOne=null;
63     protected boolean[] theMask=null;
64     protected boolean[] theRevMask=null;
65
66     protected double[] weightTab=null;
67     protected int[] mapTab=null;
68     protected ArrayList<Prop> thePropositionTab=null;
69
70     protected ArrayList<Assignment<Prop>> getWeightedSubset(int subsetSize,

```

```

71                                     ArrayList<Assignment<Prop>> assignIn) {
72     double theNorm;
73     int j,k,pivot;
74     boolean justMoved;
75     ArrayList<Assignment<Prop>> theAssignmentList;
76     theAssignmentList = new ArrayList<Assignment<Prop>>();
77     Assignment<Prop> curAssignment;
78     Prop aProposition;
79     double aValue;
80
81     // init
82     theNorm=0.;
83     pivot=subsetSize;
84     weightTab[pivot]=1.;
85     thePropositionTab.set(pivot, theOne);
86     mapTab[pivot]=theEntrySize;
87     justMoved=true;
88     // init done
89
90     // loop
91     do {
92         if(justMoved) {
93             justMoved=false;
94             for(j=pivot;j>0;) {
95                 k=j;
96                 j--;
97                 mapTab[j]=j;
98                 weightTab[j]=weightTab[k]*assignIn.get(j).value;
99                 thePropositionTab.set(j, theZero.instanceNsize().and(
100                     assignIn.get(j).attribute, thePropositionTab.get(k)));
101                 pivot--;
102             }
103             // build a new assignment?
104             aProposition=thePropositionTab.get(0);
105             if(aProposition.compareTo(theZero)!=0) {
106                 // a new assignment is created for the next case
107                 aValue=weightTab[0];
108                 curAssignment = new Assignment<Prop>();
109                 curAssignment.attribute=aProposition;
110                 curAssignment.value=aValue;
111                 theAssignmentList.add(curAssignment);
112                 theNorm+=aValue;
113             }
114         }
115         k=pivot+1;
116         j=mapTab[pivot]+1;
117         if(j<mapTab[k]) {
118             mapTab[pivot]=j;
119             weightTab[pivot]=weightTab[k]*assignIn.get(j).value;
120             thePropositionTab.set(pivot, theZero.instanceNsize().and(
121                 assignIn.get(j).attribute, thePropositionTab.get(k)));
122             justMoved=true;
123         } else pivot++;
124     } while(pivot<subsetSize);
125
126     for(j=0;j<theAssignmentList.size();j++) theAssignmentList.get(j).value/=theNorm;
127
128     return theAssignmentList;
129 }
130
131
132
133 protected ArrayList<Assignment<Prop>> askWeightedSubset(int subsetSize,
134                                     ArrayList<Assignment<Prop>> assignIn) {
135     // Test the mask in order to decide for the computation
136     int k;
137     if(theMask==null) {
138         if(theRevMask==null) return getWeightedSubset(subsetSize,assignIn);
139     } else {
140         if((k=(subsetSize-1))<theMask.length)
141             if(theMask[k]) return getWeightedSubset(subsetSize,assignIn);
142     }
143     if(theRevMask!=null) {

```

```

144         if ((k=(theEntrySize-subsetSize))<theRevMask.length)
145             if (theRevMask[k]) return getWeightedSubset(subsetSize,assignIn←
146                 );
147     }
148     return new ArrayList<Assignment<Prop>>();
149 }
150
151 ///////////////////////////////////////////////////:
152 // public part
153 //////////////////////////////////////////////////
154
155 /**
156  * Set the default answer to proposition <i>aDefault</i>.
157  * The default answer is returned by the PCRSharp referee function, when no ←
158     consensus
159  * have been found among the acceptable subset combination of sources.
160  * <BR><BR>
161  * The default answer is initialized to <i>null</i> at the class construction,
162  * which is automatically handled as a <i>zero</i>.
163  */
164 public void setDefaultAnswer(Prop aDefault) {
165     if (aDefault==null) {
166         System.err.println("Error :: "+this.getClass().getName() +
167             ".setDefaultAnswer(Prop)");
168         System.err.println("Error :: aDefault is null");
169         System.exit(0);
170     }
171     theDefault=aDefault.clone();
172 }
173
174 /**
175  * Set a mask and a reverse mask which will select the sizes of subset combination
176  * (of the sources entries) which are taken into consideration.
177  * These parameters work as follows:
178  * <br><br>
179  * If <i>aMask=null</i> and <i>aRevMask=null</i>\\,, then all subset combinations ←
180     are
181     managed (this is a dangerous choice, when there are many sources).
182  * <br><br>Otherwise:
183  * <br>
184  * If <i>aMask=null</i>, then <i>aMask</i> is not considered for masking.
185  * <br>
186  * If <i>aRevMask=null</i>, then <i>aRevMask</i> is not considered for masking.
187  * <br><br>
188  * aMask defined the clearance where it is <i>true</i> from (minimal) subset size
189  * 1 upward
190  * <br>
191  * aRevMask defined the clearance where it is <i>true</i> from (maximal) subset
192  * size <i>theEntrySize</i> downward
193  */
194 public void setMask(boolean[] aMask, boolean[] aRevMask) {
195     // NB: null Mask means that the mask is not considered
196     // null & null masks means that there is no masking
197     // aMask => define clearance from (minimal) set size 1 upward
198     // aRevMask => define clearance from (maximal) set size theEntrySize ←
199     downward
200     int i;
201     theMask=new boolean[aMask.length];
202     theRevMask=new boolean[aRevMask.length];
203     for (i=0;i<theMask.length;i++) theMask[i]=aMask[i];
204     for (i=0;i<theRevMask.length;i++) theRevMask[i]=aRevMask[i];
205 }
206
207 @Override
208 public ArrayList<Assignment<Prop>> refereeFunction(ArrayList<Assignment<Prop>>←
209     assignIn,
210     ArrayList<minAssignment<Prop←
211     >> bbaIn) {
212     if (assignIn==null) {
213         System.err.println("Error :: "+this.getClass().getName() +
214             ".refereeFunction(ArrayList<Assignment<Prop>>,ArrayList<B>)");

```

```

212         System.err.println("Error :: assignIn is null");
213         System.exit(0);
214     }
215     int i;
216     i=assignIn.size();
217     if(i<1) {
218         System.err.println("Error :: "+this.getClass().getName() +
219             ".refereeFunction(ArrayList<Assignment<Prop>>,ArrayList<B>)");
220         System.err.println("Error :: assignIn is empty");
221         System.exit(0);
222     }
223     if(theEntrySize!=i) {
224         theEntrySize=i;
225         weightTab = new double[theEntrySize+1];
226         mapTab= new int[theEntrySize+1];
227         thePropositionTab = new ArrayList<Prop>();
228         for(i=0;i<=theEntrySize;i++) {
229             thePropositionTab.add(null);
230         }
231     }
232     if(theZero==null) {
233         theZero=assignIn.get(0).attribute.instanceNsize().zero();
234         theOne=theZero.instanceNsize().one();
235     }
236     if(theDefault==null) theDefault=theZero;
237     ArrayList<Assignment<Prop>> arbitrament=null;
238     for(i=theEntrySize;i>0;i--) {
239         arbitrament=askWeightedSubset(i, assignIn);
240         if(arbitrament.size()>0) return arbitrament;
241     }
242     Assignment<Prop> finalAssignment = new Assignment<Prop>();
243     finalAssignment.attribute=theDefault.clone();
244     finalAssignment.value=1;
245     // NB: initialization of arbitrament is done in the loop
246     arbitrament.add(finalAssignment);
247     return arbitrament;
248 }
249
250 }

```

Source Code: RefereeFuserRTS.java

```

1  /*
2  *   RefereeFuserRTS.java : part of package RefereeToolbox; Implementation of
3  *   fuser by means of referee function.
4  *   ****
5  *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville
6  *
7  *   Author:   FrÃ©dÃ©ric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * Relaxed extension of {@link TreeSetRefereeFuser }.
30 *
31 * @author   <A href="http://email.fredericdambreville.com">FrÃ©dÃ©ric ↵
32 *           Dambreville</A>
33 *
34 *
35 * <BR><BR><table border='1' cellPadding='4'><tr><td>
36 * <font color="#008000" style="font-family: georgia">
37 * Copyright (c) 2010 FrÃ©dÃ©ric Dambreville<BR>
38 * <BR>
39 * RefereeToolbox is free software: you can redistribute it and/or modify
40 * it under the terms of the GNU General Public License as published by
41 * the Free Software Foundation, either version 3 of the License, or
42 * (at your option) any later version.<BR>
43 * <BR>
44 * RefereeToolbox is distributed in the hope that it will be useful,
45 * but WITHOUT ANY WARRANTY; without even the implied warranty of
46 * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
47 * GNU General Public License for more details.<BR>
48 * <BR>
49 * You should have received a copy of the GNU General Public License
50 * along with RefereeToolbox. If not, see
51 * <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
52 * </font></td></tr></table><BR>
53 *
54 */
55 public class RefereeFuserRTS < Prop extends Lattice<Prop>,
56                               B extends RefereeFuserRTS<Prop,B>>
57                               extends TreeSetRefereeFuser<Prop,B>
58                               implements RelaxedBBA<Prop,B> {
59
60     @Override
61     protected boolean relaxed() { return true; }
62
63
64     ///////////////////////////////////////////:
65     // public part
66     //////////////////////////////////////////
67
68 /**
69 * Relax <i>this</i> so that it contains no more than <i>maxMem</i> assignments.
70 *
71 */

```

```

72     @Override
73     public boolean relax(int maxMem) { return super.relax(maxMem); }
74
75     /**
76     * Relax <i>this</i> so that it contains no more than {@link RelaxedBBA#maxSize(↵
77         int) }
78     * assignments.
79     */
80     @Override
81     public boolean relax() { return super.relax(); }
82
83     /**
84     * Set or return the default maximum number of assignments stored in <i>this</i>,
85     * depending on parameter <i>newSize</i>.
86     * If <i>newSize>0</i>, then set the default maximum number of assignments to <i>↵
87         newSize</i>.
88     * In any case, return the actual value of the default maximum number.
89     * <BR><BR>
90     * N.B. It is not possible to exceed this number of assignments, except for ↵
91         temporary
92     * computed assignments.
93     */
94     @Override
95     public int maxSize(int newSize) { return super.maxSize(newSize); }

```

Source Code: RefereeSampler.java

```

1  /*
2  *   RefereeSampler.java : part of package RefereeToolbox; Implementation of
3  *   sampling-based fuser by means of referee function.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 import java.util.*;
29
30 /**
31 * This class implements a generic combination of Basic Belief Assignments by the
32 * means of referee functions and on the basis of a particle approximation. This
33 * class does not handle direct rule implementations, {@link BBAFuser}, or exact
34 * referee-based fusion {@link BBARefereeFuser}.
35 *
36 * @author      <A href="http://email.fredericdambreville.com">Frédéric ↵
37 *               Dambreville</A>
38 *
39 *
40 * <BR><BR><table border='1' cellPadding='4'><tr><td>
41 * <font color="#008000" style="font-family: georgia">
42 *   Copyright (c) 2010 Frédéric Dambreville<BR>
43 * <BR>
44 *   RefereeToolbox is free software: you can redistribute it and/or modify
45 *   it under the terms of the GNU General Public License as published by
46 *   the Free Software Foundation, either version 3 of the License, or
47 *   (at your option) any later version.<BR>
48 * <BR>
49 *   RefereeToolbox is distributed in the hope that it will be useful,
50 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
51 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
52 *   GNU General Public License for more details.<BR>
53 * <BR>
54 *   You should have received a copy of the GNU General Public License
55 *   along with RefereeToolbox. If not, see
56 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
57 * </font></td></tr></table><BR>
58 *
59 */
60 public class RefereeSampler<Prop extends Lattice<Prop>,
61                               sB extends RefereeSampler<Prop,sB> >
62                               extends TreeSetBBA<Prop,sB>
63                               implements SampledBBARefereeFuser<Prop↵
64                               ,sB> {
65
66     protected Prop theZero=null;
67
68     protected RefereeFunctionDefault<Prop> theRefereeFunction;
69
70     protected static Random rng = new Random();

```

```

71     protected boolean __updated=true;
72
73     protected double[] cumulativeDistribution_Sampler=null; // cumulative ↔
74         distribution is used // for sampling
75     protected double[] cumulativeDistribution_Mixer=null; // cumulative ↔
76         distribution is used // for sampling
77
78     protected ArrayList<Assignment<Prop>> mappedAttribute;
79
80     protected ArrayList<Assignment<Prop>> answeredAttribute;
81
82     protected int[] jumpTable_Sampler=null; // used for ensuring fast sampling
83
84     protected int[] jumpTable_Mixer=null; // used for ensuring fast sampling
85
86     protected ArrayList<minAssignment<Prop>> BBASources=new ArrayList<↔
87         minAssignment<Prop>>();
88
89     protected ArrayList<sB> fuserSources;
90
91     protected ArrayList<sB> mixerSources;
92
93     protected boolean setTables_sampler() {
94         Iterator iter = bbaTreeVA.iterator();
95         int size=bbaTreeVA.size();
96         cumulativeDistribution_Sampler=new double[size];
97         jumpTable_Sampler=new int[size];
98         mappedAttribute= new ArrayList<Assignment<Prop>>();
99         Assignment<Prop> assignment;
100         int i; // true variable
101         int k; // uniform variable
102         double Cumul=0.; // For computing law cumulatives
103         double uStep=1./size; // uniform step
104
105         for(i=0; iter.hasNext(); i++) { // compute the cumulative of inDist
106             assignment=(Assignment<Prop>) iter.next();
107             mappedAttribute.add(assignment);
108             Cumul+=assignment.value;
109             cumulativeDistribution_Sampler[i]=Cumul;
110         }
111         for(i=0; i<size; i++) cumulativeDistribution_Sampler[i]/=Cumul; // ↔
112             normalize it
113         jumpTable_Sampler[0]=(i=0);
114         Cumul=uStep;
115         for(k=1;k<size;k++) {
116             while(cumulativeDistribution_Sampler[i]<=Cumul) i++;
117             jumpTable_Sampler[k]=i;
118             Cumul+=uStep;
119         }
120         return true;
121     }
122
123     protected boolean setTables_mixer(double[] inDist) {
124         int i; // true variable
125         int k; // uniform variable
126         double Cumul=0.; // For computing law cumulatives
127         double uStep=1./inDist.length; // uniform step
128         cumulativeDistribution_Mixer=new double[inDist.length];
129         jumpTable_Mixer=new int[inDist.length];
130         for(i=0; i<inDist.length; i++) { // compute the cumulative of inDist
131             Cumul+=inDist[i];
132             cumulativeDistribution_Mixer[i]=Cumul;
133         }
134         for(i=0; i<inDist.length; i++)
135             cumulativeDistribution_Mixer[i]/=Cumul; // normalize it
136         jumpTable_Mixer[0]=(i=0);
137         Cumul=uStep;
138         for(k=1;k<inDist.length;k++) {
139             while(cumulativeDistribution_Mixer[i]<=Cumul) i++;
140             jumpTable_Mixer[k]=i;
141             Cumul+=uStep;

```

```

141     }
142     return true;
143 }
144
145 protected int drawTable_sampler() {
146     if(!_updated) if(!setTables_sampler()) return -1;
147     double x=rng.nextDouble();
148     int i=jumpTable_Sampler[((int) (jumpTable_Sampler.length*x))];
149     while (x>=cumulativeDistribution_Sampler[i]) i++;
150     return i;
151 }
152
153 protected int drawTable_mixer() {
154     double x=rng.nextDouble();
155     int i=jumpTable_Mixer[((int) (jumpTable_Mixer.length*x))];
156     while (x>=cumulativeDistribution_Mixer[i]) i++;
157     return i;
158 }
159
160
161 ///////////////////////////////////////////////////:
162 // public part
163 //////////////////////////////////////////////////
164
165 @Override
166 public void update_notification() { // called each time a change is done
167     super.update_notification();
168     _updated=true;
169 }
170
171 public double learnFrom(ArrayList<Assignment<Prop>> weightedSamples) {
172     int i,nbSamples;
173     double normalizer ,aValue,Z;
174     Prop aProposition;
175     Assignment<Prop> anAssignment;
176     nbSamples=weightedSamples.size();
177     Z=(normalizer=0.);
178
179     for(i=0;i<nbSamples;i++) {
180         anAssignment=weightedSamples.get(i);
181         aValue=anAssignment.value;
182         if(aValue<=0) {
183             System.err.println("Error :: "+this.getClass().getName() +
184                 ".learnFrom(ArrayList<Assignment<Prop>>)" );
185             System.err.println("Negative weight encountered");
186             System.exit(0);
187         }
188         aProposition = anAssignment.attribute;
189         if(theZero==null) theZero = aProposition.instanceNsize().zero();
190         if(aProposition.compareTo(theZero)==0) Z+=aValue;
191         else normalizer+=aValue;
192     }
193     clear();
194     for(i=0;i<nbSamples;i++) {
195         anAssignment=weightedSamples.get(i);
196         aValue=anAssignment.value/normalizer;
197         aProposition = anAssignment.attribute;
198         if(aProposition.compareTo(theZero)!=0) add(aProposition,aValue);
199     }
200     return Z/(Z+normalizer); // return the percentage of reject
201 }
202
203 public Assignment<Prop> makeSample() {
204     Assignment<Prop> assignment = new Assignment<Prop>();
205     assignment.value=1.;
206     assignment.attribute=mappedAttribute.get(drawTable_sampler()).attribute;
207     return assignment;
208 }
209
210 public boolean setFuser(sB left, sB right,
211     RefereeFunctionDefault<Prop> theRefereeFunction) {
212     ArrayList<sB> bbaTab= new ArrayList<sB>();
213     bbaTab.add(left);
214     bbaTab.add(right);

```

```

215         return setFuser(bbaTab, theRefereeFunction);
216     }
217
218     public boolean setFuser(ArrayList<sB> bbaIn,
219                             RefereeFunctionDefault<Prop> aRefereeFunction) {
220         int i;
221         theRefereeFunction=aRefereeFunction;
222         fuserSources=bbaIn;
223         BBASources.clear();
224         for(i=0;i<fuserSources.size();i++) BBASources.add(fuserSources.get(i));
225
226         for(i=0;i<bbaIn.size();i++) {
227             if(!bbaIn.get(i).setTables_sampler()) return false;
228         }
229         answeredAttribute=new ArrayList<Assignment<Prop>>();
230         for(i=0;i<bbaIn.size();i++) answeredAttribute.add(null);
231         return true;
232     }
233
234     public Assignment<Prop> makeFusedSample() {
235         Assignment<Prop> assignment = new Assignment<Prop>();
236         Assignment<Prop> assignmentFromSource;
237         ArrayList<Assignment<Prop>> fusedAssignment;
238         int i;
239         double cumul=0.;
240         double x=rng.nextDouble();
241         assignment.value=1.;
242         for(i=0;i<fuserSources.size();i++) {
243             sB aSource=fuserSources.get(i);
244             assignmentFromSource=aSource.mappedAttribute.get(aSource.↵
                drawTable_sampler());
245             answeredAttribute.set(i, assignmentFromSource);
246         }
247         fusedAssignment=theRefereeFunction.refereeFunction(answeredAttribute,↵
            BBASources);
248         for(i=0;i<fusedAssignment.size();i++) {
249             cumul+=fusedAssignment.get(i).value;
250             if(cumul>x) {
251                 assignment.attribute=fusedAssignment.get(i).attribute;
252                 return assignment;
253             }
254         }
255         return null;
256     }
257
258     public boolean setMixer(double[] weights, ArrayList<sB> bbaIn) {
259         if(weights.length!=bbaIn.size()) return false;
260         mixerSources=bbaIn;
261         return setTables_mixer(weights);
262     }
263
264     public sB makeMixedChoice() {
265         if(cumulativeDistribution_Mixer==null) return null;
266         int choice = drawTable_mixer();
267         return mixerSources.get(choice);
268     }
269 }

```

Source Code: RefereeToolbox_Tutorial.java

```

1  /*
2  *   RefereeToolbox_Tutorial.java : part of package RefereeToolbox; Tutorial.
3  *   ****
4  *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville
5  *
6  *   Author:   FrÃ©dÃ©ric Dambreville <http://email.fredericdambreville.com>
7  *
8  *   This file is part of RefereeToolbox.
9  *
10 *   RefereeToolbox is free software: you can redistribute it and/or modify
11 *   it under the terms of the GNU General Public License as published by
12 *   the Free Software Foundation, either version 3 of the License, or
13 *   (at your option) any later version.
14 *
15 *   RefereeToolbox is distributed in the hope that it will be useful,
16 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
17 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
18 *   GNU General Public License for more details.
19 *
20 *   You should have received a copy of the GNU General Public License
21 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
22 *   ****
23 */
24
25 package RefereeToolbox;
26
27 // juste pour tests
28 import java.util.*;
29
30 /**
31 * Class providing a tutorial for package RefereeToolbox.
32 *
33 * @author      <A href="http://email.fredericdambreville.com">FrÃ©dÃ©ric ↵
34 *              Dambreville</A>
35 *
36 *
37 * <BR><BR><table border='1' cellPadding='4'><tr><td>
38 * <font color="#008000" style="font-family: georgia">
39 *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville<BR>
40 * <BR>
41 *   RefereeToolbox is free software: you can redistribute it and/or modify
42 *   it under the terms of the GNU General Public License as published by
43 *   the Free Software Foundation, either version 3 of the License, or
44 *   (at your option) any later version.<BR>
45 * <BR>
46 *   RefereeToolbox is distributed in the hope that it will be useful,
47 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
48 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
49 *   GNU General Public License for more details.<BR>
50 * <BR>
51 *   You should have received a copy of the GNU General Public License
52 *   along with RefereeToolbox. If not, see
53 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
54 * </font></td></tr></table><BR>
55 *
56 */
57 public class RefereeToolbox_Tutorial {
58
59     /**
60     * Compare different referee functions applied with RefereeFuser and Powerset.
61     *
62     * <BR><BR>
63     * <b>Detailed code description.</b><BR>
64     * The following typonomic conventions are used:<BR>
65     * <code>
66     * <font color="#0000FF" style="font-family: georgia">
67     *   Blue color is used for commenting the following code.
68     * </font><BR>
69     *   code formatting is used for printing the code.<BR>
70     * <font color="#FF0000" style="font-family: georgia">
71     *   Red color is used for printing the possible output resulting of the

```

```

72 * previous code.
73 * </font>
74 * </code><BR>
75 * <BR><BR>
76 * Commented code:
77 * <BR><BR>
78 * <code>
79 * <font color="#0000FF" style="font-family: georgia">
80 * Declaration of proposition <i>A</i> as class <i>finalPowerset</i> and its
81 * creation;
82 * </font><BR>
83 * finalPowerset A=new finalPowerset();<BR>
84 * <font color="#0000FF" style="font-family: georgia">
85 * Set the size of the powerset to <i>3</i>; Then set <i>A</i> to the atomic
86 * proposition indexed by <i>0</i>;
87 * </font><BR>
88 * A.size(3); A.atomic(0);<BR>
89 * <font color="#0000FF" style="font-family: georgia">
90 * Declaration of <i>B</i> as <i>finalPowerset</i> and its creation and sizing
91 * as instance of <i>A</i>; Then set <i>B</i> to the atomic proposition  $\leftarrow$ 
    indexed
92 * by <i>1</i>;
93 * </font><BR>
94 * finalPowerset B=A.instanceNsize(); B.atomic(1);<BR>
95 * <font color="#0000FF" style="font-family: georgia">
96 * Declaration of <i>C</i> as <i>finalPowerset</i> and its creation and sizing
97 * as instance of <i>A</i>; Then set <i>C</i> to the atomic proposition  $\leftarrow$ 
    indexed
98 * by <i>2</i>;
99 * </font><BR>
100 * finalPowerset C=A.instanceNsize(); C.atomic(2);<BR>
101 * //<BR>
102 * <font color="#0000FF" style="font-family: georgia">
103 * Declaration of <i>AUB</i> as <i>finalPowerset</i> and its creation and  $\leftarrow$ 
    sizing
104 * as instance of <i>A</i>; Then set <i>AUB</i> to <i>A OR B</i>;
105 * </font><BR>
106 * finalPowerset AUB=A.instanceNsize(); AUB.or(A,B);<BR>
107 * <font color="#0000FF" style="font-family: georgia">
108 * Declaration of <i>BUC</i> as <i>finalPowerset</i> and its creation and  $\leftarrow$ 
    sizing
109 * as instance of <i>A</i>; Then set <i>BUC</i> to <i>B OR C</i>;
110 * <BR>
111 * Declaration of <i>CUA</i> as <i>finalPowerset</i> and its creation and  $\leftarrow$ 
    sizing
112 * as instance of <i>A</i>; Then set <i>CUA</i> to <i>C OR A</i>;
113 * </font><BR>
114 * finalPowerset BUC=A.instanceNsize(); BUC.or(B,C);<BR>
115 * finalPowerset CUA=A.instanceNsize(); CUA.or(C,A);<BR>
116 * //<BR>
117 * <font color="#0000FF" style="font-family: georgia">
118 * Declaration of <i>zero</i> as <i>finalPowerset</i> and its creation and  $\leftarrow$ 
    sizing
119 * as instance of <i>A</i>; Then set <i>zero</i> to zero;
120 * <BR>
121 * Declaration of <i>one</i> as <i>finalPowerset</i> and its creation and  $\leftarrow$ 
    sizing
122 * as instance of <i>A</i>; Then set <i>one</i> to one;
123 * </font><BR>
124 * finalPowerset zero=A.instanceNsize(); zero.zero();<BR>
125 * finalPowerset one=A.instanceNsize(); one.one();<BR>
126 * //<BR>
127 * //<BR>
128 * <font color="#0000FF" style="font-family: georgia">
129 * Declaration and creation of the referee function <i>referee1</i> as a  $\leftarrow$ 
    Dempster
130 * Shafer referee function on powerset;
131 * </font><BR>
132 * RFDempster_Powerset referee1 = new RFDempster_Powerset();<BR>
133 * <font color="#0000FF" style="font-family: georgia">
134 * Declaration and creation of the referee function <i>referee2</i> as a  $\leftarrow$ 
    Disjunctive
135 * referee function on powerset;<BR>
136 * Declaration and creation of the referee function <i>referee3</i> as a

```

```

137 * Dubois & Prade referee function on powerset;<BR>
138 * Declaration and creation of the referee function <i>referee4</i> as a PCR6
139 * referee function on powerset;<BR>
140 * Declaration and creation of the referee function <i>referee5</i> as a PCR#
141 * referee function on powerset;
142 * </font><BR>
143 * RFDisjunctive_Powerset referee2 = new RFDisjunctive_Powerset();<BR>
144 * RFDuboisPrade_Powerset referee3 = new RFDuboisPrade_Powerset();<BR>
145 * RFPCR6_Powerset referee4 = new RFPCR6_Powerset();<BR>
146 * RFPCRSharp_Powerset referee5 = new RFPCRSharp_Powerset();<BR>
147 * </BR>
148 * </BR>
149 * <font color="#0000FF" style="font-family: georgia">
150 * Declaration and creation of the basic belief assignment <i>aFuser1</i>, a
151 * bba defined over powerset and with the capability to handle fusion by means
152 * of referee functions (class {@link finalRefereeFuserRTS_Powerset});
153 * </font><BR>
154 * finalRefereeFuserRTS_Powerset aFuser1 = new finalRefereeFuserRTS_Powerset()←
    ;<BR>
155 * <font color="#0000FF" style="font-family: georgia">
156 * Add assignment <i>(A,0.09)</i> to bba <i>aFuser1</i>;
157 * </font><BR>
158 * aFuser1.add(A,0.09);<BR>
159 * <font color="#0000FF" style="font-family: georgia">
160 * Add assignment <i>(B,0.2)</i> to bba <i>aFuser1</i>;<BR>
161 * Add assignment <i>(C,0.02)</i> to bba <i>aFuser1</i>;<BR>
162 * Add assignment <i>(AUB,0.05)</i> to bba <i>aFuser1</i>;<BR>
163 * Add assignment <i>(BUC,0.03)</i> to bba <i>aFuser1</i>;<BR>
164 * Add assignment <i>(CUA,0.1)</i> to bba <i>aFuser1</i>;
165 * </font><BR>
166 * aFuser1.add(B,0.2);<BR>
167 * aFuser1.add(C,0.02);<BR>
168 * aFuser1.add(AUB,0.05);<BR>
169 * aFuser1.add(BUC,0.03);<BR>
170 * aFuser1.add(CUA,0.1);<BR>
171 * <font color="#0000FF" style="font-family: georgia">
172 * Add assignment <i>(A,0.11)</i> to bba <i>aFuser1</i>. This assignment is
173 * <i>added</i> to previously added assignment <i>(A,0.09)</i>, resulting in
174 * total assignment <i>(A,0.2)</i>;
175 * </font><BR>
176 * aFuser1.add(A,0.11);<BR>
177 * <font color="#0000FF" style="font-family: georgia">
178 * Add assignment <i>(one,0.4)</i> to bba <i>aFuser1</i>;
179 * </font><BR>
180 * aFuser1.add(one,0.4);<BR>
181 * </BR>
182 * <font color="#0000FF" style="font-family: georgia">
183 * Declaration and creation of the basic belief assignment <i>aFuser2</i>, a
184 * bba defined over powerset and with the capability to handle fusion by means
185 * of referee functions (class {@link finalRefereeFuserRTS_Powerset});
186 * </font><BR>
187 * finalRefereeFuserRTS_Powerset aFuser2 = aFuser1.instance();<BR>
188 * <font color="#0000FF" style="font-family: georgia">
189 * Add assignment <i>(A,0.1)</i> to bba <i>aFuser2</i>;<BR>
190 * Add assignment <i>(B,0.1)</i> to bba <i>aFuser2</i>;<BR>
191 * Add assignment <i>(C,0.2)</i> to bba <i>aFuser2</i>;<BR>
192 * Add assignment <i>(AUB,0.2)</i> to bba <i>aFuser2</i>;<BR>
193 * Add assignment <i>(BUC,0.1)</i> to bba <i>aFuser2</i>;<BR>
194 * Add assignment <i>(CUA,0.1)</i> to bba <i>aFuser2</i>;<BR>
195 * Add assignment <i>(one,0.2)</i> to bba <i>aFuser2</i>;
196 * </font><BR>
197 * aFuser2.add(A,0.1);<BR>
198 * aFuser2.add(B,0.1);<BR>
199 * aFuser2.add(C,0.2);<BR>
200 * aFuser2.add(AUB,0.2);<BR>
201 * aFuser2.add(BUC,0.1);<BR>
202 * aFuser2.add(CUA,0.1);<BR>
203 * aFuser2.add(one,0.2);<BR>
204 * </BR>
205 * <font color="#0000FF" style="font-family: georgia">
206 * Declaration and creation of the basic belief assignment <i>aFuser</i>, a
207 * bba defined over powerset and with the capability to handle fusion by means
208 * of referee functions (class {@link finalRefereeFuserRTS_Powerset});
209 * </font><BR>

```

```

210 * finalRefereeFuserRTS_Powerset aFuser = aFuser1.instance();<BR>
211 * //<BR>
212 * <font color="#0000FF" style="font-family: georgia">
213 * Define a common print mode <i>printMode</i> for the bba state.
214 * This variable, set to <i>1</i>, implies the print to be according to the
215 * proposition order;
216 * </font><BR>
217 * int printMode=1;<BR>
218 * <font color="#0000FF" style="font-family: georgia">
219 * Print the title of the method;
220 * </font><BR>
221 * System.out.println(<BR>
222 * &nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&~
223 * "////////////////////////////////////\n" +<BR>
224 * &nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&~
225 * "// Relaxed Method\n" +<BR>
226 * &nbsp;&nbsp;&nbsp;&nbsp;&~
227 * "////////////////////////////////////\n");<BR>
228 * <font color="#FF0000" style="font-family: georgia">
229 * //////////////////////////////////<BR>
230 * // Relaxed Method<BR>
231 * //////////////////////////////////
232 * </font><BR>
233 * System.out.println("aFuser1");<BR>
234 * <font color="#FF0000" style="font-family: georgia">
235 * aFuser1
236 * </font><BR>
237 * <font color="#0000FF" style="font-family: georgia">
238 * Print the state of <i>aFuser1</i>. With option <i>printMode=1</i>, the
239 * print is
240 * done according to the proposition order;
241 * </font><BR>
242 * &nbsp;&nbsp;&~
243 * System.out.println(aFuser1.state(printMode));<BR>
244 * <font color="#FF0000" style="font-family: georgia">
245 * bbaTreeA:<BR>
246 * x000000000000000001 -> 0.2<BR>
247 * x000000000000000002 -> 0.2<BR>
248 * x000000000000000003 -> 0.05<BR>
249 * x000000000000000004 -> 0.02<BR>
250 * x000000000000000005 -> 0.1<BR>
251 * x000000000000000006 -> 0.03<BR>
252 * x000000000000000007 -> 0.4
253 * </font><BR>
254 * &nbsp;&~
255 * System.out.println();<BR>
256 * <font color="#0000FF" style="font-family: georgia">
257 * Print the state of <i>aFuser2</i>. With option <i>printMode=1</i>, the
258 * print is
259 * done according to the proposition order;
260 * </font><BR>
261 * System.out.println("aFuser2");<BR>
262 * &nbsp;&~
263 * System.out.println(aFuser2.state(printMode));<BR>
264 * &nbsp;&~
265 * System.out.println();<BR>
266 * <font color="#FF0000" style="font-family: georgia">
267 * aFuser2<BR>
268 * bbaTreeA:<BR>
269 * x000000000000000001 -> 0.1<BR>
270 * x000000000000000002 -> 0.1<BR>
271 * x000000000000000003 -> 0.2<BR>
272 * x000000000000000004 -> 0.2<BR>
273 * x000000000000000005 -> 0.1<BR>
274 * x000000000000000006 -> 0.1<BR>
275 * x000000000000000007 -> 0.2
276 * </font><BR>
277 * <font color="#0000FF" style="font-family: georgia">
278 * Set <i>aFuser</i> as the fusion of <i>aFuser1</i> and <i>aFuser2</i>,
279 * according
280 * to the referee function <i>referee1</i>. As a result, a Dempster Shafer
281 * combination is done;
282 * </font><BR>
283 * aFuser.fuse(aFuser1,aFuser2.referee1);<BR>

```



```

350 * <font color="#FF0000" style="font-family: georgia">
351 * aFuser - Dubois & Prade<BR>
352 * Conflict Z = 0.0 %
353 * bbaTreeA:<BR>
354 * x000000000000000001 -> 0.2<BR>
355 * x000000000000000002 -> 0.17900000000000002<BR>
356 * x000000000000000003 -> 0.14<BR>
357 * x000000000000000004 -> 0.131<BR>
358 * x000000000000000005 -> 0.11199999999999999<BR>
359 * x000000000000000006 -> 0.09100000000000001<BR>
360 * x000000000000000007 -> 0.147
361 * </font><BR>
362 * <font color="#0000FF" style="font-family: georgia">
363 * Set <i>aFuser</i> as the fusion of <i>aFuser1</i> and <i>aFuser2</i>, ←
    according
364 * to the referee function <i>referee4</i>. As a result , a PCR6 combination
365 * is done;
366 * </font><BR>
367 * aFuser.fuse(aFuser1,aFuser2,referee4);<BR>
368 * <font color="#0000FF" style="font-family: georgia">
369 * Print the state of <i>aFuser</i>. With option <i>printMode=1</i>, the print←
    is
370 * done according to the proposition order;
371 * </font><BR>
372 * &nbsp; &nbsp; ;
373 * System.out.println("aFuser - PCR6");<BR>
374 * &nbsp; &nbsp; ; System.out.println("Conflict Z = "+aFuser.conflict()+" %");
375 * &nbsp; &nbsp; ;
376 * System.out.println(aFuser.state(printMode));<BR>
377 * &nbsp; &nbsp; ;
378 * System.out.println();<BR>
379 * <font color="#FF0000" style="font-family: georgia">
380 * aFuser - PCR6<BR>
381 * Conflict Z = 0.0 %
382 * bbaTreeA:<BR>
383 * x000000000000000001 -> 0.2573076923076923<BR>
384 * x000000000000000002 -> 0.23900000000000005<BR>
385 * x000000000000000003 -> 0.10563636363636364<BR>
386 * x000000000000000004 -> 0.18003030303030304<BR>
387 * x000000000000000005 -> 0.08166666666666668<BR>
388 * x000000000000000006 -> 0.056358974358974356<BR>
389 * x000000000000000007 -> 0.08
390 * </font><BR>
391 * <font color="#0000FF" style="font-family: georgia">
392 * Set <i>aFuser</i> as the fusion of <i>aFuser1</i> and <i>aFuser2</i>, ←
    according
393 * to the referee function <i>referee5</i>. As a result , a PCR# combination
394 * is done;
395 * </font><BR>
396 * aFuser.fuse(aFuser1,aFuser2,referee5);<BR>
397 * <font color="#0000FF" style="font-family: georgia">
398 * Print the state of <i>aFuser</i>. With option <i>printMode=1</i>, the print←
    is
399 * done according to the proposition order;
400 * </font><BR>
401 * &nbsp; &nbsp; ;
402 * System.out.println("aFuser - PCR#");<BR>
403 * &nbsp; &nbsp; ; System.out.println("Conflict Z = "+aFuser.conflict()+" %");
404 * &nbsp; &nbsp; ;
405 * System.out.println(aFuser.state(printMode));<BR>
406 * &nbsp; &nbsp; ;
407 * System.out.println();<BR>
408 * <font color="#FF0000" style="font-family: georgia">
409 * aFuser - PCR#<BR>
410 * Conflict Z = 0.0 %
411 * bbaTreeA:<BR>
412 * x000000000000000001 -> 0.2573076923076923<BR>
413 * x000000000000000002 -> 0.23900000000000005<BR>
414 * x000000000000000003 -> 0.10563636363636364<BR>
415 * x000000000000000004 -> 0.18003030303030304<BR>
416 * x000000000000000005 -> 0.08166666666666668<BR>
417 * x000000000000000006 -> 0.056358974358974356<BR>
418 * x000000000000000007 -> 0.08
419 * </font><BR>

```

```

420 * <BR>
421 * </code>
422 *
423 */
424 public void RefereeFuserRTS_Comparison() {
425     finalPowerSet A=new finalPowerSet();
426     A.size(3); A.atomic(0);
427     finalPowerSet B=A.instanceNsize(); B.atomic(1);
428     finalPowerSet C=A.instanceNsize(); C.atomic(2);
429     //
430     finalPowerSet AUB=A.instanceNsize(); AUB.or(A,B);
431     finalPowerSet BUC=A.instanceNsize(); BUC.or(B,C);
432     finalPowerSet CUA=A.instanceNsize(); CUA.or(C,A);
433     //
434     finalPowerSet zero=A.instanceNsize(); zero.zero();
435     finalPowerSet one=A.instanceNsize(); one.one();
436     //
437     //
438     RFDempster_PowerSet referee1 = new RFDempster_PowerSet();
439     RFDisjunctive_PowerSet referee2 = new RFDisjunctive_PowerSet();
440     RFDuboisPrade_PowerSet referee3 = new RFDuboisPrade_PowerSet();
441     RFPfCR6_PowerSet referee4 = new RFPfCR6_PowerSet();
442     RFPfCRSharp_PowerSet referee5 =new RFPfCRSharp_PowerSet();
443     //
444     //
445     finalRefereeFuserRTS_PowerSet aFuser1 = new finalRefereeFuserRTS_PowerSet←
        ();
446     aFuser1.add(A,0.09);
447     aFuser1.add(B,0.2);
448     aFuser1.add(C,0.02);
449     aFuser1.add(AUB,0.05);
450     aFuser1.add(BUC,0.03);
451     aFuser1.add(CUA,0.1);
452     aFuser1.add(A,0.11);
453     aFuser1.add(one,0.4);
454     //
455     finalRefereeFuserRTS_PowerSet aFuser2 = aFuser1.instance();
456     aFuser2.add(A,0.1);
457     aFuser2.add(B,0.1);
458     aFuser2.add(C,0.2);
459     aFuser2.add(AUB,0.2);
460     aFuser2.add(BUC,0.1);
461     aFuser2.add(CUA,0.1);
462     aFuser2.add(one,0.2);
463     //
464     finalRefereeFuserRTS_PowerSet aFuser = aFuser1.instance();
465     //
466
467     int printMode=1;
468
469     System.out.println(
470         "////////////////////////////////////////\n" +
471         "/// Relaxed Method\n" +
472         "////////////////////////////////////////\n");
473
474     System.out.println("aFuser1");
475     System.out.println(aFuser1.state(printMode));
476     System.out.println();
477     System.out.println("aFuser2");
478     System.out.println(aFuser2.state(printMode));
479     System.out.println();
480     aFuser.fuse(aFuser1,aFuser2,referee1);
481     System.out.println("aFuser - Dempster");
482     System.out.println("Conflict Z = "+aFuser.conflict()+" %");
483     System.out.println(aFuser.state(printMode));
484     System.out.println();
485     aFuser.fuse(aFuser1,aFuser2,referee2);
486     System.out.println("aFuser - Disjunctive");
487     System.out.println("Conflict Z = "+aFuser.conflict()+" %");
488     System.out.println(aFuser.state(printMode));
489     System.out.println();
490     aFuser.fuse(aFuser1,aFuser2,referee3);
491     System.out.println("aFuser - Dubois & Prade");
492     System.out.println("Conflict Z = "+aFuser.conflict()+" %");

```

```

493         System.out.println(aFuser.state(printMode));
494         System.out.println();
495         aFuser.fuse(aFuser1,aFuser2,referee4);
496         System.out.println("aFuser - PCR6");
497         System.out.println("Conflict Z = "+aFuser.conflict()+" %");
498         System.out.println(aFuser.state(printMode));
499         System.out.println();
500         aFuser.fuse(aFuser1,aFuser2,referee5);
501         System.out.println("aFuser - PCR#");
502         System.out.println("Conflict Z = "+aFuser.conflict()+" %");
503         System.out.println(aFuser.state(printMode));
504         System.out.println();
505     }
506 }
507
508 /**
509  * Compare different referee functions applied with RefereeSampler and  $\leftrightarrow$ 
510     Powerset.
511     *
512     * <b>Detailed code description.</b><br>
513     * The following typonomic conventions are used:<br>
514     * <code>
515     * <font color="#0000FF" style="font-family: georgia">
516     * Blue color is used for commenting the following code.
517     * </font><br>
518     * code formatting is used for printing the code.<br>
519     * <font color="#FF0000" style="font-family: georgia">
520     * Red color is used for printing the possible output resulting of the
521     * previous code.
522     * </font>
523     * </code><br>
524     * <br><br>
525     * Commented code:
526     * <br><br>
527     * <code>
528     * <font color="#0000FF" style="font-family: georgia">
529     * Declaration of proposition <i>A</i> as class <i>finalPowerset</i> and its
530     * creation;
531     * </font><br>
532     * finalPowerset A=new finalPowerset();<br>
533     * <font color="#0000FF" style="font-family: georgia">
534     * Set the size of the powerset to <i>3</i>; Then set <i>A</i> to the atomic
535     * proposition indexed by <i>0</i>;
536     * </font><br>
537     * A.size(3); A.atomic(0);<br>
538     * <font color="#0000FF" style="font-family: georgia">
539     * Declaration of <i>B</i> as <i>finalPowerset</i> and its creation and sizing
540     * as instance of <i>A</i>; Then set <i>B</i> to the atomic proposition  $\leftrightarrow$ 
541     * indexed
542     * by <i>1</i>;
543     * </font><br>
544     * finalPowerset B=A.instanceNsize(); B.atomic(1);<br>
545     * <font color="#0000FF" style="font-family: georgia">
546     * Declaration of <i>C</i> as <i>finalPowerset</i> and its creation and sizing
547     * as instance of <i>A</i>; Then set <i>C</i> to the atomic proposition  $\leftrightarrow$ 
548     * indexed
549     * by <i>2</i>;
550     * </font><br>
551     * finalPowerset C=A.instanceNsize(); C.atomic(2);<br>
552     * <br>
553     * <font color="#0000FF" style="font-family: georgia">
554     * Declaration of <i>AUB</i> as <i>finalPowerset</i> and its creation and  $\leftrightarrow$ 
555     * sizing
556     * as instance of <i>A</i>; Then set <i>AUB</i> to <i>A OR B</i>;
557     * </font><br>
558     * finalPowerset AUB=A.instanceNsize(); AUB.or(A,B);<br>
559     * <font color="#0000FF" style="font-family: georgia">
560     * Declaration of <i>BUC</i> as <i>finalPowerset</i> and its creation and  $\leftrightarrow$ 
561     * sizing
562     * as instance of <i>A</i>; Then set <i>BUC</i> to <i>B OR C</i>;
563     * <br>
564     * Declaration of <i>CUA</i> as <i>finalPowerset</i> and its creation and  $\leftrightarrow$ 
565     * sizing

```

```

561 * as instance of <i>A</i>; Then set <i>CUA</i> to <i>C OR A</i>;
562 * </font><BR>
563 * finalPowerset BUC=A.instanceNsize(); BUC.or(B,C);<BR>
564 * finalPowerset CUA=A.instanceNsize(); CUA.or(C,A);<BR>
565 * </font><BR>
566 * <font color="#0000FF" style="font-family: georgia">
567 * Declaration of <i>zero</i> as <i>finalPowerset</i> and its creation and ←
    sizing
568 * as instance of <i>A</i>; Then set <i>zero</i> to zero;
569 * <BR>
570 * Declaration of <i>one</i> as <i>finalPowerset</i> and its creation and ←
    sizing
571 * as instance of <i>A</i>; Then set <i>one</i> to one;
572 * </font><BR>
573 * finalPowerset zero=A.instanceNsize(); zero.zero();<BR>
574 * finalPowerset one=A.instanceNsize(); one.one();<BR>
575 * </font><BR>
576 * </font><BR>
577 * <font color="#0000FF" style="font-family: georgia">
578 * Declaration and creation of the referee function <i>referee1</i> as a ←
    Dempster
579 * Shafer referee function on powerset;
580 * </font><BR>
581 * RFDempster_Powerset referee1 = new RFDempster_Powerset();<BR>
582 * <font color="#0000FF" style="font-family: georgia">
583 * Declaration and creation of the referee function <i>referee2</i> as a ←
    Disjunctive
584 * referee function on powerset;<BR>
585 * Declaration and creation of the referee function <i>referee3</i> as a
    Dubois & Prade referee function on powerset;<BR>
586 * Declaration and creation of the referee function <i>referee4</i> as a PCR6
    referee function on powerset;<BR>
587 * Declaration and creation of the referee function <i>referee5</i> as a PCR#
    referee function on powerset;
588 * </font><BR>
589 * RFDdisjunctive_Powerset referee2 = new RFDdisjunctive_Powerset();<BR>
590 * RFDDuboisPrade_Powerset referee3 = new RFDuboisPrade_Powerset();<BR>
591 * RFPPCR6_Powerset referee4 = new RFPPCR6_Powerset();<BR>
592 * RFPPCRSharp_Powerset referee5 =new RFPPCRSharp_Powerset();<BR>
593 * </font><BR>
594 * </font><BR>
595 * <font color="#0000FF" style="font-family: georgia">
596 * Declaration and creation of the basic belief assignment <i>aSampler1</i>, a
    bba defined over powerset and with the capability to handle fusion by means
    of referee sampling (class {@link finalRefereeSampler_Powerset});
597 * </font><BR>
598 * finalRefereeSampler_Powerset aSampler1 = new finalRefereeSampler_Powerset()←
    ;<BR>
599 * <font color="#0000FF" style="font-family: georgia">
600 * Add assignment <i>(A,0.09)</i> to bba <i>aSampler1</i>;
601 * </font><BR>
602 * aSampler1.add(A,0.09);<BR>
603 * <font color="#0000FF" style="font-family: georgia">
604 * Add assignment <i>(B,0.2)</i> to bba <i>aSampler1</i>;<BR>
605 * Add assignment <i>(C,0.02)</i> to bba <i>aSampler1</i>;<BR>
606 * Add assignment <i>(AUB,0.05)</i> to bba <i>aSampler1</i>;<BR>
607 * Add assignment <i>(BUC,0.03)</i> to bba <i>aSampler1</i>;<BR>
608 * Add assignment <i>(CUA,0.1)</i> to bba <i>aSampler1</i>;
609 * </font><BR>
610 * aSampler1.add(B,0.2);<BR>
611 * aSampler1.add(C,0.02);<BR>
612 * aSampler1.add(AUB,0.05);<BR>
613 * aSampler1.add(BUC,0.03);<BR>
614 * aSampler1.add(CUA,0.1);<BR>
615 * <font color="#0000FF" style="font-family: georgia">
616 * Add assignment <i>(A,0.11)</i> to bba <i>aSampler1</i>. This assignment is
    <i>added</i> to previously added assignment <i>(A,0.09)</i>, resulting in
    total assignment <i>(A,0.2)</i>;
617 * </font><BR>
618 * aSampler1.add(A,0.11);<BR>
619 * <font color="#0000FF" style="font-family: georgia">
620 * Add assignment <i>(one,0.4)</i> to bba <i>aSampler1</i>;
621 * </font><BR>
622 * aSampler1.add(one,0.4);<BR>
623 * </font><BR>
624 * </font><BR>
625 * </font><BR>
626 * </font><BR>
627 * </font><BR>
628 * </font><BR>
629 * </font><BR>

```

```

630 * //<BR>
631 * <font color="#0000FF" style="font-family: georgia">
632 * Declaration and creation of the basic belief assignment <i>aSampler2</i>, a
633 * bba defined over powerset and with the capability to handle fusion by means
634 * of referee sampling (class {@link finalRefereeSampler_Powerset});
635 * </font><BR>
636 * finalRefereeSampler_Powerset aSampler2 = aSampler1.instance();<BR>
637 * <font color="#0000FF" style="font-family: georgia">
638 * Add assignment <i>(A,0.1)</i> to bba <i>aSampler2</i>;<BR>
639 * Add assignment <i>(B,0.1)</i> to bba <i>aSampler2</i>;<BR>
640 * Add assignment <i>(C,0.2)</i> to bba <i>aSampler2</i>;<BR>
641 * Add assignment <i>(AUB,0.2)</i> to bba <i>aSampler2</i>;<BR>
642 * Add assignment <i>(BUC,0.1)</i> to bba <i>aSampler2</i>;<BR>
643 * Add assignment <i>(CUA,0.1)</i> to bba <i>aSampler2</i>;<BR>
644 * Add assignment <i>(one,0.2)</i> to bba <i>aSampler2</i>;
645 * </font><BR>
646 * aSampler2.add(A,0.1);<BR>
647 * aSampler2.add(B,0.1);<BR>
648 * aSampler2.add(C,0.2);<BR>
649 * aSampler2.add(AUB,0.2);<BR>
650 * aSampler2.add(BUC,0.1);<BR>
651 * aSampler2.add(CUA,0.1);<BR>
652 * aSampler2.add(one,0.2);<BR>
653 * //<BR>
654 * <font color="#0000FF" style="font-family: georgia">
655 * Declaration and creation of the basic belief assignment <i>aSampler</i>, a
656 * bba defined over powerset and with the capability to handle fusion by means
657 * of referee sampling (class {@link finalRefereeSampler_Powerset});
658 * </font><BR>
659 * finalRefereeSampler_Powerset aSampler = aSampler1.instance();<BR>
660 * //<BR>
661 * <font color="#0000FF" style="font-family: georgia">
662 * Define a common print mode <i>printMode</i> for the bba state.
663 * This variable, set to <i>1</i>, implies the print to be according to the
664 * proposition order;
665 * </font><BR>
666 * int printMode=1;<BR>
667 * <font color="#0000FF" style="font-family: georgia">
668 * Print the title of the method;
669 * </font><BR>
670 * System.out.println(<BR>
671 * &nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&
672 * "////////////////////////////////////////\n" +<BR>
673 * &nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&
674 * "/// Sampling Method\n" +<BR>
675 * &nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&
676 * "////////////////////////////////////////\n");<BR>
677 * <font color="#FF0000" style="font-family: georgia">
678 * //////////////////////////////////////////<BR>
679 * // Sampling Method<BR>
680 * //////////////////////////////////////////
681 * </font><BR>
682 *
683 * <font color="#0000FF" style="font-family: georgia">
684 * Variables declaration.
685 * <i>n</i> and <i>Z</i> are instrumental and used for sample indices and ↵
686 * contradiction
687 * degree repectively.
688 * <i>NbSamples</i> stores the number of samples generated by each computation↵
689 * ;
690 * </font><BR>
691 * int n;<BR>
692 * int NbSamples=1000000;<BR>
693 * double Z;<BR>
694 *
695 * <font color="#0000FF" style="font-family: georgia">
696 * Declaration and creation of the basic belief assignment <i>Samples</i>. ↵
697 * This
698 * bba is instrumental and used for computing the samples statistic ↵
699 * incrementally;
700 * </font><BR>
701 * finalRefereeSampler_Powerset Samples= aSampler1.instance();<BR>
702 * <font color="#0000FF" style="font-family: georgia">
703 * Print the state of <i>aSampler1</i>. With option <i>printMode=1</i>, the ↵

```

```

700     print is
701     * done according to the proposition order;
702     * </font><BR>
703     * System.out.println("aSampler1");<BR>
704     * &nbsp; &nbsp; System.out.println(aSampler1.state(printMode));<BR>
705     * <font color="#FF0000" style="font-family: georgia">
706     * aSampler1<BR>
707     * bbaTreeA:<BR>
708     * x0000000000000001 -> 0.2<BR>
709     * x0000000000000002 -> 0.2<BR>
710     * x0000000000000003 -> 0.05<BR>
711     * x0000000000000004 -> 0.02<BR>
712     * x0000000000000005 -> 0.1<BR>
713     * x0000000000000006 -> 0.03<BR>
714     * x0000000000000007 -> 0.4
715     * </font><BR>
716     * &nbsp; &nbsp; System.out.println();<BR>
717     * <font color="#0000FF" style="font-family: georgia">
718     * Print the state of <i>aSampler2</i>. With option <i>printMode=1</i>, the
719     * print is done according to the proposition order;
720     * </font><BR>
721     * System.out.println("aSampler2");<BR>
722     * &nbsp; &nbsp; System.out.println(aSampler2.state(printMode));<BR>
723     * &nbsp; &nbsp; System.out.println();<BR>
724     * //<BR>
725     * <font color="#FF0000" style="font-family: georgia">
726     * aSampler2<BR>
727     * bbaTreeA:<BR>
728     * x0000000000000001 -> 0.1<BR>
729     * x0000000000000002 -> 0.1<BR>
730     * x0000000000000003 -> 0.2<BR>
731     * x0000000000000004 -> 0.2<BR>
732     * x0000000000000005 -> 0.1<BR>
733     * x0000000000000006 -> 0.1<BR>
734     * x0000000000000007 -> 0.2
735     * </font><BR>
736     * <font color="#0000FF" style="font-family: georgia">
737     * Initialize the fuser of <i>aSampler</i> with bba enties <i>aFuser1</i> and
738     * <i>aFuser2</i>, and with the referee function <i>referee1</i> (Dempster ←
739     * Shafer);
740     * </font><BR>
741     * aSampler.setFuser(aSampler1, aSampler2, referee1);<BR>
742     * <font color="#0000FF" style="font-family: georgia">
743     * Clear the samples container <i>Samples</i>;
744     * </font><BR>
745     * Samples.clear();<BR>
746     * <font color="#0000FF" style="font-family: georgia">
747     * Build the samples (<i>NbSamples</i> times) fused by means of the fuser and
748     * store them within the container;
749     * </font><BR>
750     * {@code for (n=0;n<NbSamples;n++) Samples.add(aSampler.makeFusedSample());}<←
751     * <font color="#0000FF" style="font-family: georgia">
752     * Learn the bba <i>aSampler</i> from the samples <i>Samples</i> and store the
753     * percentage of conflict samples within <i>Z</i>;
754     * </font><BR>
755     * Z=aSampler.learnFrom(Samples.toArray());<BR>
756     * <font color="#0000FF" style="font-family: georgia">
757     * Print the conflict and the state of <i>aSampler</i> (these results are ←
758     * random).
759     * With option <i>printMode=1</i>, the print is done according to the ←
760     * proposition
761     * order;
762     * </font><BR>
763     * System.out.println("aSampler - Dempster --- " + NbSamples + " particles");<←
764     * &nbsp; &nbsp; System.out.println("Conflict Z = "+Z+" %");<BR>
765     * &nbsp; &nbsp; System.out.println(aSampler.state(printMode));<BR>
766     * &nbsp; &nbsp; System.out.println();<BR>
767     * &nbsp; &nbsp; //<BR>
768     * <font color="#FF0000" style="font-family: georgia">
769     * aSampler - Dempster --- 100000 particles<BR>

```

```

768 * Conflict Z = 0.190523 %<BR>
769 * bbaTreeA:<BR>
770 * x000000000000000001 -> 0.2474844868970953<BR>
771 * x000000000000000002 -> 0.2219408334023079<BR>
772 * x000000000000000003 -> 0.1233846051215785<BR>
773 * x000000000000000004 -> 0.16099654468255428<BR>
774 * x000000000000000005 -> 0.08678813604339593<BR>
775 * x000000000000000006 -> 0.06061197538657676<BR>
776 * x000000000000000007 -> 0.09879341846649133<BR>
777 * </font><BR>
778 *
779 * <font color="#0000FF" style="font-family: georgia">
780 * Initialize the fuser of <i>aSampler</i> with bba enties <i>aFuser1</i> and
781 * <i>aFuser2</i>, and with the referee function <i>referee2</i> (Disjunctive)<←
782 * </font><BR>
783 * aSampler.setFuser(aSampler1, aSampler2, referee2);<BR>
784 * <font color="#0000FF" style="font-family: georgia">
785 * Clear the samples container <i>Samples</i>;
786 * </font><BR>
787 * Samples.clear();<BR>
788 * <font color="#0000FF" style="font-family: georgia">
789 * Build the samples (<i>NbSamples</i> times) fused by means of the fuser and
790 * store them within the container;
791 * </font><BR>
792 * { @code for (n=0;n<NbSamples;n++) Samples.add(aSampler.makeFusedSample()); }<←
793 * <font color="#0000FF" style="font-family: georgia">
794 * Learn the bba <i>aSampler</i> from the samples <i>Samples</i> and store the
795 * percentage of conflict samples within <i>Z</i>;
796 * </font><BR>
797 * Z=aSampler.learnFrom(Samples.toArray());<BR>
798 * <font color="#0000FF" style="font-family: georgia">
799 * Print the conflict and the state of <i>aSampler</i> (these results are <←
800 * random).
801 * With option <i>printMode=1</i>, the print is done according to the <←
802 * proposition
803 * order;
804 * </font><BR>
805 * System.out.println("aSampler - Disjunctive — " + NbSamples + " particles")<←
806 * <BR>
807 * &nbsp; &nbsp; &nbsp; System.out.println("Conflict Z = "+Z+" %");<BR>
808 * &nbsp; &nbsp; &nbsp; System.out.println(aSampler.state(printMode));<BR>
809 * &nbsp; &nbsp; &nbsp; System.out.println();<BR>
810 * &nbsp; &nbsp; &nbsp; //<BR>
811 * <font color="#FF0000" style="font-family: georgia">
812 * aSampler - Disjunctive — 1000000 particles<BR>
813 * Conflict Z = 0.0 %<BR>
814 * bbaTreeA:<BR>
815 * x000000000000000001 -> 0.01991<BR>
816 * x000000000000000002 -> 0.019988<BR>
817 * x000000000000000003 -> 0.139937<BR>
818 * x000000000000000004 -> 0.004052<BR>
819 * x000000000000000005 -> 0.103861<BR>
820 * x000000000000000006 -> 0.075948<BR>
821 * x000000000000000007 -> 0.636304
822 * </font><BR>
823 *
824 * <font color="#0000FF" style="font-family: georgia">
825 * Initialize the fuser of <i>aSampler</i> with bba enties <i>aFuser1</i> and
826 * <i>aFuser2</i>, and with the referee function <i>referee3</i> (Dubois & <←
827 * Prade);
828 * </font><BR>
829 * aSampler.setFuser(aSampler1, aSampler2, referee3);<BR>
830 * <font color="#0000FF" style="font-family: georgia">
831 * Clear the samples container <i>Samples</i>;
832 * </font><BR>
833 * Samples.clear();<BR>
834 * <font color="#0000FF" style="font-family: georgia">
835 * Build the samples (<i>NbSamples</i> times) fused by means of the fuser and
836 * store them within the container;
837 * </font><BR>
838 * { @code for (n=0;n<NbSamples;n++) Samples.add(aSampler.makeFusedSample()); }<←
839 * <BR>

```

```

835 * <font color="#0000FF" style="font-family: georgia">
836 * Learn the bba <i>aSampler</i> from the samples <i>Samples</i> and store the
837 * percentage of conflict samples within <i>Z</i>;
838 * </font><BR>
839 * Z=aSampler.learnFrom(Samples.toArray());<BR>
840 * <font color="#0000FF" style="font-family: georgia">
841 * Print the conflict and the state of <i>aSampler</i> (these results are ←
      random).
842 * With option <i>printMode=1</i>, the print is done according to the ←
      proposition
843 * order;
844 * </font><BR>
845 * System.out.println("aSampler - Dubois & Prade — " + NbSamples + " ←
      particles");<BR>
846 * &nbsp; &nbsp; &nbsp; System.out.println(" Conflict Z = "+Z+" %");<BR>
847 * &nbsp; &nbsp; &nbsp; System.out.println(aSampler.state(printMode));<BR>
848 * &nbsp; &nbsp; &nbsp; System.out.println();<BR>
849 * &nbsp; &nbsp; &nbsp; //<BR>
850 * <font color="#FF0000" style="font-family: georgia">
851 * aSampler - Dubois & Prade — 1000000 particles<BR>
852 * Conflict Z = 0.0 %<BR>
853 * bbaTreeA:<BR>
854 * x0000000000000001 -> 0.200409<BR>
855 * x0000000000000002 -> 0.179814<BR>
856 * x0000000000000003 -> 0.139608<BR>
857 * x0000000000000004 -> 0.130784<BR>
858 * x0000000000000005 -> 0.111702<BR>
859 * x0000000000000006 -> 0.090511<BR>
860 * x0000000000000007 -> 0.147172
861 * </font><BR>
862 *
863 * <font color="#0000FF" style="font-family: georgia">
864 * Initialize the fuser of <i>aSampler</i> with bba enties <i>aFuser1</i> and
865 * <i>aFuser2</i>, and with the referee function <i>referee4</i> (PCR6);
866 * </font><BR>
867 * aSampler.setFuser(aSampler1, aSampler2, referee4);<BR>
868 * <font color="#0000FF" style="font-family: georgia">
869 * Clear the samples container <i>Samples</i>;
870 * </font><BR>
871 * Samples.clear();<BR>
872 * <font color="#0000FF" style="font-family: georgia">
873 * Build the samples (<i>NbSamples</i> times) fused by means of the fuser and
874 * store them within the container;
875 * </font><BR>
876 * { @code for (n=0;n<NbSamples;n++) Samples.add(aSampler.makeFusedSample()); }<←
      BR>
877 * <font color="#0000FF" style="font-family: georgia">
878 * Learn the bba <i>aSampler</i> from the samples <i>Samples</i> and store the
879 * percentage of conflict samples within <i>Z</i>;
880 * </font><BR>
881 * Z=aSampler.learnFrom(Samples.toArray());<BR>
882 * <font color="#0000FF" style="font-family: georgia">
883 * Print the conflict and the state of <i>aSampler</i> (these results are ←
      random).
884 * With option <i>printMode=1</i>, the print is done according to the ←
      proposition
885 * order;
886 * </font><BR>
887 * System.out.println("aSampler - PCR6 — " + NbSamples + " particles");<BR>
888 * &nbsp; &nbsp; &nbsp; System.out.println(" Conflict Z = "+Z+" %");<BR>
889 * &nbsp; &nbsp; &nbsp; System.out.println(aSampler.state(printMode));<BR>
890 * &nbsp; &nbsp; &nbsp; System.out.println();<BR>
891 * &nbsp; &nbsp; &nbsp; //<BR>
892 * <font color="#FF0000" style="font-family: georgia">
893 * aSampler - PCR6 — 1000000 particles<BR>
894 * Conflict Z = 0.0 %<BR>
895 * bbaTreeA:<BR>
896 * x0000000000000001 -> 0.25761<BR>
897 * x0000000000000002 -> 0.238275<BR>
898 * x0000000000000003 -> 0.105398<BR>
899 * x0000000000000004 -> 0.179867<BR>
900 * x0000000000000005 -> 0.081813<BR>
901 * x0000000000000006 -> 0.056784<BR>
902 * x0000000000000007 -> 0.080253<BR>

```

```

903 * </font><BR>
904 *
905 * <font color="#0000FF" style="font-family: georgia">
906 * Initialize the fuser of <i>aSampler</i> with bba enties <i>aFuser1</i> and
907 * <i>aFuser2</i>, and with the referee function <i>referee4</i> (PCR#);
908 * </font><BR>
909 * aSampler.setFuser(aSampler1, aSampler2, referee5);<BR>
910 * <font color="#0000FF" style="font-family: georgia">
911 * Clear the samples container <i>Samples</i>;
912 * </font><BR>
913 * Samples.clear();<BR>
914 * <font color="#0000FF" style="font-family: georgia">
915 * Build the samples (<i>NbSamples</i> times) fused by means of the fuser and
916 * store them within the container;
917 * </font><BR>
918 * { @code for (n=0; n<NbSamples; n++) Samples.add(aSampler.makeFusedSample()); } <←
919 * <font color="#0000FF" style="font-family: georgia">
920 * Learn the bba <i>aSampler</i> from the samples <i>Samples</i> and store the
921 * percentage of conflict samples within <i>Z</i>;
922 * </font><BR>
923 * Z=aSampler.learnFrom(Samples.toArray());<BR>
924 * <font color="#0000FF" style="font-family: georgia">
925 * Print the conflict and the state of <i>aSampler</i> (these results are ←
926 * random).
927 * With option <i>printMode=1</i>, the print is done according to the ←
928 * proposition
929 * order;
930 * </font><BR>
931 * System.out.println("aSampler - PCR# — " + NbSamples + " particles");<BR>
932 * &nbsp; &nbsp; System.out.println("Conflict Z = "+Z+" %");<BR>
933 * &nbsp; &nbsp; System.out.println(aSampler.state(printMode));<BR>
934 * &nbsp; &nbsp; System.out.println();<BR>
935 * <font color="#FF0000" style="font-family: georgia">
936 * aSampler - PCR# — 1000000 particles <BR>
937 * Conflict Z = 0.0 %<BR>
938 * bbaTreeA:<BR>
939 * x000000000000000001 -> 0.257286 <BR>
940 * x000000000000000002 -> 0.239343 <BR>
941 * x000000000000000003 -> 0.105115 <BR>
942 * x000000000000000004 -> 0.179943 <BR>
943 * x000000000000000005 -> 0.08186 <BR>
944 * x000000000000000006 -> 0.056558 <BR>
945 * x000000000000000007 -> 0.079895
946 * </font><BR>
947 *
948 * </code>
949 */
950 public void RefereeSampler_Comparison () {
951     final Powerset A=new final Powerset ();
952     A.size(3); A.atomic(0);
953     final Powerset B=A.instanceNsize(); B.atomic(1);
954     final Powerset C=A.instanceNsize(); C.atomic(2);
955     //
956     final Powerset AUB=A.instanceNsize(); AUB.or(A,B);
957     final Powerset BUC=A.instanceNsize(); BUC.or(B,C);
958     final Powerset CUA=A.instanceNsize(); CUA.or(C,A);
959     //
960     final Powerset zero=A.instanceNsize(); zero.zero();
961     final Powerset one=A.instanceNsize(); one.one();
962     //
963     RFDempster_Powerset referee1 = new RFDempster_Powerset ();
964     RFDisjunctive_Powerset referee2 = new RFDisjunctive_Powerset ();
965     RFDuboisPrade_Powerset referee3 = new RFDuboisPrade_Powerset ();
966     RFPCR6_Powerset referee4 = new RFPCR6_Powerset ();
967     RFPCRSharp_Powerset referee5 = new RFPCRSharp_Powerset ();
968     //
969     //
970     final RefereeSampler_Powerset aSampler1 = new final RefereeSampler_Powerset ←
971     ();
972     aSampler1.add(A,0.09);
973     aSampler1.add(B,0.2);

```

```

973     aSampler1.add(C,0.02);
974     aSampler1.add(AUB,0.05);
975     aSampler1.add(BUC,0.03);
976     aSampler1.add(CUA,0.1);
977     aSampler1.add(A,0.11);
978     aSampler1.add(one,0.4);
979     //
980     finalRefereeSampler_Powerset aSampler2 = aSampler1.instance();
981     aSampler2.add(A,0.1);
982     aSampler2.add(B,0.1);
983     aSampler2.add(C,0.2);
984     aSampler2.add(AUB,0.2);
985     aSampler2.add(BUC,0.1);
986     aSampler2.add(CUA,0.1);
987     aSampler2.add(one,0.2);
988     //
989     finalRefereeSampler_Powerset aSampler = aSampler1.instance();
990 //
991
992     int printMode=1;
993
994     System.out.println(
995         "////////////////////////////////////////\n" +
996         "/// Sampling Method\n" +
997         "////////////////////////////////////////\n");
998
999     int n;
1000     int NbSamples=1000000;
1001     double Z;
1002     finalRefereeSampler_Powerset Samples= aSampler1.instance();
1003
1004     System.out.println("aSampler1");
1005     System.out.println(aSampler1.state(printMode));
1006     System.out.println();
1007     System.out.println("aSampler2");
1008     System.out.println(aSampler2.state(printMode));
1009     System.out.println();
1010     //
1011     aSampler.setFuser(aSampler1, aSampler2, referee1);
1012     Samples.clear();
1013     for(n=0;n<NbSamples;n++) Samples.add(aSampler.makeFusedSample());
1014     Z=aSampler.learnFrom(Samples.toArray());
1015     System.out.println("aSampler - Dempster — " + NbSamples + " particles");
1016     System.out.println("Conflict Z = "+Z+" %");
1017     System.out.println(aSampler.state(printMode));
1018     System.out.println();
1019     //
1020     aSampler.setFuser(aSampler1, aSampler2, referee2);
1021     Samples.clear();
1022     for(n=0;n<NbSamples;n++) Samples.add(aSampler.makeFusedSample());
1023     Z=aSampler.learnFrom(Samples.toArray());
1024     System.out.println("aSampler - Disjunctive — " + NbSamples + " particles"←
1025     );
1026     System.out.println("Conflict Z = "+Z+" %");
1027     System.out.println(aSampler.state(printMode));
1028     System.out.println();
1029     //
1030     aSampler.setFuser(aSampler1, aSampler2, referee3);
1031     Samples.clear();
1032     for(n=0;n<NbSamples;n++) Samples.add(aSampler.makeFusedSample());
1033     Z=aSampler.learnFrom(Samples.toArray());
1034     System.out.println("aSampler - Dubois & Prade — " + NbSamples + " ←
1035     particles");
1036     System.out.println("Conflict Z = "+Z+" %");
1037     System.out.println(aSampler.state(printMode));
1038     System.out.println();
1039     //
1040     aSampler.setFuser(aSampler1, aSampler2, referee4);
1041     Samples.clear();
1042     for(n=0;n<NbSamples;n++) Samples.add(aSampler.makeFusedSample());
1043     Z=aSampler.learnFrom(Samples.toArray());
1044     System.out.println("aSampler - PCR6 — " + NbSamples + " particles");
1045     System.out.println("Conflict Z = "+Z+" %");
1046     System.out.println(aSampler.state(printMode));

```

```

1045         System.out.println();
1046         //
1047         aSampler.setFuser(aSampler1, aSampler2, referee5);
1048         Samples.clear();
1049         for(n=0;n<NbSamples;n++) Samples.add(aSampler.makeFusedSample());
1050         Z=aSampler.learnFrom(Samples.toArray());
1051         System.out.println("aSampler - PCR# -- " + NbSamples + " particles");
1052         System.out.println("Conflict Z = "+Z+" %");
1053         System.out.println(aSampler.state(printMode));
1054         System.out.println();
1055     }
1056 }
1057
1058 /**
1059  * Compare different referee functions applied with RefereeFuser/↔
1060  * RefereeSampler and Powerset.
1061  */
1062 public void Referee_Comparison() {
1063     RefereeFuserRTS_Comparison();
1064     RefereeSampler_Comparison();
1065 }
1066
1067 /**
1068  * Test some logical manipulations ({@link Freeboolean}, {@link Superpowerset↔
1069  * },
1070  * {@link Openhyperpowerset}, {@link Closedhyperpowerset}, {@link Powerset}).
1071  */
1072 public void logical_tests() {
1073     int theSizeOfFrame = 4;
1074     int theSizeOfFramePowerset = 8;
1075
1076     logical_tests_Freeboolean(theSizeOfFrame);
1077     System.out.println("\n-----\n" +
1078         "-----\n");
1079     logical_tests_Superpowerset(theSizeOfFrame);
1080     System.out.println("\n-----\n" +
1081         "-----\n");
1082     logical_tests_Openhyperpowerset(theSizeOfFrame);
1083     System.out.println("\n-----\n" +
1084         "-----\n");
1085     logical_tests_Closedhyperpowerset(theSizeOfFrame);
1086     System.out.println("\n-----\n" +
1087         "-----\n");
1088     logical_tests_Powerset(theSizeOfFramePowerset);
1089 }
1090
1091 /**
1092  * Test some logical manipulations on Freeboolean.
1093  *
1094  * <BR><BR>
1095  * <b>Detailed code description.</b><BR>
1096  * The following typonomic conventions are used:<BR>
1097  * <code>
1098  * <font color="#0000FF" style="font-family: georgia">
1099  * Blue color is used for commenting the following code.
1100  * </font><BR>
1101  * code formatting is used for printing the code.<BR>
1102  * <font color="#FF0000" style="font-family: georgia">
1103  * Red color is used for printing the possible output resulting of the
1104  * previous code.
1105  * </font>
1106  * </code><BR><BR>
1107  * For the output, it is assumed that <i>theSizeOfFrame=4</i> (parameter of ↔
1108  * the method).
1109  * <BR><BR>
1110  * Commented code:
1111  * <BR><BR>
1112  * <code>
1113  * int i;<BR>
1114  * <font color="#0000FF" style="font-family: georgia">
1115  * Declaration of a free Boolean algebra, <i>fFb</i>;

```

[illegible]

```

1185 * complement(atomF[0]) = x00000000000005555<BR>
1186 * complement(atomF[1]) = x00000000000003333<BR>
1187 * complement(atomF[2]) = x0000000000000f0f<BR>
1188 * complement(atomF[3]) = x0000000000000ff<BR>
1189 * <BR>
1190 * -----<BR>
1191 * </font>
1192 * <font color="#0000FF" style="font-family: georgia">
1193 * Print the cocomplement of <i>zero</i>, of <i>one</i> and the table of
1194 * cocomplements of the atomic propositions. The cocomplements
1195 * are computed by means of code { @code fFb.cocomplement(atomF[i]); } and
1196 * stored within <i>fFb</i>;
1197 * </font><BR>
1198 * fFb.zero().cocomplement();<BR>
1199 * System.out.println("cocomplement(zero) = "+fFb.state());<BR>
1200 * fFb.one().cocomplement();<BR>
1201 * System.out.println("cocomplement(one) = "+fFb.state());<BR>
1202 * { @code for(i=0;i<theSizeOfFrame;i++) } {<BR>
1203 * &nbsp; &nbsp; &nbsp; fFb.cocomplement(atomF[i]);<BR>
1204 * &nbsp; &nbsp; &nbsp; System.out.println("cocomplement(atomF["+i+"] = " +fFb.state←
1205 * )<BR>
1206 * }<BR>
1207 * System.out.println("\n-----\n");<BR>
1208 * <font color="#FF0000" style="font-family: georgia">
1209 * cocomplement(zero) = x000000000000ffff<BR>
1210 * cocomplement(one) = x0000000000000000<BR>
1211 * cocomplement(atomF[0]) = x0000000000005555<BR>
1212 * cocomplement(atomF[1]) = x0000000000003333<BR>
1213 * cocomplement(atomF[2]) = x000000000000f0f<BR>
1214 * cocomplement(atomF[3]) = x000000000000ff<BR>
1215 * <BR>
1216 * -----<BR>
1217 * </font>
1218 * <font color="#0000FF" style="font-family: georgia">
1219 * The following codes (21 lines) tests the property <i>(A OR B) AND (B OR C) ↔
1220 * = B OR (A AND C)</i>,
1221 * and print the results of the test.
1222 * Propositions <i>A, B, C</i> are defined respectively as the <i>(←
1223 * theSizeOfFrame/4)</i>-th,
1224 * <i>(theSizeOfFrame/2)</i>-th, <i>(3*theSizeOfFrame/4)</i>-th atomics ←
1225 * propositions.
1226 * </font><BR>
1227 * System.out.println("\n\n///// Test: (A OR B) AND (B OR C) = B OR (A AND C ←
1228 * )");<BR>
1229 * <font color="#FF0000" style="font-family: georgia">
1230 * ///// Test: (A OR B) AND (B OR C) = B OR (A AND C)<BR>
1231 * </font>
1232 * finalFreeboolean A = atomF[theSizeOfFrame/4].clone();
1233 * <font color="#0000FF" style="font-family: georgia">
1234 * // Method { @link Lattice#clone() } create an exact copy of the proposition←
1235 * </font><BR>
1236 * finalFreeboolean B = atomF[theSizeOfFrame/2].clone();<BR>
1237 * finalFreeboolean C = atomF[(3*theSizeOfFrame)/4].clone();<BR>
1238 * finalFreeboolean AUB = fFb.instanceNsize();<BR>
1239 * finalFreeboolean BUC = fFb.instanceNsize();<BR>
1240 * finalFreeboolean ANC = fFb.instanceNsize();<BR>
1241 * finalFreeboolean left = fFb.instanceNsize();<BR>
1242 * finalFreeboolean right = fFb.instanceNsize();<BR>
1243 * <font color="#0000FF" style="font-family: georgia">
1244 * Compute <i>A OR B</i> and store it within <i>AUB</i>;<BR>
1245 * Compute <i>B OR C</i> and store it within <i>BUC</i>;<BR>
1246 * </font>
1247 * AUB.or(A, B);<BR>
1248 * BUC.or(B, C);<BR>
1249 * <font color="#0000FF" style="font-family: georgia">
1250 * Compute <i>A AND C</i> and store it within <i>ANC</i>;<BR>
1251 * Compute <i>AUB AND BUC</i> and store it within <i>left</i>;<BR>
1252 * Compute <i>B OR ANC</i> and store it within <i>right</i>;<BR>
1253 * </font>
1254 * ANC.and(A, C);<BR>
1255 * left.and(AUB,BUC);<BR>
1256 * right.or(B,ANC);<BR>
1257 * <font color="#0000FF" style="font-family: georgia">

```

```

1253 * Test if <i>left</i> and <i>right</i> are equal, and store the result within
1254 * <i>isEqual</i>;<BR>
1255 * </font>
1256 * boolean isEqual=left.compareTo(right)==0;<BR>
1257 * <font color="#0000FF" style="font-family: georgia">
1258 * Print propositions <i>A,B,C,left,right</i> and the boolean <i>isEqual</i>;<←
1259 * </font>
1260 * System.out.println("A = atomF["+theSizeOfFrame/4+"] = " + A.state());<BR>
1261 * System.out.println("B = atomF["+theSizeOfFrame/2+"] = " + B.state());<BR>
1262 * System.out.println("C = atomF["+3*theSizeOfFrame/4+"] = " + C.state());<←
1263 * </font>
1264 * System.out.println("(A OR B) AND (B OR C) = " + left.state());<BR>
1265 * System.out.println("B OR (A AND C) = " + right.state());<BR>
1266 * System.out.println("isEqual = "+isEqual);<BR>
1267 * <font color="#FF0000" style="font-family: georgia">
1268 * A = atomF[1] = x000000000000cccc<BR>
1269 * B = atomF[2] = x000000000000f0f0<BR>
1270 * C = atomF[3] = x000000000000ff00<BR>
1271 * (A OR B) AND (B OR C) = x000000000000fcf0<BR>
1272 * B OR (A AND C) = x000000000000fcf0<BR>
1273 * isEqual = true<BR>
1274 * </font>
1275 * </code>
1276 */
1277 public void logical_tests_Freeboolean(int theSizeOfFrame) {
1278
1279     int i;
1280     finalFreeboolean fFb = new finalFreeboolean();
1281     if(fFb.size(theSizeOfFrame)!=theSizeOfFrame) {
1282         System.err.println("Error :: RefereeToolbox_Tutorial.←
1283             logical_tests_Freeboolean(int)\n" +
1284             "Exceed authorized bounds!");
1285         System.exit(0);
1286     }
1287     System.out.println("\n\n///// Test: Freeboolean - size = " + ←
1288         theSizeOfFrame +
1289         "\n\n");
1290     finalFreeboolean[] atomF = new finalFreeboolean[theSizeOfFrame];
1291     for(i=0;i<theSizeOfFrame;i++) {
1292         atomF[i]=fFb.newInstance();
1293         atomF[i].atomic(i);
1294     }
1295     fFb.zero();
1296     System.out.println("zero = "+fFb.state());
1297     fFb.one();
1298     System.out.println("one = "+fFb.state());
1299     for(i=0;i<theSizeOfFrame;i++) {
1300         System.out.println("atomF["+i+"] = " +atomF[i].state());
1301     }
1302     System.out.println("\n-----\n");
1303     fFb.zero().complement();
1304     System.out.println("complement(zero) = "+fFb.state());
1305     fFb.one().complement();
1306     System.out.println("complement(one) = "+fFb.state());
1307     for(i=0;i<theSizeOfFrame;i++) {
1308         fFb.complement(atomF[i]);
1309         System.out.println("complement(atomF["+i+"] = " +fFb.state());
1310     }
1311     System.out.println("\n-----\n");
1312     fFb.zero().cocomplement();
1313     System.out.println("cocomplement(zero) = "+fFb.state());
1314     fFb.one().cocomplement();
1315     System.out.println("cocomplement(one) = "+fFb.state());
1316     for(i=0;i<theSizeOfFrame;i++) {
1317         fFb.cocomplement(atomF[i]);
1318         System.out.println("cocomplement(atomF["+i+"] = " +fFb.state());
1319     }
1320     System.out.println("\n-----\n");
1321     System.out.println("\n\n///// Test: (A OR B) AND (B OR C) = B OR (A AND C←
1322         ");
1323     finalFreeboolean A = atomF[theSizeOfFrame/4].clone();

```



```

1392         int) }; <BR>
1393 * </font>
1394 * finalSuperpowerset[] atomS = new finalSuperpowerset[theSizeOfFrame]; <BR>
1395 * {@code for(i=0;i<theSizeOfFrame;i++) } {<BR>
1396 * &nbsp; &nbsp; &nbsp; atomS[i]=fSps.instanceNsize();<BR>
1397 * &nbsp; &nbsp; &nbsp; atomS[i].atomic(i);<BR>
1398 * }<BR>
1399 * <font color="#0000FF" style="font-family: georgia">
1400 * Print <i>zero</i>, <i>one</i> and the table of atomic propositions (printed
1401 * with hexadecimal coding);
1402 * </font><BR>
1403 * fSps.zero();<BR>
1404 * System.out.println("zero = "+fSps.state());<BR>
1405 * fSps.one();<BR>
1406 * System.out.println("one = "+fSps.state());<BR>
1407 * {@code for(i=0;i<theSizeOfFrame;i++) } {<BR>
1408 * &nbsp; &nbsp; &nbsp; System.out.println("atomS["+i+"] = " +atomS[i].state());<BR>
1409 * }<BR>
1410 * System.out.println("\n-----\n");<BR>
1411 * <font color="#FF0000" style="font-family: georgia">
1412 * zero = x0000000000000000<BR>
1413 * one = x00000000000000ff<BR>
1414 * atomS[0] = x000000000000aaaa<BR>
1415 * atomS[1] = x000000000000cccc<BR>
1416 * atomS[2] = x000000000000f0f0<BR>
1417 * atomS[3] = x000000000000ff00<BR>
1418 * <BR>
1419 * -----<BR>
1420 * </font>
1421 * <font color="#0000FF" style="font-family: georgia">
1422 * Print the complement of <i>zero</i>, of <i>one</i> and the table of
1423 * complements of the atomic propositions. The complements
1424 * are computed by means of code {@code fSps.complement(atom[i]); } and
1425 * stored within <i>fSps</i>;
1426 * </font><BR>
1427 * fSps.zero().complement();<BR>
1428 * System.out.println("complement(zero) = "+fSps.state());<BR>
1429 * fSps.one().complement();<BR>
1430 * System.out.println("complement(one) = "+fSps.state());<BR>
1431 * {@code for(i=0;i<theSizeOfFrame;i++) } {<BR>
1432 * &nbsp; &nbsp; &nbsp; fSps.complement(atomS[i]);<BR>
1433 * &nbsp; &nbsp; &nbsp; System.out.println("complement(atomS["+i+"] = " +fSps.state()←
1434 * &nbsp; &nbsp; &nbsp; ());<BR>
1435 * }<BR>
1436 * System.out.println("\n-----\n");<BR>
1437 * <font color="#FF0000" style="font-family: georgia">
1438 * complement(zero) = x000000000000fffe<BR>
1439 * complement(one) = x0000000000000000<BR>
1440 * complement(atomS[0]) = x0000000000005554<BR>
1441 * complement(atomS[1]) = x0000000000003332<BR>
1442 * complement(atomS[2]) = x000000000000f0fe<BR>
1443 * complement(atomS[3]) = x00000000000000fe<BR>
1444 * <BR>
1445 * -----<BR>
1446 * </font>
1447 * <font color="#0000FF" style="font-family: georgia">
1448 * Print the cocomplement of <i>zero</i>, of <i>one</i> and the table of
1449 * cocomplements of the atomic propositions. The cocomplements
1450 * are computed by means of code {@code fSps.cocomplement(atomS[i]); } and
1451 * stored within <i>fSps</i>;
1452 * </font><BR>
1453 * fSps.zero().cocomplement();<BR>
1454 * System.out.println("cocomplement(zero) = "+fSps.state());<BR>
1455 * fSps.one().cocomplement();<BR>
1456 * System.out.println("cocomplement(one) = "+fSps.state());<BR>
1457 * {@code for(i=0;i<theSizeOfFrame;i++) } {<BR>
1458 * &nbsp; &nbsp; &nbsp; fSps.cocomplement(atomS[i]);<BR>
1459 * &nbsp; &nbsp; &nbsp; System.out.println("cocomplement(atomS["+i+"] = " +fSps.←
1460 * &nbsp; &nbsp; &nbsp; state());<BR>
1461 * }<BR>
1462 * System.out.println("\n-----\n");<BR>
1463 * <font color="#FF0000" style="font-family: georgia">
1464 * cocomplement(zero) = x000000000000fffe<BR>

```

```

1463 * cocomplement(one) = x0000000000000000<BR>
1464 * cocomplement(atomS[0]) = x0000000000005554<BR>
1465 * cocomplement(atomS[1]) = x0000000000003332<BR>
1466 * cocomplement(atomS[2]) = x000000000000f0e<BR>
1467 * cocomplement(atomS[3]) = x0000000000000fe<BR>
1468 * <BR>
1469 * -----<BR>
1470 * </font>
1471 *
1472 * <font color="#0000FF" style="font-family: georgia">
1473 * The following codes (21 lines) tests the property <i>(A OR B) AND (B OR C) ←
    = B OR (A AND C)</i>,
1474 * and print the results of the test.
1475 * Propositions <i>A, B, C</i> are defined respectively as the <i>(←
    theSizeOfFrame/4)</i>-th,
1476 * <i>(theSizeOfFrame/2)</i>-th, <i>(3*theSizeOfFrame/4)</i>-th atomics ←
    propositions.
1477 * </font><BR>
1478 * System.out.println("\n\n///// Test: (A OR B) AND (B OR C) = B OR (A AND C ←
    )");<BR>
1479 * <font color="#FF0000" style="font-family: georgia">
1480 * ///// Test: (A OR B) AND (B OR C) = B OR (A AND C)<BR>
1481 * </font>
1482 * finalSuperspowerset A = atomS[theSizeOfFrame/4].clone();
1483 * <font color="#0000FF" style="font-family: georgia">
1484 * // Method {@link Lattice#clone()} create an exact copy of the proposition←
    </font><BR>
1485 * finalSuperspowerset B = atomS[theSizeOfFrame/2].clone();<BR>
1486 * finalSuperspowerset C = atomS[(3*theSizeOfFrame)/4].clone();<BR>
1487 * finalSuperspowerset AUB = fSps.instanceNsize();<BR>
1488 * finalSuperspowerset BUC = fSps.instanceNsize();<BR>
1489 * finalSuperspowerset ANC = fSps.instanceNsize();<BR>
1490 * finalSuperspowerset left = fSps.instanceNsize();<BR>
1491 * finalSuperspowerset right = fSps.instanceNsize();<BR>
1492 * <font color="#0000FF" style="font-family: georgia">
1493 * Compute <i>A OR B</i> and store it within <i>AUB</i>;<BR>
1494 * Compute <i>B OR C</i> and store it within <i>BUC</i>;<BR>
1495 * </font>
1496 * AUB.or(A, B);<BR>
1497 * BUC.or(B, C);<BR>
1498 * <font color="#0000FF" style="font-family: georgia">
1499 * Compute <i>A AND C</i> and store it within <i>ANC</i>;<BR>
1500 * Compute <i>AUB AND BUC</i> and store it within <i>left</i>;<BR>
1501 * Compute <i>B OR ANC</i> and store it within <i>right</i>;<BR>
1502 * </font>
1503 * ANC.and(A, C);<BR>
1504 * left.and(AUB,BUC);<BR>
1505 * right.or(B,ANC);<BR>
1506 * <font color="#0000FF" style="font-family: georgia">
1507 * Test if <i>left</i> and <i>right</i> are equal, and store the result within
1508 * <i>isEqual</i>;<BR>
1509 * </font>
1510 * boolean isEqual=left.compareTo(right)==0;<BR>
1511 * <font color="#0000FF" style="font-family: georgia">
1512 * Print propositions <i>A,B,C,left,right</i> and the boolean <i>isEqual</i>;<BR>
    <BR>
1513 * </font>
1514 * System.out.println("A = atomS["+theSizeOfFrame/4+"] = " + A.state());<BR>
1515 * System.out.println("B = atomS["+theSizeOfFrame/2+"] = " + B.state());<BR>
1516 * System.out.println("C = atomS["+theSizeOfFrame/4+"] = " + C.state());<BR>
    <BR>
1517 * System.out.println("(A OR B) AND (B OR C) = " + left.state());<BR>
1518 * System.out.println("B OR (A AND C) = " + right.state());<BR>
1519 * System.out.println("isEqual = "+isEqual);<BR>
1520 * <font color="#FF0000" style="font-family: georgia">
1521 * A = atomS[1] = x000000000000cccc<BR>
1522 * B = atomS[2] = x000000000000f0f0<BR>
1523 * C = atomS[3] = x000000000000ff00<BR>
1524 * (A OR B) AND (B OR C) = x000000000000fcf0<BR>
1525 * B OR (A AND C) = x000000000000fcf0<BR>
1526 * isEqual = true<BR>
1527 * </font>
1528 *
1529 */

```

```

1530 public void logical_tests_Superpowerset(int theSizeOfFrame) {
1531
1532     int i;
1533     finalSuperpowerset fSps = new finalSuperpowerset();
1534     if(fSps.size(theSizeOfFrame)!=theSizeOfFrame) {
1535         System.err.println("Error :: RefereeToolbox_Tutorial.<-
1536             logical_tests_Superpowerset(int)\n" +
1537                 "Exceed authorized bounds!");
1538         System.exit(0);
1539     }
1540     System.out.println("\n\n///// Test: Superpowerset - size = " + <-
1541         theSizeOfFrame +
1542         "\n\n");
1543     finalSuperpowerset[] atomS = new finalSuperpowerset[theSizeOfFrame];
1544     for(i=0;i<theSizeOfFrame;i++) {
1545         atomS[i]=fSps.instanceNsize();
1546         atomS[i].atomic(i);
1547     }
1548     fSps.zero();
1549     System.out.println("zero = "+fSps.state());
1550     fSps.one();
1551     System.out.println("one = "+fSps.state());
1552     for(i=0;i<theSizeOfFrame;i++) {
1553         System.out.println("atomS["+i+"] = " +atomS[i].state());
1554     }
1555     System.out.println("\n-----\n");
1556     fSps.zero().complement();
1557     System.out.println("complement(zero) = "+fSps.state());
1558     fSps.one().complement();
1559     System.out.println("complement(one) = "+fSps.state());
1560     for(i=0;i<theSizeOfFrame;i++) {
1561         fSps.complement(atomS[i]);
1562         System.out.println("complement(atomS["+i+"] = " +fSps.state());
1563     }
1564     System.out.println("\n-----\n");
1565     fSps.zero().cocomplement();
1566     System.out.println("cocomplement(zero) = "+fSps.state());
1567     fSps.one().cocomplement();
1568     System.out.println("cocomplement(one) = "+fSps.state());
1569     for(i=0;i<theSizeOfFrame;i++) {
1570         fSps.cocomplement(atomS[i]);
1571         System.out.println("cocomplement(atomS["+i+"] = " +fSps.state());
1572     }
1573     System.out.println("\n-----\n");
1574     System.out.println("\n\n///// Test: (A OR B) AND (B OR C) = B OR (A AND C<-
1575         )");
1576     finalSuperpowerset A = atomS[theSizeOfFrame/4].clone();
1577     finalSuperpowerset B = atomS[theSizeOfFrame/2].clone();
1578     finalSuperpowerset C = atomS[(3*theSizeOfFrame)/4].clone();
1579     finalSuperpowerset AUB = fSps.instanceNsize();
1580     finalSuperpowerset BUC = fSps.instanceNsize();
1581     finalSuperpowerset ANC = fSps.instanceNsize();
1582     finalSuperpowerset left = fSps.instanceNsize();
1583     finalSuperpowerset right = fSps.instanceNsize();
1584     AUB.or(A, B);
1585     BUC.or(B, C);
1586     ANC.and(A, C);
1587     left.and(AUB, BUC);
1588     right.or(B, ANC);
1589     boolean isEqual=left.compareTo(right)==0;
1590     System.out.println("A = atomS["+theSizeOfFrame/4+"] = " + A.state());
1591     System.out.println("B = atomS["+theSizeOfFrame/2+"] = " + B.state());
1592     System.out.println("C = atomS["+theSizeOfFrame/4+"] = " + C.state());
1593     System.out.println("(A OR B) AND (B OR C) = " + left.state());
1594     System.out.println("B OR (A AND C) = " + right.state());
1595     System.out.println("isEqual = "+isEqual);
1596 }
1597
1598 /**
1599  * Test some logical manipulations on Openhyperpowerset.
1600  */

```

[illegible]

```

1669 * atom[1] = x000000000000cccc<BR>
1670 * atom[2] = x000000000000f0f0<BR>
1671 * atom[3] = x000000000000ff00<BR>
1672 * <BR>
1673 * -----<BR>
1674 * </font>
1675 * <font color="#0000FF" style="font-family: georgia">
1676 * Print the complement of <i>zero</i>, of <i>one</i> and the table of
1677 * complements of the atomic propositions. The complements
1678 * are computed by means of code {@code fOhps.complement(atom[i]); } and
1679 * stored within <i>fOhps</i>;
1680 * </font><BR>
1681 * fOhps.zero().complement();<BR>
1682 * System.out.println("complement(zero) = "+fOhps.state());<BR>
1683 * fOhps.one().complement();<BR>
1684 * System.out.println("complement(one) = "+fOhps.state());<BR>
1685 * {@code for(i=0;i<theSizeOfFrame;i++) } {<BR>
1686 * &nbsp; &nbsp; fOhps.complement(atom[i]);<BR>
1687 * &nbsp; &nbsp; System.out.println("complement(atom["+i+"] = " +fOhps.state←
1688 * ();<BR>
1689 * }<BR>
1690 *
1691 * System.out.println("\n-----\n");<BR>
1692 * <font color="#FF0000" style="font-family: georgia">
1693 * complement(zero) = x000000000000ffff<BR>
1694 * complement(one) = x0000000000000000<BR>
1695 * complement(atom[0]) = x0000000000000000<BR>
1696 * complement(atom[1]) = x0000000000000000<BR>
1697 * complement(atom[2]) = x0000000000000000<BR>
1698 * complement(atom[3]) = x0000000000000000<BR>
1699 * <BR>
1700 * -----<BR>
1701 * </font>
1702 * <font color="#0000FF" style="font-family: georgia">
1703 * Print the cocomplement of <i>zero</i>, of <i>one</i> and the table of
1704 * cocomplements of the atomic propositions. The cocomplements
1705 * are computed by means of code {@code fOhps.cocomplement(atom[i]); } and
1706 * stored within <i>fOhps</i>;
1707 * </font><BR>
1708 * fOhps.zero().cocomplement();<BR>
1709 * System.out.println("cocomplement(zero) = "+fOhps.state());<BR>
1710 * fOhps.one().cocomplement();<BR>
1711 * System.out.println("cocomplement(one) = "+fOhps.state());<BR>
1712 * {@code for(i=0;i<theSizeOfFrame;i++) } {<BR>
1713 * &nbsp; &nbsp; fOhps.cocomplement(atom[i]);<BR>
1714 * &nbsp; &nbsp; System.out.println("cocomplement(atom["+i+"] = " +fOhps.←
1715 * state());<BR>
1716 * }<BR>
1717 *
1718 * System.out.println("\n-----\n");<BR>
1719 * <font color="#FF0000" style="font-family: georgia">
1720 * cocomplement(zero) = x000000000000ffff<BR>
1721 * cocomplement(one) = x0000000000000000<BR>
1722 * cocomplement(atom[0]) = x000000000000ffff<BR>
1723 * cocomplement(atom[1]) = x000000000000ffff<BR>
1724 * cocomplement(atom[2]) = x000000000000ffff<BR>
1725 * cocomplement(atom[3]) = x000000000000ffff<BR>
1726 * <BR>
1727 * -----<BR>
1728 * </font>
1729 *
1730 * <font color="#0000FF" style="font-family: georgia">
1731 * The following codes (21 lines) tests the property <i>(A OR B) AND (B OR C) ←
1732 * = B OR (A AND C)</i>,
1733 * and print the results of the test.
1734 * Propositions <i>A, B, C</i> are defined respectively as the <i>(←
1735 * theSizeOfFrame/4)</i>-th,
1736 * <i>(theSizeOfFrame/2)</i>-th, <i>(3*theSizeOfFrame/4)</i>-th atomics ←
1737 * propositions.
1738 * </font><BR>
1739 * System.out.println("\n\n///// Test: (A OR B) AND (B OR C) = B OR (A AND C ←
1740 * )");<BR>
1741 * <font color="#FF0000" style="font-family: georgia">
1742 * ///// Test: (A OR B) AND (B OR C) = B OR (A AND C)<BR>
1743 * </font>

```

```

1737 * finalOpenhyperpowerset A = atom[theSizeOfFrame/4].clone();
1738 * <font color="#0000FF" style="font-family: georgia">
1739 * // Method {@link Lattice#clone()} create an exact copy of the proposition↵
1740 * </font><BR>
1741 * finalOpenhyperpowerset B = atom[theSizeOfFrame/2].clone();<BR>
1742 * finalOpenhyperpowerset C = atom[(3*theSizeOfFrame)/4].clone();<BR>
1743 * finalOpenhyperpowerset AUB = fOhps.instanceNsize();<BR>
1744 * finalOpenhyperpowerset BUC = fOhps.instanceNsize();<BR>
1745 * finalOpenhyperpowerset ANC = fOhps.instanceNsize();<BR>
1746 * finalOpenhyperpowerset left = fOhps.instanceNsize();<BR>
1747 * finalOpenhyperpowerset right = fOhps.instanceNsize();<BR>
1748 * <font color="#0000FF" style="font-family: georgia">
1749 * Compute <i>A OR B</i> and store it within <i>AUB</i>;<BR>
1750 * Compute <i>B OR C</i> and store it within <i>BUC</i>;<BR>
1751 * </font>
1752 * AUB.or(A, B);<BR>
1753 * BUC.or(B, C);<BR>
1754 * <font color="#0000FF" style="font-family: georgia">
1755 * Compute <i>A AND C</i> and store it within <i>ANC</i>;<BR>
1756 * Compute <i>AUB AND BUC</i> and store it within <i>left</i>;<BR>
1757 * Compute <i>B OR ANC</i> and store it within <i>right</i>;<BR>
1758 * </font>
1759 * ANC.and(A, C);<BR>
1760 * left.and(AUB,BUC);<BR>
1761 * right.or(B,ANC);<BR>
1762 * <font color="#0000FF" style="font-family: georgia">
1763 * Test if <i>left</i> and <i>right</i> are equal, and store the result within
1764 * <i>isEqual</i>;<BR>
1765 * </font>
1766 * boolean isEqual=left.compareTo(right)==0;<BR>
1767 * <font color="#0000FF" style="font-family: georgia">
1768 * Print propositions <i>A,B,C,left,right</i> and the boolean <i>isEqual</i>;<BR>
1769 * </font>
1770 * System.out.println("A = atom["+theSizeOfFrame/4+"] = " + A.state());<BR>
1771 * System.out.println("B = atom["+theSizeOfFrame/2+"] = " + B.state());<BR>
1772 * System.out.println("C = atom["+theSizeOfFrame/4+"] = " + C.state());<BR>
1773 * System.out.println("(A OR B) AND (B OR C) = " + left.state());<BR>
1774 * System.out.println("B OR (A AND C) = " + right.state());<BR>
1775 * System.out.println("isEqual = "+isEqual);<BR>
1776 * <font color="#FF0000" style="font-family: georgia">
1777 * A = atom[1] = x000000000000cccc<BR>
1778 * B = atom[2] = x000000000000f0f0<BR>
1779 * C = atom[3] = x000000000000ff00<BR>
1780 * (A OR B) AND (B OR C) = x000000000000fcf0<BR>
1781 * B OR (A AND C) = x000000000000fcf0<BR>
1782 * isEqual = true<BR>
1783 * </font>
1784 * </code>
1785 */
1786 public void logical_tests_Openhyperpowerset(int theSizeOfFrame) {
1787
1788     int i;
1789     finalOpenhyperpowerset f0hps = new finalOpenhyperpowerset();
1790     if(f0hps.size(theSizeOfFrame)!=theSizeOfFrame) {
1791         System.err.println("Error :: RefereeToolbox_Tutorial.↵
1792             logical_tests_Openhyperpowerset(int)\n" +
1793             "Exceed authorized bounds!");
1794         System.exit(0);
1795     }
1796     System.out.println("\n\n///// Test: Openhyperpowerset - size = " + ↵
1797         theSizeOfFrame +
1798         "\n\n");
1799     finalOpenhyperpowerset[] atom = new finalOpenhyperpowerset[theSizeOfFrame↵
1800     ];
1801     for(i=0;i<theSizeOfFrame;i++) {
1802         atom[i]=f0hps.instanceNsize();
1803         atom[i].atomic(i);
1804     }
1805     f0hps.zero();
1806     System.out.println("zero = "+f0hps.state());
1807     f0hps.one();

```

```

1805     System.out.println("one = "+f0hps.state());
1806     for(i=0;i<theSizeOfFrame;i++) {
1807         System.out.println("atom["+i+"] = " +atom[i].state());
1808     }
1809     System.out.println("\n-----\n");
1810     f0hps.zero().complement();
1811     System.out.println("complement(zero) = "+f0hps.state());
1812     f0hps.one().complement();
1813     System.out.println("complement(one) = "+f0hps.state());
1814     for(i=0;i<theSizeOfFrame;i++) {
1815         f0hps.complement(atom[i]);
1816         System.out.println("complement(atom["+i+"]) = " +f0hps.state());
1817     }
1818     System.out.println("\n-----\n");
1819     f0hps.zero().cocomplement();
1820     System.out.println("cocomplement(zero) = "+f0hps.state());
1821     f0hps.one().cocomplement();
1822     System.out.println("cocomplement(one) = "+f0hps.state());
1823     for(i=0;i<theSizeOfFrame;i++) {
1824         f0hps.cocomplement(atom[i]);
1825         System.out.println("cocomplement(atom["+i+"]) = " +f0hps.state());
1826     }
1827     System.out.println("\n-----\n");
1828
1829     System.out.println("\n\n///// Test: (A OR B) AND (B OR C) = B OR (A AND C←
        )");
1830
1831     finalOpenhyperpowerset A = atom[theSizeOfFrame/4].clone();
1832     finalOpenhyperpowerset B = atom[theSizeOfFrame/2].clone();
1833     finalOpenhyperpowerset C = atom[(3*theSizeOfFrame)/4].clone();
1834     finalOpenhyperpowerset AUB = f0hps.instanceNsize();
1835     finalOpenhyperpowerset BUC = f0hps.instanceNsize();
1836     finalOpenhyperpowerset ANC = f0hps.instanceNsize();
1837     finalOpenhyperpowerset left = f0hps.instanceNsize();
1838     finalOpenhyperpowerset right = f0hps.instanceNsize();
1839     AUB.or(A, B);
1840     BUC.or(B, C);
1841     ANC.and(A, C);
1842     left.and(AUB, BUC);
1843     right.or(B, ANC);
1844     boolean isEqual=left.compareTo(right)==0;
1845     System.out.println("A = atom["+theSizeOfFrame/4+"] = " + A.state());
1846     System.out.println("B = atom["+theSizeOfFrame/2+"] = " + B.state());
1847     System.out.println("C = atom["+theSizeOfFrame/4+"] = " + C.state());
1848     System.out.println("(A OR B) AND (B OR C) = " + left.state());
1849     System.out.println("B OR (A AND C) = " + right.state());
1850     System.out.println("isEqual = "+isEqual);
1851 }
1852
1853 /**
1854  * Test some logical manipulations on Closedhyperpowerset.
1855  *
1856  * <BR><BR>
1857  * <b>Detailed code description.</b><BR>
1858  * The following typonomic conventions are used:<BR>
1859  * <code>
1860  * <font color="#0000FF" style="font-family: georgia">
1861  * Blue color is used for commenting the following code.
1862  * </font><BR>
1863  * code formatting is used for printing the code.<BR>
1864  * <font color="#FF0000" style="font-family: georgia">
1865  * Red color is used for printing the possible output resulting of the
1866  * previous code.
1867  * </font>
1868  * </code><BR><BR>
1869  * For the output, it is assumed that <i>theSizeOfFrame=4</i> (parameter of ←
        the method).
1870  * <BR><BR>
1871  * Commented code:
1872  * <BR><BR>
1873  * <code>
1874  * int i;<BR>
1875  * <font color="#0000FF" style="font-family: georgia">
1876  * Declaration of a closed hyperpowerset, <i>fChps</i>;

```

```

1877 * </font><BR>
1878 * finalClosedhyperpowerset fChps = new finalClosedhyperpowerset();<BR>
1879 * <font color="#0000FF" style="font-family: georgia">
1880 * Resize <i>fChps</i> to <i>theSizeOfFrame</i>, the parameter of the method.
1881 * If the resizing failed , produce an error message and exit ;
1882 * </font><BR>
1883 * if (fChps.size(theSizeOfFrame)!=theSizeOfFrame) {<BR>
1884 * &nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&~System.err.println("Error :: RefereeToolbox_Tutorial.<br>
logical_tests_Closedhyperpowerset(int)" +<br>
&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&~"Exceed authorized bounds!");<br>
&nbsp;&nbsp;&nbsp;&nbsp;&~System.exit(0);<br>
}<br>
<font color="#0000FF" style="font-family: georgia">
Print the title of the method;
</font><BR>
1891 * System.out.println("\n\n///// Test: Closedhyperpowerset - size = " + <br>
theSizeOfFrame +<br>
&nbsp;&nbsp;&~" //\n\n");<br>
<font color="#FF0000" style="font-family: georgia">
1894 * ///// Test: Closedhyperpowerset - size = 4 &nbsp;&nbsp;&~//<br>
1895 * </font>
1896 * <font color="#0000FF" style="font-family: georgia">
1897 * Create the table of atomic propositions , <i>atomC</i>; <br>
1898 * Create each atomic proposition by instancing and resizing from <i>fChps</i><br>
> , using
1899 * {@code fChps.instanceNsize()}; <br>
1900 * Define each atomic by applying the method {@link GeneratedLattice#atomic(<br>
int ) }; <br>
1901 * </font>
1902 * finalClosedhyperpowerset[] atomC = new finalClosedhyperpowerset[<br>
theSizeOfFrame];<br>
1903 * {@code for(i=0;i<theSizeOfFrame;i++) } <br>
1904 * &nbsp;&nbsp;&~atomC[i]=fChps.instanceNsize();<br>
1905 * &nbsp;&nbsp;&~atomC[i].atomic(i);<br>
1906 * }<br>
1907 * <font color="#0000FF" style="font-family: georgia">
1908 * Print <i>zero</i>, <i>one</i> and the table of atomic propositions (printed
1909 * with hexadecimal coding);
1910 * </font><BR>
1911 * fChps.zero();<br>
1912 * System.out.println("zero = "+fChps.state());<br>
1913 * fChps.one();<br>
1914 * System.out.println("one = "+fChps.state());<br>
1915 * {@code for(i=0;i<theSizeOfFrame;i++) } <br>
1916 * &nbsp;&~System.out.println("atomC["+i+"] = " +atomC[i].state());<br>
1917 * }<br>
1918 * System.out.println("<n-----<n")<br>
1919 * <font color="#FF0000" style="font-family: georgia">
1920 * zero = x0000000000000000 <br>
1921 * one = x000000000000fffe <br>
1922 * atomC[0] = x0000000000aaaa <br>
1923 * atomC[1] = x0000000000cccc <br>
1924 * atomC[2] = x0000000000f0f0 <br>
1925 * atomC[3] = x0000000000ff00 <br>
1926 * <br>
1927 * -----<br>
1928 * </font>
1929 * 
1930 * <font color="#0000FF" style="font-family: georgia">
1931 * Print the complement of <i>zero</i>, of <i>one</i> and the table of <br>
complements
of the atomic propositions. The complements are computed by means of code
{@code fChps.complement(atomC[i]); } and stored within <i>fChps</i>;
1934 * </font><BR>
1935 * fChps.zero().complement();<br>
1936 * System.out.println("complement(zero) = "+fChps.state());<br>
1937 * fChps.one().complement();<br>
1938 * System.out.println("complement(one) = "+fChps.state());<br>
1939 * {@code for(i=0;i<theSizeOfFrame;i++) } <br>
1940 * &nbsp;&~fChps.complement(atomC[i]);<br>
1941 * &nbsp;&~System.out.println("complement(atomC["+i+"]) = " +fChps.state<br>
());<br>
} <br>
1943 * System.out.println("<n-----<n")<br>

```

```

1944 * <font color="#FF0000" style="font-family: georgia">
1945 * complement(zero) = x000000000000fffe<BR>
1946 * complement(one) = x0000000000000000<BR>
1947 * complement(atomC[0]) = x0000000000000000<BR>
1948 * complement(atomC[1]) = x0000000000000000<BR>
1949 * complement(atomC[2]) = x0000000000000000<BR>
1950 * complement(atomC[3]) = x0000000000000000<BR>
1951 * <BR>
1952 * -----<BR>
1953 * </font>
1954 *
1955 * <font color="#0000FF" style="font-family: georgia">
1956 * Print the cocomplement of <i>zero</i>, of <i>one</i> and the table of ←
    cocomplements
1957 * of the atomic propositions. The cocomplements
1958 * are computed by means of code {@code fChps.cocomplement(atomC[i]); } and
1959 * stored within <i>fChps</i>;
1960 * </font><BR>
1961 * fChps.zero().cocomplement();<BR>
1962 * System.out.println("cocomplement(zero) = "+fChps.state());<BR>
1963 * fChps.one().cocomplement();<BR>
1964 * System.out.println("cocomplement(one) = "+fChps.state());<BR>
1965 * {@code for (i=0;i<theSizeOfFrame;i++) } {<BR>
1966 * &nbsp; &nbsp; fChps.cocomplement(atomC[i]);<BR>
1967 * &nbsp; &nbsp; System.out.println("cocomplement(atomC["+i+"] = " +fChps.←
    state());<BR>
1968 * }<BR>
1969 * System.out.println("\n-----\n");<BR>
1970 * <font color="#FF0000" style="font-family: georgia">
1971 * cocomplement(zero) = x000000000000fffe<BR>
1972 * cocomplement(one) = x0000000000000000<BR>
1973 * cocomplement(atomC[0]) = x000000000000fffc<BR>
1974 * cocomplement(atomC[1]) = x000000000000fffa<BR>
1975 * cocomplement(atomC[2]) = x000000000000ffee<BR>
1976 * cocomplement(atomC[3]) = x000000000000fefe<BR>
1977 * <BR>
1978 * -----<BR>
1979 * </font>
1980 *
1981 * <font color="#0000FF" style="font-family: georgia">
1982 * The following codes (21 lines) tests the property <i>(A OR B) AND (B OR C) ←
    = B OR (A AND C)</i>,
1983 * and print the results of the test.
1984 * Propositions <i>A, B, C</i> are defined respectively as the <i>(←
    theSizeOfFrame/4)</i>-th,
1985 * <i>(theSizeOfFrame/2)</i>-th, <i>(3*theSizeOfFrame/4)</i>-th atomics ←
    propositions.
1986 * </font><BR>
1987 * System.out.println("\n\n///// Test: (A OR B) AND (B OR C) = B OR (A AND C ←
    )");<BR>
1988 * <font color="#FF0000" style="font-family: georgia">
1989 * ///// Test: (A OR B) AND (B OR C) = B OR (A AND C)<BR>
1990 * </font>
1991 * finalClosedhyperpowerset A = atomC[theSizeOfFrame/4].clone();
1992 * <font color="#0000FF" style="font-family: georgia">
1993 * // Method {@link Lattice#clone()} create an exact copy of the proposition←
    </font><BR>
1994 * finalClosedhyperpowerset B = atomC[theSizeOfFrame/2].clone();<BR>
1995 * finalClosedhyperpowerset C = atomC[(3*theSizeOfFrame)/4].clone();<BR>
1996 * finalClosedhyperpowerset AUB = fChps.instanceNsize();<BR>
1997 * finalClosedhyperpowerset BUC = fChps.instanceNsize();<BR>
1998 * finalClosedhyperpowerset ANC = fChps.instanceNsize();<BR>
1999 * finalClosedhyperpowerset left = fChps.instanceNsize();<BR>
2000 * finalClosedhyperpowerset right = fChps.instanceNsize();<BR>
2001 * <font color="#0000FF" style="font-family: georgia">
2002 * Compute <i>A OR B</i> and store it within <i>AUB</i>;<BR>
2003 * Compute <i>B OR C</i> and store it within <i>BUC</i>;<BR>
2004 * </font>
2005 * AUB.or(A, B);<BR>
2006 * BUC.or(B, C);<BR>
2007 * <font color="#0000FF" style="font-family: georgia">
2008 * Compute <i>A AND C</i> and store it within <i>ANC</i>;<BR>
2009 * Compute <i>AUB AND BUC</i> and store it within <i>left</i>;<BR>
2010 * Compute <i>B OR ANC</i> and store it within <i>right</i>;<BR>

```

```

2011 * </font>
2012 * ANC.and(A, C);<BR>
2013 * left.and(AUB,BUC);<BR>
2014 * right.or(B,ANC);<BR>
2015 * <font color="#0000FF" style="font-family: georgia">
2016 * Test if <i>left</i> and <i>right</i> are equal, and store the result within
2017 * <i>isEqual</i>;<BR>
2018 * </font>
2019 * boolean isEqual=left.compareTo(right)==0;<BR>
2020 * <font color="#0000FF" style="font-family: georgia">
2021 * Print propositions <i>A,B,C,left,right</i> and the boolean <i>isEqual</i>;<BR>
2022 * </font>
2023 * System.out.println("A = atomC["+theSizeOfFrame/4+"] = " + A.state());<BR>
2024 * System.out.println("B = atomC["+theSizeOfFrame/2+"] = " + B.state());<BR>
2025 * System.out.println("C = atomC["+ (3*theSizeOfFrame)/4+"] = " + C.state());<BR>
2026 * System.out.println("(A OR B) AND (B OR C) = " + left.state());<BR>
2027 * System.out.println("B OR (A AND C) = " + right.state());<BR>
2028 * System.out.println("isEqual = "+isEqual);<BR>
2029 * <font color="#FF0000" style="font-family: georgia">
2030 * A = atomC[1] = x000000000000cccc<BR>
2031 * B = atomC[2] = x000000000000f0f0<BR>
2032 * C = atomC[3] = x000000000000ff00<BR>
2033 * (A OR B) AND (B OR C) = x000000000000fcf0<BR>
2034 * B OR (A AND C) = x000000000000fcf0<BR>
2035 * isEqual = true<BR>
2036 * </font>
2037 * </code>
2038 *
2039 */
2040 public void logical_tests_Closedhyperpowerset(int theSizeOfFrame) {
2041
2042     int i;
2043     finalClosedhyperpowerset fChps = new finalClosedhyperpowerset();
2044     if(fChps.size(theSizeOfFrame)!=theSizeOfFrame) {
2045         System.err.println("Error :: RefereeToolbox_Tutorial.<BR>
2046             logical_tests_Closedhyperpowerset(int)\n" +
2047             "Exceed authorized bounds!");
2048         System.exit(0);
2049     }
2050     System.out.println("\n\n///// Test: Closedhyperpowerset - size = " + theSizeOfFrame +
2051         "\n\n");
2052     finalClosedhyperpowerset[] atomC = new finalClosedhyperpowerset[theSizeOfFrame];
2053     for(i=0;i<theSizeOfFrame;i++) {
2054         atomC[i]=fChps.instanceNsize();
2055         atomC[i].atomic(i);
2056     }
2057     fChps.zero();
2058     System.out.println("zero = "+fChps.state());
2059     fChps.one();
2060     System.out.println("one = "+fChps.state());
2061     for(i=0;i<theSizeOfFrame;i++) {
2062         System.out.println("atomC["+i+"] = " +atomC[i].state());
2063     }
2064     System.out.println("\n-----\n");
2065     fChps.zero().complement();
2066     System.out.println("complement(zero) = "+fChps.state());
2067     fChps.one().complement();
2068     System.out.println("complement(one) = "+fChps.state());
2069     for(i=0;i<theSizeOfFrame;i++) {
2070         fChps.complement(atomC[i]);
2071         System.out.println("complement(atomC["+i+"] = " +fChps.state());
2072     }
2073     System.out.println("\n-----\n");
2074     fChps.zero().cocomplement();
2075     System.out.println("cocomplement(zero) = "+fChps.state());
2076     fChps.one().cocomplement();
2077     System.out.println("cocomplement(one) = "+fChps.state());
2078     for(i=0;i<theSizeOfFrame;i++) {
2079         fChps.cocomplement(atomC[i]);
2080         System.out.println("cocomplement(atomC["+i+"] = " +fChps.state());

```

```

2080 }
2081
2082 System.out.println("\n-----\n");
2083
2084 System.out.println("\n\n///// Test: (A OR B) AND (B OR C) = B OR (A AND C ←
    )");
2085 finalClosedhyperpowerset A = atomC[theSizeOfFrame/4].clone();
2086 finalClosedhyperpowerset B = atomC[theSizeOfFrame/2].clone();
2087 finalClosedhyperpowerset C = atomC[(3*theSizeOfFrame)/4].clone();
2088 finalClosedhyperpowerset AUB = fChps.instanceNsize();
2089 finalClosedhyperpowerset BUC = fChps.instanceNsize();
2090 finalClosedhyperpowerset ANC = fChps.instanceNsize();
2091 finalClosedhyperpowerset left = fChps.instanceNsize();
2092 finalClosedhyperpowerset right = fChps.instanceNsize();
2093 AUB.or(A, B);
2094 BUC.or(B, C);
2095 ANC.and(A, C);
2096 left.and(AUB,BUC);
2097 right.or(B,ANC);
2098 boolean isEqual=left.compareTo(right)==0;
2099 System.out.println("A = atomC["+theSizeOfFrame/4+"] = " + A.state());
2100 System.out.println("B = atomC["+theSizeOfFrame/2+"] = " + B.state());
2101 System.out.println("C = atomC["+theSizeOfFrame/4*3+"] = " + C.state());
2102 System.out.println("(A OR B) AND (B OR C) = " + left.state());
2103 System.out.println("B OR (A AND C ) = " + right.state());
2104 System.out.println("isEqual = "+isEqual);
2105
2106 }
2107
2108 /**
2109 * Test some logical manipulations on Powerset.
2110 *
2111 * <BR><BR>
2112 * <b>Detailed code description.</b><BR>
2113 * The following typonomic conventions are used:<BR>
2114 * <code>
2115 * <font color="#0000FF" style="font-family: georgia">
2116 * Blue color is used for commenting the following code.
2117 * </font><BR>
2118 * code formatting is used for printing the code.<BR>
2119 * <font color="#FF0000" style="font-family: georgia">
2120 * Red color is used for printing the possible output resulting of the
2121 * previous code.
2122 * </font>
2123 * </code><BR><BR>
2124 * For the output, it is assumed that <i>theSizeOfFrame=8</i> (parameter of ←
        the method).
2125 *
2126 * <BR><BR>
2127 * Commented code:
2128 * <BR><BR>
2129 * <code>
2130 * int i;<BR>
2131 * <font color="#0000FF" style="font-family: georgia">
2132 * Declaration of a powerset , <i>fPset</i>;
2133 * </font><BR>
2134 * finalPowerset fPset = new finalPowerset();<BR>
2135 * <font color="#0000FF" style="font-family: georgia">
2136 * Resize <i>fPset</i> to <i>theSizeOfFrame</i>, the parameter of the method.
2137 * If the resizing failed, produce an error message and exit;
2138 * </font><BR>
2139 * if (fPset.size(theSizeOfFrame)!=theSizeOfFrame) {<BR>
2140 * &nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&System.err.println("Error : RefereeToolbox_Tutorial.←
        logical_tests_Closedhyperpowerset(int)\n" +<BR>
2141 * &nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&"Exceed authorized bounds!");<BR>
2142 * &nbsp;&nbsp;&nbsp;&nbsp;&System.exit(0);<BR>
2143 * }<BR>
2144 * //<BR>
2145 * <font color="#0000FF" style="font-family: georgia">
2146 * Print the title of the method;
2147 * </font><BR>
2148 * System.out.println("\n\n///// Test: Powerset - size = " + theSizeOfFrame ←
        +<BR>
2149 * &nbsp;&nbsp;&nbsp;&nbsp;& " //\n\n");<BR>
2150 * <font color="#FF0000" style="font-family: georgia">

```

```

2150 * //Test: Powerset - size = 8 &nbsp; &nbsp; &nbsp; //<BR>
2151 * </font>
2152 * <font color="#0000FF" style="font-family: georgia">
2153 * Create the table of atomic propositions, <i>atomPset</i>; <BR>
2154 * Create each atomic proposition by instanting and resizing from <i>fPset</i>
2155 * >, using
2156 * {@code fPset.instanceNsize();}<BR>
2157 * Define each atomic by applying the method {@link GeneratedLattice#atomic(
2158 * int) };<BR>
2159 * </font>
2160 * final Powerset[] atomPset = new final Powerset[theSizeOfFrame];<BR>
2161 * {@code for (i=0;i<theSizeOfFrame;i++) } {<BR>
2162 * &nbsp; &nbsp; &nbsp; atomPset[i]=fPset.instanceNsize();<BR>
2163 * &nbsp; &nbsp; &nbsp; atomPset[i].atomic(i);<BR>
2164 * }<BR>
2165 * <font color="#0000FF" style="font-family: georgia">
2166 * Print the table of atomic propositions (printed with hexadecimal coding);
2167 * </font><BR>
2168 * {@code for (i=0;i<theSizeOfFrame;i++) } {<BR>
2169 * &nbsp; &nbsp; &nbsp; System.out.println("atomPset["+i+"]" +<BR>
2170 * &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; " = " +atomPset[i].state());<BR>
2171 * }<BR>
2172 * System.out.println("\n-----\n");<BR>
2173 * <font color="#FF0000" style="font-family: georgia">
2174 * atomPset[0] = x0000000000000001<BR>
2175 * atomPset[1] = x0000000000000002<BR>
2176 * atomPset[2] = x0000000000000004<BR>
2177 * atomPset[3] = x0000000000000008<BR>
2178 * atomPset[4] = x0000000000000010<BR>
2179 * atomPset[5] = x0000000000000020<BR>
2180 * atomPset[6] = x0000000000000040<BR>
2181 * atomPset[7] = x0000000000000080<BR>
2182 * <BR>
2183 * -----<BR>
2184 * </font>
2185 * <font color="#0000FF" style="font-family: georgia">
2186 * Print the table of complements of the atomic propositions. The complements
2187 * are computed by means of code {@code fPset.complement(atomPset[i]); } and
2188 * stored within <i>fPset</i>;
2189 * </font><BR>
2190 * {@code for (i=0;i<theSizeOfFrame;i++) } {<BR>
2191 * &nbsp; &nbsp; &nbsp; fPset.complement(atomPset[i]);<BR>
2192 * &nbsp; &nbsp; &nbsp; System.out.println("complement(atomPset["+i+"]" +<BR>
2193 * &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; " = " +fPset.state());<BR>
2194 * }<BR>
2195 * System.out.println("\n-----\n");<BR>
2196 * <font color="#FF0000" style="font-family: georgia">
2197 * complement(atomPset[0]) = x00000000000000fe<BR>
2198 * complement(atomPset[1]) = x00000000000000fd<BR>
2199 * complement(atomPset[2]) = x00000000000000fb<BR>
2200 * complement(atomPset[3]) = x00000000000000f7<BR>
2201 * complement(atomPset[4]) = x00000000000000ef<BR>
2202 * complement(atomPset[5]) = x00000000000000df<BR>
2203 * complement(atomPset[6]) = x00000000000000bf<BR>
2204 * complement(atomPset[7]) = x000000000000007f<BR>
2205 * <BR>
2206 * -----<BR>
2207 * </font>
2208 * <font color="#0000FF" style="font-family: georgia">
2209 * Print the table of cocomplements of the atomic propositions. The
2210 * cocomplements
2211 * are computed by means of code {@code fPset.cocomplement(atomPset[i]); } and
2212 * stored within <i>fPset</i>;
2213 * </font><BR>
2214 * {@code for (i=0;i<theSizeOfFrame;i++) } {<BR>
2215 * &nbsp; &nbsp; &nbsp; fPset.cocomplement(atomPset[i]);<BR>
2216 * &nbsp; &nbsp; &nbsp; System.out.println("cocomplement(atomPset["+i+"]" +<BR>
2217 * &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; " = " +fPset.state());<BR>
2218 * }<BR>
2219 * System.out.println("\n-----\n");<BR>
2220 * <font color="#FF0000" style="font-family: georgia">
2221 * cocomplement(atomPset[0]) = x00000000000000fe<BR>
2222 * cocomplement(atomPset[1]) = x00000000000000fd<BR>

```

```

2221 * cocomplement(atomPset[2]) = x00000000000000fb<BR>
2222 * cocomplement(atomPset[3]) = x00000000000000f7<BR>
2223 * cocomplement(atomPset[4]) = x00000000000000ef<BR>
2224 * cocomplement(atomPset[5]) = x00000000000000df<BR>
2225 * cocomplement(atomPset[6]) = x00000000000000bf<BR>
2226 * cocomplement(atomPset[7]) = x000000000000007f<BR>
2227 * <BR>
2228 * -----<BR>
2229 * </font>
2230 *
2231 * <font color="#0000FF" style="font-family: georgia">
2232 * The following codes (21 lines) tests the property <i>(A OR B) AND (B OR C) ←
2233 * = B OR (A AND C)</i>,
2234 * and print the results of the test.
2235 * Propositions <i>A, B, C</i> are defined respectively as the <i>(←
2236 * theSizeOfFrame/4)</i>-th,
2237 * <i>(theSizeOfFrame/2)</i>-th, <i>(3*theSizeOfFrame/4)</i>-th atomics ←
2238 * propositions.
2239 * </font><BR>
2240 * System.out.println("\n\n///// Test: (A OR B) AND (B OR C) = B OR (A AND C ←
2241 * )");<BR>
2242 * <font color="#FF0000" style="font-family: georgia">
2243 * ///// Test: (A OR B) AND (B OR C) = B OR (A AND C)<BR>
2244 * </font>
2245 * finalPowerset A = atomPset[theSizeOfFrame/4].clone(); <font color="#0000FF" ←
2246 * style="font-family: georgia">
2247 * // Method {@link Lattice#clone()} create an exact copy of the proposition←
2248 * </font><BR>
2249 * finalPowerset B = atomPset[theSizeOfFrame/2].clone();<BR>
2250 * finalPowerset C = atomPset[(3*theSizeOfFrame)/4].clone();<BR>
2251 * finalPowerset AUB = fPset.instanceNsize();<BR>
2252 * finalPowerset BUC = fPset.instanceNsize();<BR>
2253 * finalPowerset ANC = fPset.instanceNsize();<BR>
2254 * finalPowerset left = fPset.instanceNsize();<BR>
2255 * finalPowerset right = fPset.instanceNsize();<BR>
2256 * <font color="#0000FF" style="font-family: georgia">
2257 * Compute <i>A OR B</i> and store it within <i>AUB</i>;<BR>
2258 * Compute <i>B OR C</i> and store it within <i>BUC</i>;<BR>
2259 * </font>
2260 * AUB.or(A, B);<BR>
2261 * BUC.or(B, C);<BR>
2262 * <font color="#0000FF" style="font-family: georgia">
2263 * Compute <i>A AND C</i> and store it within <i>ANC</i>;<BR>
2264 * Compute <i>AUB AND BUC</i> and store it within <i>left</i>;<BR>
2265 * Compute <i>B OR ANC</i> and store it within <i>right</i>;<BR>
2266 * </font>
2267 * ANC.and(A, C);<BR>
2268 * left.and(AUB,BUC);<BR>
2269 * right.or(B,ANC);<BR>
2270 * <font color="#0000FF" style="font-family: georgia">
2271 * Test if <i>left</i> and <i>right</i> are equal, and store the result within
2272 * <i>isEqual</i>;<BR>
2273 * </font>
2274 * boolean isEqual=left.compareTo(right)==0;<BR>
2275 * <font color="#0000FF" style="font-family: georgia">
2276 * Print propositions <i>A,B,C,left ,right</i> and the boolean <i>isEqual</i>;<BR>
2277 * </font>
2278 * System.out.println("A = atomPset["+theSizeOfFrame/4+"] = " + A.state());<BR>
2279 * System.out.println("B = atomPset["+theSizeOfFrame/2+"] = " + B.state());<BR>
2280 * System.out.println("C = atomPset["+3*theSizeOfFrame/4+"] = " + C.state());<BR>
2281 * System.out.println("(A OR B) AND (B OR C) = " + left.state());<BR>
2282 * System.out.println("B OR (A AND C) = " + right.state());<BR>
2283 * System.out.println("isEqual = "+isEqual);<BR>
2284 * <font color="#FF0000" style="font-family: georgia">
2285 * A = atomPset[2] = x0000000000000004<BR>
2286 * B = atomPset[4] = x0000000000000010<BR>
2287 * C = atomPset[6] = x0000000000000040<BR>
2288 * (A OR B) AND (B OR C) = x0000000000000010<BR>
2289 * B OR (A AND C) = x0000000000000010<BR>
2290 * isEqual = true<BR>

```

```

2285 * </font>
2286 *
2287 * </code>
2288 *
2289 */
2290 public void logical_tests_Powerset (int theSizeOfFrame) {
2291     int i;
2292     finalPowerset fPset = new finalPowerset();
2293     if (fPset.size(theSizeOfFrame) != theSizeOfFrame) {
2294         System.err.println("Error :: RefereeToolbox_Tutorial.<←
2295             logical_tests_Closedhyperpowerset(int)\n" +
2296                 "Exceed authorized bounds!");
2297         System.exit(0);
2298     }
2299     //
2300     System.out.println("\n\n///// Test: Powerset - size = " + theSizeOfFrame <←
2301         +
2302         " //\n\n");
2303     finalPowerset[] atomPset = new finalPowerset[theSizeOfFrame];
2304     for (i=0; i<theSizeOfFrame; i++) {
2305         atomPset[i] = fPset.instanceNsize();
2306         atomPset[i].atomic(i);
2307     }
2308     for (i=0; i<theSizeOfFrame; i++) {
2309         System.out.println("atomPset["+i+"]" +
2310             " = " + atomPset[i].state());
2311     }
2312     System.out.println("\n-----\n");
2313     for (i=0; i<theSizeOfFrame; i++) {
2314         fPset.complement(atomPset[i]);
2315         System.out.println("complement(atomPset["+i+"])" +
2316             " = " + fPset.state());
2317     }
2318     System.out.println("\n-----\n");
2319     for (i=0; i<theSizeOfFrame; i++) {
2320         fPset.cocomplement(atomPset[i]);
2321         System.out.println("cocomplement(atomPset["+i+"])" +
2322             " = " + fPset.state());
2323     }
2324     System.out.println("\n-----\n");
2325     System.out.println("\n\n///// Test: (A OR B) AND (B OR C) = B OR (A AND C<←
2326         )");
2327     finalPowerset A = atomPset[theSizeOfFrame/4].clone();
2328     finalPowerset B = atomPset[theSizeOfFrame/2].clone();
2329     finalPowerset C = atomPset[(3*theSizeOfFrame)/4].clone();
2330     finalPowerset AUB = fPset.instanceNsize();
2331     finalPowerset BUC = fPset.instanceNsize();
2332     finalPowerset ANC = fPset.instanceNsize();
2333     finalPowerset left = fPset.instanceNsize();
2334     finalPowerset right = fPset.instanceNsize();
2335     AUB.or(A, B);
2336     BUC.or(B, C);
2337     ANC.and(A, C);
2338     left.and(AUB, BUC);
2339     right.or(B, ANC);
2340     boolean isEqual = left.compareTo(right) == 0;
2341     System.out.println("A = atomPset["+theSizeOfFrame/4+"] = " + A.state());
2342     System.out.println("B = atomPset["+theSizeOfFrame/2+"] = " + B.state());
2343     System.out.println("C = atomPset["+theSizeOfFrame/4*3+"] = " + C.state()<←
2344         );
2345     System.out.println("(A OR B) AND (B OR C) = " + left.state());
2346     System.out.println("B OR (A AND C) = " + right.state());
2347     System.out.println("isEqual = " + isEqual);
2348 }
2349
2350 /**
2351 * Compare different referee functions applied to the fusion of 3 bba.
2352 * Both sampling and relaxed approaches are considered.
2353 *
2354 * This example works like { @link RefereeToolbox_Tutorial#<←

```

```

2355     RefereeFuserRTS_Comparison() }
2356 * and {@link RefereeToolbox_Tutorial#RefereeSampler_Comparison() } so that
2357 * it is not explained in details.
2358 * However, it is noticed that the combinations work here on three sources ,
2359 * denoted <i>aFuser1</i>, <i>aFuser2</i>, <i>aFuser3</i> for the relaxed approach,
2360 * and <i>aSampler1</i>, <i>aSampler2</i>, <i>aSampler3</i> for the sampled approach.
2361 * In order to compute on these tree sources, it is necessary to use an <i>ArrayList</i>
2362 * containing the sources, and apply the methods:<BR>
2363 * {@link BBAREfereeFuser#fuse(java.util.ArrayList, RefereeToolbox.<BR>
2364 *     RefereeFunctionDefault) }
2365 * for the relaxed approach<BR>
2366 * {@link SampledBBARefereeFuser#setFuser(java.util.ArrayList, RefereeToolbox.<BR>
2367 *     RefereeFunctionDefault) }
2368 * for the sampling approach<BR>
2369 * <BR>
2370 * Typically, the fusion by means of PCR# is done by the following codes:<BR>
2371 * <code>
2372 * // referee function definition<BR>
2373 * RFPCRSharp_Powerset referee5 =new RFPCRSharp_Powerset();<BR>
2374 * // [...] <BR>
2375 * // Array creation<BR>
2376 * <font color="#FF0000" >
2377 * ArrayList<finalRefereeFuserRTS_Powerset> bbaArrayR =<BR>
2378 * &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; new {@code ArrayList<
2379 *     finalRefereeFuserRTS_Powerset>}();<BR>
2380 * bbaArrayR.add(aFuser1);<BR>
2381 * bbaArrayR.add(aFuser2);<BR>
2382 * bbaArrayR.add(aFuser3);<BR>
2383 * </font>
2384 * // [...] <BR>
2385 * // Combination<BR>
2386 * <font color="#FF0000" >
2387 * aFuser.fuse(bbaArrayR, referee5);<BR>
2388 * </font>
2389 * </code>
2390 * for the relaxed approach,<BR>
2391 * <code>
2392 * // referee function definition<BR>
2393 * RFPCRSharp_Powerset referee5 =new RFPCRSharp_Powerset();<BR>
2394 * // [...] <BR>
2395 * // Array creation<BR>
2396 * <font color="#FF0000" >
2397 * ArrayList<finalRefereeSampler_Powerset> bbaArrayS =<BR>
2398 * &nbsp; &nbsp; &nbsp; &nbsp; &nbsp; new {@code ArrayList<
2399 *     finalRefereeSampler_Powerset>}();<BR>
2400 * bbaArrayS.add(aSampler1);<BR>
2401 * bbaArrayS.add(aSampler2);<BR>
2402 * bbaArrayS.add(aSampler3);<BR>
2403 * </font>
2404 * // [...] <BR>
2405 * // Combination<BR>
2406 * <font color="#FF0000" >
2407 * aSampler.setFuser(bbaArrayS, referee5);<BR>
2408 * </font>
2409 * Samples.clear();<BR>
2410 * {@code for(n=0;n<NbSamples;n++) } Samples.add(aSampler.makeFusedSample());<BR>
2411 * Z=aSampler.learnFrom(Samples.toArray());<BR>
2412 * </code>
2413 * for the sampled approach,<BR>
2414 * <BR>
2415 * where <i>aFuser</i> and <i>aSampler</i> are output bba for each
2416 * respective approaches.
2417 *
2418 */
2419 public void Referee_On_3_Entries(){
2420
2421     int printMode=1;
2422     //
2423     finalPowerset A=new finalPowerset();
2424     A.size(3); A.atomic(0);

```

```

2420 finalPowerSet B=A.instanceNsize(); B.atomic(1);
2421 finalPowerSet C=A.instanceNsize(); C.atomic(2);
2422 //
2423 finalPowerSet AUB=A.instanceNsize(); AUB.or(A,B);
2424 finalPowerSet BUC=A.instanceNsize(); BUC.or(B,C);
2425 finalPowerSet CUA=A.instanceNsize(); CUA.or(C,A);
2426 //
2427 finalPowerSet zero=A.instanceNsize(); zero.zero();
2428 finalPowerSet one=A.instanceNsize(); one.one();
2429 //
2430 //
2431 RFDempster_PowerSet referee1 = new RFDempster_PowerSet();
2432 RFDisjunctive_PowerSet referee2 = new RFDisjunctive_PowerSet();
2433 RFDuboisPrade_PowerSet referee3 = new RFDuboisPrade_PowerSet();
2434 RFPCR6_PowerSet referee4 = new RFPCR6_PowerSet();
2435 RFPCRSharp_PowerSet referee5 =new RFPCRSharp_PowerSet();
2436 //
2437 //
2438 finalRefereeFuserRTS_PowerSet aFuser1 = new finalRefereeFuserRTS_PowerSet←
    ();
2439 aFuser1.add(A,0.6);
2440 aFuser1.add(AUB,0.4);
2441 //
2442 finalRefereeFuserRTS_PowerSet aFuser2 = aFuser1.instance();
2443 aFuser2.add(A,0.3);
2444 aFuser2.add(CUA,0.7);
2445 //
2446 finalRefereeFuserRTS_PowerSet aFuser3 = aFuser1.instance();
2447 aFuser3.add(B,0.8);
2448 aFuser3.add(one,0.2);
2449 //
2450 ArrayList<finalRefereeFuserRTS_PowerSet> bbaArrayR =
2451     new ArrayList<finalRefereeFuserRTS_PowerSet>();
2452 bbaArrayR.add(aFuser1);
2453 bbaArrayR.add(aFuser2);
2454 bbaArrayR.add(aFuser3);
2455 //
2456 finalRefereeFuserRTS_PowerSet aFuser = aFuser1.instance();
2457
2458 finalRefereeSampler_PowerSet aSampler1 = new finalRefereeSampler_PowerSet←
    ();
2459 aSampler1.addAll(aFuser1.toArray());
2460 //
2461 finalRefereeSampler_PowerSet aSampler2 = aSampler1.instance();
2462 aSampler2.addAll(aFuser2.toArray());
2463 //
2464 finalRefereeSampler_PowerSet aSampler3 = aSampler1.instance();
2465 aSampler3.addAll(aFuser3.toArray());
2466 //
2467 ArrayList<finalRefereeSampler_PowerSet> bbaArrayS =
2468     new ArrayList<finalRefereeSampler_PowerSet>();
2469 bbaArrayS.add(aSampler1);
2470 bbaArrayS.add(aSampler2);
2471 bbaArrayS.add(aSampler3);
2472 //
2473 finalRefereeSampler_PowerSet aSampler = aSampler1.instance();
2474 //
2475 //
2476 System.out.println(
2477     "//////////\n" +
2478     "/// Relaxed Method\n" +
2479     "//////////\n");
2480 System.out.println("aFuser1");
2481     System.out.println(aFuser1.state(printMode));
2482     System.out.println();
2483 System.out.println("aFuser2");
2484     System.out.println(aFuser2.state(printMode));
2485     System.out.println();
2486 System.out.println("aFuser3");
2487     System.out.println(aFuser3.state(printMode));
2488     System.out.println();
2489 aFuser.fuse(bbaArrayR,referee1);
2490 System.out.println("aFuser - Dempster");
2491     System.out.println("Conflict Z = "+aFuser.conflict()+" %");

```

```

2492         System.out.println(aFuser.state(printMode));
2493         System.out.println();
2494     aFuser.fuse(bbaArrayR,referee2);
2495     System.out.println("aFuser - Disjunctive");
2496         System.out.println("Conflict Z = "+aFuser.conflict()+" %");
2497         System.out.println(aFuser.state(printMode));
2498         System.out.println();
2499     aFuser.fuse(bbaArrayR,referee3);
2500     System.out.println("aFuser - Dubois & Prade");
2501         System.out.println("Conflict Z = "+aFuser.conflict()+" %");
2502         System.out.println(aFuser.state(printMode));
2503         System.out.println();
2504     aFuser.fuse(bbaArrayR,referee4);
2505     System.out.println("aFuser - PCR6");
2506         System.out.println("Conflict Z = "+aFuser.conflict()+" %");
2507         System.out.println(aFuser.state(printMode));
2508         System.out.println();
2509     aFuser.fuse(bbaArrayR,referee5);
2510     System.out.println("aFuser - PCR#");
2511         System.out.println("Conflict Z = "+aFuser.conflict()+" %");
2512         System.out.println(aFuser.state(printMode));
2513         System.out.println();
2514
2515     System.out.println(
2516         "////////////////////////////////////////\n" +
2517         "/// Sampling Method\n" +
2518         "////////////////////////////////////////\n");
2519
2520     int n;
2521     int NbSamples=1000000;
2522     double Z;
2523     finalRefereeSampler_Powerset Samples= aSampler1.instance();
2524
2525     System.out.println("aSampler1");
2526         System.out.println(aSampler1.state(printMode));
2527         System.out.println();
2528     System.out.println("aSampler2");
2529         System.out.println(aSampler2.state(printMode));
2530         System.out.println();
2531     System.out.println("aSampler3");
2532         System.out.println(aSampler3.state(printMode));
2533         System.out.println();
2534
2535     //
2536     aSampler.setFuser(bbaArrayS, referee1);
2537     Samples.clear();
2538     for(n=0;n<NbSamples;n++) Samples.add(aSampler.makeFusedSample());
2539     Z=aSampler.learnFrom(Samples.toArray());
2540     System.out.println("aSampler - Dempster — " + NbSamples + " particles");
2541         System.out.println("Conflict Z = "+Z+" %");
2542         System.out.println(aSampler.state(printMode));
2543         System.out.println();
2544     //
2545     aSampler.setFuser(bbaArrayS, referee2);
2546     Samples.clear();
2547     for(n=0;n<NbSamples;n++) Samples.add(aSampler.makeFusedSample());
2548     Z=aSampler.learnFrom(Samples.toArray());
2549     System.out.println("aSampler - Disjunctive — " + NbSamples + " particles"←
2550     );
2551         System.out.println("Conflict Z = "+Z+" %");
2552         System.out.println(aSampler.state(printMode));
2553         System.out.println();
2554     //
2555     aSampler.setFuser(bbaArrayS, referee3);
2556     Samples.clear();
2557     for(n=0;n<NbSamples;n++) Samples.add(aSampler.makeFusedSample());
2558     Z=aSampler.learnFrom(Samples.toArray());
2559     System.out.println("aSampler - Dubois & Prade — " + NbSamples + " ←
2560     particles");
2561         System.out.println("Conflict Z = "+Z+" %");
2562         System.out.println(aSampler.state(printMode));
2563         System.out.println();
2564     //
2565     aSampler.setFuser(bbaArrayS, referee4);
2566     Samples.clear();

```


[illegible]

```

2694 class myRefereeFunction<Prop extends ComplementedLattice<Prop> >
2695     extends RefereeFunctionDempster<Prop> {
2696     public Prop excludedProposition = null;
2697
2698     @Override
2699     public ArrayList<Assignment<Prop>> refereeFunction(
2700         ArrayList<Assignment<Prop>> assignIn,
2701         ArrayList<minAssignment<Prop>> bbaIn) {
2702         if(excludedProposition==null) return super.refereeFunction(↵
            assignIn, bbaIn);
2703         ArrayList<Assignment<Prop>> output=super.refereeFunction(assignIn,↵
            bbaIn);
2704         if(excludedProposition.contains(output.get(0).attribute))
2705             output.get(0).attribute.zero();
2706         else output.get(0).attribute.and(output.get(0).attribute,
2707             excludedProposition.clone().cocomplement());
2708         return output;
2709     }
2710 }
2711
2712
2713 final Powerset A=new finalPowerset();
2714 A.size(3); A.atomic(0);
2715 final Powerset B=A.instanceNsize(); B.atomic(1);
2716 final Powerset C=A.instanceNsize(); C.atomic(2);
2717 //
2718 final Powerset AUB=A.instanceNsize(); AUB.or(A,B);
2719 final Powerset BUC=A.instanceNsize(); BUC.or(B,C);
2720 final Powerset CUA=A.instanceNsize(); CUA.or(C,A);
2721 //
2722 final Powerset zero=A.instanceNsize(); zero.zero();
2723 final Powerset one=A.instanceNsize(); one.one();
2724 //
2725 //
2726 myRefereeFunction<finalPowerset> myReferee =
2727     new myRefereeFunction<finalPowerset>();
2728 myReferee.excludedProposition=A;
2729 //
2730 //
2731 final RefereeFuserRTS_Powerset aFuser1 = new finalRefereeFuserRTS_Powerset↵
    ();
2732 aFuser1.add(A,0.09);
2733 aFuser1.add(B,0.2);
2734 aFuser1.add(C,0.02);
2735 aFuser1.add(AUB,0.05);
2736 aFuser1.add(BUC,0.03);
2737 aFuser1.add(CUA,0.1);
2738 aFuser1.add(A,0.11);
2739 aFuser1.add(one,0.4);
2740 //
2741 final RefereeFuserRTS_Powerset aFuser2 = aFuser1.instance();
2742 aFuser2.add(A,0.1);
2743 aFuser2.add(B,0.1);
2744 aFuser2.add(C,0.2);
2745 aFuser2.add(AUB,0.2);
2746 aFuser2.add(BUC,0.1);
2747 aFuser2.add(CUA,0.1);
2748 aFuser2.add(one,0.2);
2749 //
2750 final RefereeFuserRTS_Powerset aFuser = aFuser1.instance();
2751 //
2752
2753 int printMode=1;
2754
2755 System.out.println(
2756     "//////////\n" +
2757     "/// Relaxed Method\n" +
2758     "//////////\n");
2759
2760 System.out.println("aFuser1");
2761     System.out.println(aFuser1.state(printMode));
2762     System.out.println();
2763 System.out.println("aFuser2");
2764     System.out.println(aFuser2.state(printMode));

```

```
2765         System.out.println();
2766         aFuser.fuse(aFuser1,aFuser2,myReferee);
2767         System.out.println("aFuser - myReferee");
2768         System.out.println("Conflict Z = "+aFuser.conflict()+" %");
2769         System.out.println(aFuser.state(printMode));
2770         System.out.println();
2771     }
2772 }
2773
2774
2775 }
```

Source Code: RefereeToolbox_Version.java

```

1  /*
2  *   RefereeToolbox_Version.java : part of package RefereeToolbox; Version.
3  *   ****
4  *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville
5  *
6  *   Author:   FrÃ©dÃ©ric Dambreville <http://email.fredericdambreville.com>
7  *
8  *   This file is part of RefereeToolbox.
9  *
10 *   RefereeToolbox is free software: you can redistribute it and/or modify
11 *   it under the terms of the GNU General Public License as published by
12 *   the Free Software Foundation, either version 3 of the License, or
13 *   (at your option) any later version.
14 *
15 *   RefereeToolbox is distributed in the hope that it will be useful,
16 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
17 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
18 *   GNU General Public License for more details.
19 *
20 *   You should have received a copy of the GNU General Public License
21 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
22 *   ****
23 */
24
25 package RefereeToolbox;
26
27 /**
28 * Class providing information about the version of package RefereeToolbox.
29 *
30 * @author      <A href="http://email.fredericdambreville.com">FrÃ©dÃ©ric ↵
31 *              Dambreville</A>
32 *
33 *
34 * <BR><BR><table border='1' cellPadding='4'><tr><td>
35 * <font color="#008000" style="font-family: georgia">
36 *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville<BR>
37 * <BR>
38 *   RefereeToolbox is free software: you can redistribute it and/or modify
39 *   it under the terms of the GNU General Public License as published by
40 *   the Free Software Foundation, either version 3 of the License, or
41 *   (at your option) any later version.<BR>
42 * <BR>
43 *   RefereeToolbox is distributed in the hope that it will be useful,
44 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
45 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
46 *   GNU General Public License for more details.<BR>
47 * <BR>
48 *   You should have received a copy of the GNU General Public License
49 *   along with RefereeToolbox. If not, see
50 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
51 * </font></td></tr></table><BR>
52 *
53 */
54 public class RefereeToolbox_Version {
55
56 /**
57 * Return the current version name.
58 *
59 */
60     public String version() {
61         return "ZERO.0.1";
62     }
63
64 /**
65 * Return the current version code.
66 *
67 */
68     public int version_code() {
69         return 1;
70     }
71

```


Source Code: RelaxedBBA.java

```

1  /*
2  *   RelaxedBBA.java : part of package RefereeToolbox; Interface for Basic
3  *   Belief Assignment with relaxation.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * Methods for relaxing Basic Belief Assignment. The relaxation is based on a
30 * simple logarithmic-time summarization method.
31 *
32 * @author   <A href="http://email.fredericdambreville.com">Frédéric ↵
33 *           Dambreville</A>
34 *
35 *
36 * <BR><BR><table border='1' cellPadding='4'><tr><td>
37 * <font color="#008000" style="font-family: georgia">
38 * Copyright (c) 2010 Frédéric Dambreville<BR>
39 * <BR>
40 * RefereeToolbox is free software: you can redistribute it and/or modify
41 * it under the terms of the GNU General Public License as published by
42 * the Free Software Foundation, either version 3 of the License, or
43 * (at your option) any later version.<BR>
44 * <BR>
45 * RefereeToolbox is distributed in the hope that it will be useful,
46 * but WITHOUT ANY WARRANTY; without even the implied warranty of
47 * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
48 * GNU General Public License for more details.<BR>
49 * <BR>
50 * You should have received a copy of the GNU General Public License
51 * along with RefereeToolbox. If not, see
52 * <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
53 * </font></td></tr></table><BR>
54 *
55 */
56 public interface RelaxedBBA<Prop extends Lattice<Prop>, B extends RelaxedBBA<Prop, ↵
57     B> >
58     extends BasicBeliefAssignment<Prop,B> {
59 /**
60 * Relax <i>this</i> so that it contains no more than <i>maxMem</i> assignments.
61 *
62 */
63     boolean relax(int maxMem);
64
65 /**
66 * Relax <i>this</i> so that it contains no more than {@link RelaxedBBA#maxSize(↵
67     int) }
68 * assignments.
69 *
70 */

```

```

70     boolean relax();
71
72     /**
73      * Set or return the default maximum number of assignments stored in <i>this</i>,
74      * depending on parameter <i>newSize</i>.
75      * If <i>newSize>0</i>, then set the default maximum number of assignments to <i>↔
76      *   newSize</i>.
77      * In any case, return the actual value of the default maximum number.
78      * <BR><BR>
79      * N.B. It is not possible to exceed this number of assignments, except for ↔
80      *   temporary
81      *   computed assignments.
82      */
83     int maxSize(int newSize);

```

Source Code: RelaxedTreeSetBBA.java

```

1  /*
2  *   RelaxedTreeSetBBA.java : part of package RefereeToolbox; Implementation of
3  *   relaxed Basic Belief Assignment.
4  *   ****
5  *   Copyright (c) 2010 FrÃ©dÃ©ric Dambreville
6  *
7  *   Author:   FrÃ©dÃ©ric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * Relaxed extension of {@link TreeSetBBA }.
30 *
31 * @author   <A href="http://email.fredericdambreville.com">FrÃ©dÃ©ric ↵
32 *           Dambreville</A>
33 *
34 *
35 * <BR><BR><table border='1' cellPadding='4'><tr><td>
36 * <font color="#008000" style="font-family: georgia">
37 * Copyright (c) 2010 FrÃ©dÃ©ric Dambreville<BR>
38 * <BR>
39 * RefereeToolbox is free software: you can redistribute it and/or modify
40 * it under the terms of the GNU General Public License as published by
41 * the Free Software Foundation, either version 3 of the License, or
42 * (at your option) any later version.<BR>
43 * <BR>
44 * RefereeToolbox is distributed in the hope that it will be useful,
45 * but WITHOUT ANY WARRANTY; without even the implied warranty of
46 * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
47 * GNU General Public License for more details.<BR>
48 * <BR>
49 * You should have received a copy of the GNU General Public License
50 * along with RefereeToolbox. If not, see
51 * <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
52 * </font></td></tr></table><BR>
53 *
54 */
55 public class RelaxedTreeSetBBA< Prop extends Lattice<Prop>,
56                               B extends RelaxedTreeSetBBA<Prop,B> >
57       extends TreeSetBBA<Prop,B>
58       implements RelaxedBBA<Prop,B> {
59
60     @Override
61     protected boolean relaxed() { return true; }
62
63
64     ///////////////////////////////////////////:
65     // public part
66     //////////////////////////////////////////
67
68 /**
69 * Relax <i>this</i> so that it contains no more than <i>maxMem</i> assignments.
70 *
71 */

```

```

72     @Override
73     public boolean relax(int maxMem) { return super.relax(maxMem); }
74
75 /**
76  * Relax <i>this</i> so that it contains no more than {@link RelaxedBBA#maxSize(↵
77     int) }
78     * assignments.
79     */
80     @Override
81     public boolean relax() { return super.relax(); }
82
83 /**
84  * Set or return the default maximum number of assignments stored in <i>this</i>,
85  * depending on parameter <i>newSize</i>.
86  * If <i>newSize>0</i>, then set the default maximum number of assignments to <i>↵
87     newSize</i>.
88  * In any case, return the actual value of the default maximum number.
89  * <BR><BR>
90  * N.B. It is not possible to exceed this number of assignments, except for ↵
91     temporary
92     * computed assignments.
93     */
94     @Override
95     public int maxSize(int newSize) { return super.maxSize(newSize); }

```

Source Code: RFDempster_Powerset.java

```

1  /*
2  *   RFDempster_Powerset.java : part of package RefereeToolbox; Implementation
3  *   of referee function.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * A non generic instance of {@link RefereeFunctionDempster} specialized for
30 * Lattice structures typed {@link finalPowerset}.
31 *
32 * @author   <A href="http://email.fredericdambreville.com">Frédéric ↵
33 *           Dambreville</A>
34 *
35 *
36 * <BR><BR><table border='1' cellPadding='4'><tr><td>
37 * <font color="#008000" style="font-family: georgia">
38 *   Copyright (c) 2010 Frédéric Dambreville<BR>
39 * <BR>
40 *   RefereeToolbox is free software: you can redistribute it and/or modify
41 *   it under the terms of the GNU General Public License as published by
42 *   the Free Software Foundation, either version 3 of the License, or
43 *   (at your option) any later version.<BR>
44 * <BR>
45 *   RefereeToolbox is distributed in the hope that it will be useful,
46 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
47 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
48 *   GNU General Public License for more details.<BR>
49 * <BR>
50 *   You should have received a copy of the GNU General Public License
51 *   along with RefereeToolbox. If not, see
52 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
53 * </font></td></tr></table><BR>
54 *
55 */
56 public class RFDempster_Powerset extends RefereeFunctionDempster<finalPowerset> {
57
58 }

```

Source Code: RFDisjunctive_Powerset.java

```

1  /*
2  *   RFDisjunctive_Powerset.java : part of package RefereeToolbox;
3  *   Implementation of referee function.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * A non generic instance of {@link RefereeFunctionDisjunctive} specialized for
30 * Lattice structures typed {@link finalPowerset}.
31 *
32 * @author   <A href="http://email.fredericdambreville.com">Frédéric ↵
33 *           Dambreville</A>
34 *
35 *
36 * <BR><table border='1' cellPadding='4'><tr><td>
37 * <font color="#008000" style="font-family: georgia">
38 *   Copyright (c) 2010 Frédéric Dambreville<BR>
39 * <BR>
40 *   RefereeToolbox is free software: you can redistribute it and/or modify
41 *   it under the terms of the GNU General Public License as published by
42 *   the Free Software Foundation, either version 3 of the License, or
43 *   (at your option) any later version.<BR>
44 * <BR>
45 *   RefereeToolbox is distributed in the hope that it will be useful,
46 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
47 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
48 *   GNU General Public License for more details.<BR>
49 * <BR>
50 *   You should have received a copy of the GNU General Public License
51 *   along with RefereeToolbox. If not, see
52 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
53 * </font></td></tr></table><BR>
54 *
55 */
56 public class RFDisjunctive_Powerset extends RefereeFunctionDisjunctive<↵
57     finalPowerset> {
58 }

```

Source Code: RFDuboisPrade_Powerset.java

```

1  /*
2  *   RFDuboisPrade_Powerset.java : part of package RefereeToolbox;
3  *   Implementation of referee function.
4  *   *****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   *****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * A non generic instance of {@link RefereeFunctionDuboisPrade } specialized for
30 * Lattice structures typed {@link finalPowerset }.
31 *
32 * @author      <A href="http://email.fredericdambreville.com">Frédéric ↵
33 *              Dambreville</A>
34 *
35 *
36 * <BR><BR><table border='1' cellPadding='4'><tr><td>
37 * <font color="#008000" style="font-family: georgia">
38 *   Copyright (c) 2010 Frédéric Dambreville<BR>
39 * <BR>
40 *   RefereeToolbox is free software: you can redistribute it and/or modify
41 *   it under the terms of the GNU General Public License as published by
42 *   the Free Software Foundation, either version 3 of the License, or
43 *   (at your option) any later version.<BR>
44 * <BR>
45 *   RefereeToolbox is distributed in the hope that it will be useful,
46 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
47 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
48 *   GNU General Public License for more details.<BR>
49 * <BR>
50 *   You should have received a copy of the GNU General Public License
51 *   along with RefereeToolbox. If not, see
52 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
53 * </font></td></tr></table><BR>
54 *
55 */
56 public class RFDuboisPrade_Powerset extends RefereeFunctionDuboisPrade<↵
57     finalPowerset> {
58 }

```

Source Code: RFPCR6_Powerset.java

```

1  /*
2  *   RFPCR6_Powerset.java : part of package RefereeToolbox; Implementation of
3  *   referee function.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * A non generic instance of {@link RefereeFunctionPCR6 } specialized for
30 * Lattice structures typed {@link finalPowerset }.
31 *
32 * @author      <A href="http://email.fredericdambreville.com">Frédéric ↵
33 *              Dambreville</A>
34 *
35 *
36 * <BR><BR><table border='1' cellPadding='4'><tr><td>
37 * <font color="#008000" style="font-family: georgia">
38 *   Copyright (c) 2010 Frédéric Dambreville<BR>
39 * <BR>
40 *   RefereeToolbox is free software: you can redistribute it and/or modify
41 *   it under the terms of the GNU General Public License as published by
42 *   the Free Software Foundation, either version 3 of the License, or
43 *   (at your option) any later version.<BR>
44 * <BR>
45 *   RefereeToolbox is distributed in the hope that it will be useful,
46 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
47 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
48 *   GNU General Public License for more details.<BR>
49 * <BR>
50 *   You should have received a copy of the GNU General Public License
51 *   along with RefereeToolbox. If not, see
52 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
53 * </font></td></tr></table><BR>
54 *
55 */
56 public class RFPCR6_Powerset extends RefereeFunctionPCR6<finalPowerset> {
57
58 }

```

Source Code: RFPCRSharp_Powerset.java

```

1  /*
2  *   RFPCRSharp_Powerset.java : part of package RefereeToolbox; Implementation
3  *   of referee function.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * A non generic instance of {@link RefereeFunctionPCRSharp } specialized for
30 * Lattice structures typed {@link finalPowerset }.
31 *
32 * @author   <A href="http://email.fredericdambreville.com">Frédéric ↵
33 *           Dambreville</A>
34 *
35 *
36 * <BR><BR><table border='1' cellPadding='4'><tr><td>
37 * <font color="#008000" style="font-family: georgia">
38 *   Copyright (c) 2010 Frédéric Dambreville<BR>
39 * <BR>
40 *   RefereeToolbox is free software: you can redistribute it and/or modify
41 *   it under the terms of the GNU General Public License as published by
42 *   the Free Software Foundation, either version 3 of the License, or
43 *   (at your option) any later version.<BR>
44 * <BR>
45 *   RefereeToolbox is distributed in the hope that it will be useful,
46 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
47 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
48 *   GNU General Public License for more details.<BR>
49 * <BR>
50 *   You should have received a copy of the GNU General Public License
51 *   along with RefereeToolbox. If not, see
52 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
53 * </font></td></tr></table><BR>
54 *
55 */
56 public class RFPCRSharp_Powerset extends RefereeFunctionPCRSharp<finalPowerset> {
57
58 }

```

Source Code: SampledBBA.java

```

1  /*
2  *   SampledBBA.java : part of package RefereeToolbox; Interface for sampled
3  *   Basic Belief Assignment.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 import java.util.*;
29
30 /**
31 * Methods for sampling Basic Belief Assignments and learning Basic Belief
32 * Assignments
33 * from a samples vector.
34 *
35 * @author   <A href="http://email.fredericdambreville.com">Frédéric
36 *           Dambreville</A>
37 *
38 * <BR><table border='1' cellPadding='4'><tr><td>
39 * <font color="#008000" style="font-family: georgia">
40 *   Copyright (c) 2010 Frédéric Dambreville<BR>
41 * <BR>
42 *   RefereeToolbox is free software: you can redistribute it and/or modify
43 *   it under the terms of the GNU General Public License as published by
44 *   the Free Software Foundation, either version 3 of the License, or
45 *   (at your option) any later version.<BR>
46 * <BR>
47 *   RefereeToolbox is distributed in the hope that it will be useful,
48 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
49 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
50 *   GNU General Public License for more details.<BR>
51 * <BR>
52 *   You should have received a copy of the GNU General Public License
53 *   along with RefereeToolbox. If not, see
54 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
55 * </font></td></tr></table><BR>
56 *
57 */
58 public interface SampledBBA<Prop extends Lattice<Prop>, sB extends SampledBBA<Prop,
59   ,sB> >
60   extends BasicBeliefAssignment<Prop,sB> {
61
62 /**
63 * Learn a new basic belief assignment for <i>this</i> from a given array of ←
64 * weighted
65 * proposition particles. The weighed particle are provided as an array of ←
66 * assignment
67 * ArrayLattice<{@link Assignment }>.
68 * A mesure of conflict is returned, as a percentage of the conflicting samples.
69 *
70 */

```

```

68     double learnFrom(ArrayList<Assignment<Prop>> weightedSamples);
69
70 /**
71  * Make a proposition sample according to the basic belief assignement stored
72  * within <i>this</i>.
73  * The produced sample is weighted (at this time, the weight is 1), and, for this
74  * reason, is produced as an assignment {@link Assignment } with
75  * value 1.
76  *
77  */
78     Assignment<Prop> makeSample(); // weight may be null
79     // in such a case, uniform weight is considered
80
81 /**
82  * Initialize the sampled mixer. Are needed as entry the basic belief assignments
83  * to be mixed, provided within array <i>bbaIn</i>, and the weights stored within
84  * <i>weights</i>. It is not necessary that the weights sum to 1, but the weights
85  * cannot be negative.
86  *
87  */
88     boolean setMixer(double[] weights, ArrayList<SB> bbaIn);
89
90 /**
91  * Make a <i>random</i> choice among the basic belief assignments in proportion
92  * to their respective weights.
93  * Both the weights and basic belief assignments have been first provided to ←
94  * method
95  * {@link SampledBBARefereeFuser#setMixer }. It is necessary to run the method
96  * {@link SampledBBARefereeFuser#setMixer } before the first run of
97  * {@link SampledBBARefereeFuser#makeMixedChoice() }.
98  * The produced sample is weighted (at this time, the weight is 1), and, for this
99  * reason, is produced as an assignment {@link Assignment } with
100  * value 1.
101  *
102  */
103     SB makeMixedChoice();
104 }

```

Source Code: SampledBBARefereeFuser.java

```

1  /*
2  *   SampledBBARefereeFuser.java : part of package RefereeToolbox; Interface for
3  *   sampled fuser based on referee function.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 import java.util.*;
29
30 /**
31 * Methods for fusing Basic Belief Assignments by the means of referee functions
32 * and on the basis of a particle approximation. This interface does not concern
33 * direct rule implementations, {@link BBAFuser}, or exact referee-based fusion
34 * {@link BBARefereeFuser}.
35 *
36 * @see          BBAFuser
37 * @see          BBARefereeFuser
38 * @author        <A href="http://email.fredericdambreville.com">Frédéric ↵
39 *               Dambreville</A>
40 *
41 *
42 * <BR><BR><table border='1' cellPadding='4'><tr><td>
43 * <font color="#008000" style="font-family: georgia">
44 *   Copyright (c) 2010 Frédéric Dambreville<BR>
45 * <BR>
46 *   RefereeToolbox is free software: you can redistribute it and/or modify
47 *   it under the terms of the GNU General Public License as published by
48 *   the Free Software Foundation, either version 3 of the License, or
49 *   (at your option) any later version.<BR>
50 * <BR>
51 *   RefereeToolbox is distributed in the hope that it will be useful,
52 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
53 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
54 *   GNU General Public License for more details.<BR>
55 * <BR>
56 *   You should have received a copy of the GNU General Public License
57 *   along with RefereeToolbox. If not, see
58 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
59 * </font></td></tr></table><BR>
60 *
61 */
62 public interface SampledBBARefereeFuser<Prop extends Lattice<Prop>,
63                                     sB extends SampledBBARefereeFuser<Prop,sB>>
64                                     extends SampledBBA<Prop,sB> {
65
66 /**
67 * Initialize the sampled fuser. Are needed as entry the basic belief assignments
68 * to be fused, provided within array <i>bbaIn</i>, and a referee function
69 * <i>theRefereeFunction</i>.
70 *
71 */

```

```

72     boolean setFuser(ArrayList<sB> bbaIn, RefereeFunctionDefault<Prop> ←
73         theRefereeFunction);
74
75 /**
76  * Initialize the sampled fuser. Are needed as entry the basic belief assignments
77  * to be fused, provided as <i>left</i> and <i>right</i>, and a referee function
78  * <i>theRefereeFunction</i>.
79  */
80     boolean setFuser(sB left, sB right, RefereeFunctionDefault<Prop> ←
81         theRefereeFunction);
82
83 /**
84  * Make a proposition sample according to the fused basic belief assignement ←
85  * implied
86  * by the basic belief assignements and referee function provided to method
87  * {@link SampledBBARefereeFuser#setFuser(java.util.ArrayList,
88  * RefereeToolbox.RefereeFunctionDefault) }
89  * or {@link SampledBBARefereeFuser#setFuser(RefereeToolbox.SampledBBARefereeFuser←
90  * ,
91  * RefereeToolbox.SampledBBARefereeFuser, RefereeToolbox.RefereeFunctionDefault) ←
92  * }.
93  * It is necessary to run these methods
94  * before the first run of
95  * {@link SampledBBARefereeFuser#makeFusedSample() }.
96  * The produced sample is weighted (at this time, the weight is 1), and, for this
97  * reason, is produced as an assignment {@link Assignment } with
98  * value 1.
99  */
100    Assignment<Prop> makeFusedSample();

```

Source Code: Superpowerset.java

```

1  /*
2  *   Superpowerset.java : part of package RefereeToolbox; Implementation of
3  *   superpowerset.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 /**
29 * Implementation of a Superpowerset structure by means of an array of {@code long}
30 * }.
31 * Structural and logical methods are inherited from {@link Freeboolean }.
32 * However, Superpowersets come with the constraint that the union of all atomic
33 * propositions is one or equivalently, the intersection of all negated
34 * atomic
35 * propositions is zero:
36 * <BR><BR>
37 * <i> <b>OR</b><sub>0 ≤ i < sizeFrame</sub> atomic(i) = one</i>
38 * <BR>
39 * <i> <b>AND</b><sub>0 ≤ i < sizeFrame</sub> atomic(i) = zero</i>
40 * <BR><BR>
41 * Then, zero is still defined by zeroing all bits; but one is
42 * defined
43 * by setting to 1 all active bits except the first one.
44 * The complement/cocomplement operators are inherited from the operators {@code ~}
45 * }
46 * working on {@code long}; exceeding bits are masked by a AND with one.
47 *
48 * @author   <A href="http://email.fredericdambreville.com">Frédéric
49 *   Dambreville</A>
50 *
51 *
52 * <BR><BR><table border='1' cellPadding='4'><tr><td>
53 * <font color="#008000" style="font-family: georgia">
54 * Copyright (c) 2010 Frédéric Dambreville<BR>
55 * <BR>
56 * RefereeToolbox is free software: you can redistribute it and/or modify
57 * it under the terms of the GNU General Public License as published by
58 * the Free Software Foundation, either version 3 of the License, or
59 * (at your option) any later version.<BR>
60 * <BR>
61 * RefereeToolbox is distributed in the hope that it will be useful,
62 * but WITHOUT ANY WARRANTY; without even the implied warranty of
63 * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
64 * GNU General Public License for more details.<BR>
65 * <BR>
66 * You should have received a copy of the GNU General Public License
67 * along with RefereeToolbox. If not, see
68 * <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
69 * </font></td></tr></table><BR>
70 *
71 */

```

```

68 public class Superpowerset<L extends Superpowerset<L> > extends Freeboolean<L> {
69
70
71     ///////////////////////////////////////////:
72     // public part
73     //////////////////////////////////////
74
75     /**
76      * Set <i>this</i> to one, the neutral element for
77      * {@link Superpowerset#and(java.lang.Object, java.lang.Object) }.
78      * For the class {@link Superpowerset }, the first bit of <i>one</i> is set to 0.
79      *
80      */
81     @Override
82     public L one() {
83         super.one();
84         _memory[0]&=0xFFFFFFFFFFFFFEL; // remove the first bit
85         return (L) this;
86     }
87
88     /**
89      * Compute the <b>complement</b> of <i>aProposition</i> and store the result ←
90      * within
91      * <i>this</i>.
92      * For the class {@link Superpowerset }, the first bit of the result is set to 0.
93      * <BR><BR>
94      * <b>Documentation inherited from {@link Freeboolean }:</b><BR>
95      * {@inheritDoc}
96      *
97      */
98     @Override
99     public L complement(L aProposition) {
100         super.complement(aProposition);
101         _memory[0]&=0xFFFFFFFFFFFFFEL; // remove the first bit
102         return (L) this;
103     }
104
105     /**
106      * Compute the <b>complement</b> of <i>this</i> and store the result within
107      * <i>this</i>.
108      * For the class {@link Superpowerset }, the first bit of the result is set to 0.
109      * <BR><BR>
110      * <b>Documentation inherited from {@link Freeboolean }:</b><BR>
111      * {@inheritDoc}
112      *
113      */
114     @Override
115     public L complement() {
116         super.complement();
117         _memory[0]&=0xFFFFFFFFFFFFFEL; // remove the first bit
118         return (L) this;
119     }
120 }

```

Source Code: TreeSetBBA.java

```

1  /*
2  *   TreeSetBBA.java : part of package RefereeToolbox; Implementation of Basic
3  *   Belief Assignment.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 import java.util.*;
29
30 /**
31 * Implement the Basic Belief Assignment by means of a double {@link TreeSet }.
32 * The TreeSet is applied to storing the list of assignments, typed {@link ↵
33 *   Assignment },
34 * which define the Basic Belief Assignment. A double ordering of the assignment is
35 * implemented: an increasing total order over the attributes of the assignments,
36 * and a decreasing (total) ordering over the values of the assignments.
37 * The attribute-related ordering is instrumental for logarithmic manipulation of
38 * the assignments on the basis of an addressing by the attribute.
39 * The value-related ordering is used by subclasses of {@link TreeSetBBA} for
40 * relaxing the Basic Belief Assignment: by means of an interative summarization,
41 * each step being logarithmic time, the size of the assignments list is ↵
42 * maintained
43 * under a maximal bound.
44 * The relaxation is not available from this class.
45 *
46 * <BR>
47 * These logarithmic operations are made possible by the property of the class
48 * {@link TreeSet }.
49 *
50 * @author   <A href="http://email.fredericdambreville.com">Frédéric ↵
51 *   Dambreville</A>
52 *
53 *
54 *
55 * <BR><BR><table border='1' cellPadding='4'><tr><td>
56 * <font color="#008000" style="font-family: georgia">
57 *   Copyright (c) 2010 Frédéric Dambreville<BR>
58 * <BR>
59 *   RefereeToolbox is free software: you can redistribute it and/or modify
60 *   it under the terms of the GNU General Public License as published by
61 *   the Free Software Foundation, either version 3 of the License, or
62 *   (at your option) any later version.<BR>
63 * <BR>
64 *   RefereeToolbox is distributed in the hope that it will be useful,
65 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
66 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
67 *   GNU General Public License for more details.<BR>
68 * <BR>
69 *   You should have received a copy of the GNU General Public License
70 *   along with RefereeToolbox. If not, see
71 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
72 * </font></td></tr></table><BR>
73 *

```

```

70  */
71  public class TreeSetBBA<Prop extends Lattice<Prop>,
72                                     B extends TreeSetBBA<Prop,B> >
73                                     extends BBACCommon<Prop,B> {
74
75      protected int theMaxSize = 20;
76
77      protected boolean relaxed() { return false; }
78
79      protected final Comparator< Assignment<Prop> > comparatorA =
80          new Comparator< Assignment<Prop> > () {
81          //
82          public int compare(Assignment<Prop> left, Assignment<Prop> right) {
83
84              return left.attribute.compareTo(right.attribute);
85          }
86      };
87
88
89      protected final Comparator< Assignment<Prop> > comparatorVA =
90          new Comparator< Assignment<Prop> > () {
91
92          public int compare(Assignment<Prop> left, Assignment<Prop> right) {
93              // Comparison order is reverted
94              int answerV = right.value.compareTo(left.value);
95              if(answerV!=0) return answerV;
96              return left.attribute.compareTo(right.attribute);
97          }
98      };
99
100
101      protected TreeSet<Assignment<Prop>> bbaTreeA = new TreeSet<Assignment<Prop>>(←
102          comparatorA);
103
104      protected TreeSet<Assignment<Prop>> bbaTreeVA = new TreeSet<Assignment<Prop>>(←
105          comparatorVA);
106
107      protected boolean _relaxStep() { // only used with the relaxed extensions of ←
108          the class
109          if(bbaTreeA.size()<2) {
110              System.err.println("Error :: "+this.getClass().getName() +
111                  "._relaxStep() :: bbaTreeA.size()<2");
112              System.exit(0);
113          }
114          Assignment<Prop> lastPair=bbaTreeVA.pollLast();
115          Assignment<Prop> prevLastPair = bbaTreeVA.pollLast();
116          bbaTreeA.remove(lastPair);
117          bbaTreeA.remove(prevLastPair);
118          prevLastPair.value+=lastPair.value;
119          prevLastPair.attribute.or(prevLastPair.attribute,lastPair.attribute);
120          add(prevLastPair);
121          return true;
122      }
123
124      ///////////////////////////////////////////////////:
125      // public part
126      ///////////////////////////////////
127
128      /**
129       * Do an exact copy of input into <i>this</i>.
130       */
131      @Override
132      public B duplicate(B input) {
133          load(input.bbaTreeVA);
134          return (B) this;
135      }
136
137      /**
138       * Return a representation of the state of <i>this</i> printed as
139       * a String. Typically, this state is the list of all stored assignments (←
140         proposition

```

```

140 * and value). Depending on the parameter <i>choix</i> in entry, the ↵
      representation
141 * is modified as follows:<br><br>
142 * <i>choix==0</i> — Nothing is printed.
143 * <br>
144 * <i>choix==1</i> — Assignments are printed in increasing order of their
145 * propositions,
146 * <br>
147 * <i>choix==2</i> — Assignments are printed in decreasing order of their
148 * value,
149 * <br>
150 * <i>choix==3</i> — Do both print in that order.
151 * <br><br>
152 * Assignments are printed according to the following format:
153 * <br>
154 * <code> attribute -> value </code>
155 * <br>
156 * The attribute is printed according to its own state method {@link Lattice#state↵
      () }.
157 *
158 */
159 @Override
160 public String state(int choix) {
161     String theState="";
162     if((choix&1)==1) {
163         theState="bbaTreeA:\n";
164         for (Iterator<Assignment<Prop>> it = bbaTreeA.iterator();
165              it.hasNext(); ) {
166             Assignment<Prop> currentPair=it.next();
167             theState+=currentPair.attribute.state() + " -> " +
168                     currentPair.value + "\n";
169         }
170     }
171     if((choix&3)==3) theState+="\n";
172     if((choix&2)==2) {
173         theState+="bbaTreeVA:\n";
174         for (Iterator<Assignment<Prop>> it = bbaTreeVA.iterator();
175              it.hasNext(); ) {
176             Assignment<Prop> currentPair=it.next();
177             theState+=currentPair.attribute.state() + " -> " +
178                     currentPair.value + "\n";
179         }
180     }
181     return theState;
182 }
183
184
185 /**
186 * Create an array of the assignments stored within the class. These assignments ↵
      not
187 * necessary sum to 1. Notice that the assignments should be positively valued
188 * (focal elements), although <i>this</i> is not a strict requirement.
189 *
190 */
191 @Override
192 public ArrayList<Assignment<Prop>> toArray() {
193     return new ArrayList<Assignment<Prop>> (bbaTreeVA);
194 }
195
196 /**
197 * Remove all assignments from <i>this</i>. The class instance is cleared.
198 *
199 */
200 @Override
201 public void clear() {
202     bbaTreeA.clear();
203     bbaTreeVA.clear();
204     update_notification();
205 }
206
207 /**
208 * Add an assignment characterized by a proposition <i>aProposition</i> and a ↵
      value
209 * <i>anAssignmentValue</i> to <i>this</i>.

```

```

210 * If an assignment already exists for <i>aProposition</i>, say with value <i>←
    theOldValue</i>,
211 * then the new assignment of <i>aProposition</i> is stored with value
212 * <i>theOldValue+anAssignmentValue</i>.
213 *
214 */
215 @Override
216 public boolean add(Prop aProposition, double anAssignmentValue) {
217     if(anAssignmentValue<=0) return false;
218     Assignment<Prop> anAssignment=new Assignment<Prop>();
219     anAssignment.attribute=aProposition.clone(); // avoid border effect with ←
        entry
220     anAssignment.value=anAssignmentValue;
221     Assignment<Prop> foundPair=findProposition(anAssignment);
222     if(foundPair!=null) {
223         anAssignment.value+= foundPair.value;
224         bbaTreeA.remove(foundPair);
225         bbaTreeVA.remove(foundPair);
226     }
227     bbaTreeA.add(anAssignment);
228     bbaTreeVA.add(anAssignment);
229     update_notification();
230     return true;
231 }
232
233 /**
234 * Search if there is an assignment stored within the class, and which attribute
235 * is equal to the attribute of <i>anAssignment</i>.
236 * Return the found assignment, if there is one. Otherwise, return <i>null</i>.
237 *
238 */
239 @Override
240 public Assignment<Prop> findProposition(Assignment<Prop> anAssignment) {
241     Assignment<Prop> foundPair=bbaTreeA.ceiling(anAssignment);
242     if(foundPair!=null) {
243         if(foundPair.attribute.compareTo(anAssignment.attribute)==0) {
244             return foundPair;
245         }
246     }
247     return null;
248 }
249
250 /**
251 * Get the belief of <i>aProposition</i>. Although not required, it is assumed ←
    that
252 * the assignments sum to 1.
253 *
254 */
255 @Override
256 public double Bel(Prop aProposition) {
257     double belief=0.;
258     for (Iterator<Assignment<Prop>> it = bbaTreeA.iterator();
259          it.hasNext(); ) {
260         Assignment<Prop> currentPair=it.next();
261         if(aProposition.contains(currentPair.attribute))
262             belief+=currentPair.value;
263     }
264     return belief;
265 }
266
267 /**
268 * Get the plausibility of <i>aProposition</i>. Although not required, it is ←
    assumed that
269 * the assignments sum to 1.
270 *
271 */
272 @Override
273 public double Pl(Prop aProposition) {
274     double belief=0.;
275     for (Iterator<Assignment<Prop>> it = bbaTreeA.iterator();
276          it.hasNext(); ) {
277         Assignment<Prop> currentPair=it.next();
278         if(aProposition.intersects(currentPair.attribute))
279             belief+=currentPair.value;

```

```

280     }
281     return belief;
282 }
283
284 /**
285  * Remove the assignment related to proposition <i>aProposition</i>, if there is
286  * such assignment stored within <i>this</i>.
287  * Return the value assigned to the proposition.
288  *
289  */
290 @Override
291 public double remove(Prop aProposition) {
292     Assignment<Prop> foundPair=findProposition(aProposition);
293     if(foundPair!=null) {
294         double theValue=foundPair.value;
295         bbaTreeA.remove(foundPair);
296         bbaTreeVA.remove(foundPair);
297         update_notification();
298         return theValue;
299     }
300     return 0.;
301 }
302
303 /**
304  * Make a mix of the basic belief assignments stored within the entry, <i>bbaIn</i>←
305  * >
306  * according to their respective weight <i>weight</i>. This mix is stored into <i>←
307  * this</i>.
308  *
309  */
310 @Override
311 public B mix(ArrayList<B> bbaIn, double[] weight) {
312     int nbIn=bbaIn.size();
313
314     if(nbIn<1) return null;
315     if(nbIn!=weight.length) return null;
316     double cumul=0;
317     double aValue;
318     int i;
319     Iterator j;
320     Assignment<Prop> refOut;
321     for(i=0;i<nbIn;i++) {
322         aValue=weight[i];
323         if(aValue<0) return null;
324         cumul+=aValue;
325     }
326     if(cumul==0) return null;
327     clear();
328     B bbaResult=instance();
329     for(i=0;i<nbIn;i++) {
330         aValue=weight[i]/cumul;
331         for(j=(bbaIn.get(i)).bbaTreeVA.iterator(); j.hasNext();) {
332             refOut=(Assignment<Prop>) j.next();
333             bbaResult.add(refOut.attribute, aValue*refOut.value);
334         }
335     }
336     duplicate(bbaResult);
337     update_notification();
338     return (B) this;
339 }
340
341 @Override
342 public void update_notification() { // called each time a change is done
343     if(relaxed()) relax();
344     else super.update_notification();
345 }
346
347 ///////////////////////////////////////////////////:
348 // reserved part
349 //////////////////////////////////////////////////
350
351 /**
352  * This method is not accessible from class {@link TreeSetBBA} and generates an ←

```

```

352     error
353     * report and a code exit.
354     */
355     public boolean relax(int maxMem) {
356         if(!relaxed()) {
357             System.err.println("Class" + this.getClass().getName()
358                               + " does not implement relaxation");
359             System.exit(0);
360         }
361         if(maxMem<1) return false;
362         boolean test=true;
363         while(bbaTreeA.size()>maxMem) {
364             test=test&&_relaxStep();
365         }
366         super.update_notification();
367         return test;
368     }
369
370 /**
371  * This method is not accessible from class {@link TreeSetBBA } and generates an ↵
372     error
373     * report and a code exit.
374     */
375     public boolean relax(){
376         if(!relaxed()) {
377             System.err.println("Class" + this.getClass().getName()
378                               + " does not implement relaxation");
379             System.exit(0);
380         }
381         return relax(maxSize(-1));
382     }
383
384 /**
385  * This method is not accessible from class {@link TreeSetBBA } and generates an ↵
386     error
387     * report and a code exit.
388     */
389     public int maxSize(int newSize) {
390         if(!relaxed()) {
391             System.err.println("Class" + this.getClass().getName()
392                               + " does not implement relaxation");
393             System.exit(0);
394         }
395         if(newSize>0) {
396             theMaxSize=newSize;
397             relax();
398         }
399         return theMaxSize;
400     }
401 }
402

```

Source Code: TreeSetRefereeFuser.java

```

1  /*
2  *   TreeSetRefereeFuser.java : part of package RefereeToolbox; Implementation
3  *   of fuser based on referee function.
4  *   ****
5  *   Copyright (c) 2010 Frédéric Dambreville
6  *
7  *   Author:   Frédéric Dambreville <http://email.fredericdambreville.com>
8  *
9  *   This file is part of RefereeToolbox.
10 *
11 *   RefereeToolbox is free software: you can redistribute it and/or modify
12 *   it under the terms of the GNU General Public License as published by
13 *   the Free Software Foundation, either version 3 of the License, or
14 *   (at your option) any later version.
15 *
16 *   RefereeToolbox is distributed in the hope that it will be useful,
17 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
18 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
19 *   GNU General Public License for more details.
20 *
21 *   You should have received a copy of the GNU General Public License
22 *   along with RefereeToolbox. If not, see <http://www.gnu.org/licenses/>.
23 *   ****
24 */
25
26 package RefereeToolbox;
27
28 import java.util.*;
29
30 /**
31 * This class implements a generic combination of Basic Belief Assignments by the
32 * means of referee functions and on the basis of an exact computation. This
33 * class does not handle direct rule implementations, {@link BBAFuser}, or
34 * implementations based on referee sampling, {@link SampledBBARefereeFuser}.
35 *
36 * @author      <A href="http://email.fredericdambreville.com">Frédéric ↵
37 *               Dambreville</A>
38 *
39 *
40 * <BR><BR><table border='1' cellPadding='4'><tr><td>
41 * <font color="#008000" style="font-family: georgia">
42 *   Copyright (c) 2010 Frédéric Dambreville<BR>
43 * <BR>
44 *   RefereeToolbox is free software: you can redistribute it and/or modify
45 *   it under the terms of the GNU General Public License as published by
46 *   the Free Software Foundation, either version 3 of the License, or
47 *   (at your option) any later version.<BR>
48 * <BR>
49 *   RefereeToolbox is distributed in the hope that it will be useful,
50 *   but WITHOUT ANY WARRANTY; without even the implied warranty of
51 *   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
52 *   GNU General Public License for more details.<BR>
53 * <BR>
54 *   You should have received a copy of the GNU General Public License
55 *   along with RefereeToolbox. If not, see
56 *   <a href='http://www.gnu.org/licenses/'>http://www.gnu.org/licenses/</a>.
57 * </font></td></tr></table><BR>
58 *
59 */
60
61 public class TreeSetRefereeFuser<Prop extends Lattice<Prop>,
62     B extends TreeSetRefereeFuser<Prop,B> >
63     extends TreeSetBBA<Prop,B>
64     implements BBASources<Prop, B> {
65
66     protected double theConflict=-1.;
67     protected Prop theZero=null;
68     protected ArrayList<minAssignment<Prop>> BBASources= new ArrayList<↵
69         minAssignment<Prop>>();
70

```

```

71 ///////////////////////////////////////////////////:
72 // public part
73 //////////////////////////////////////////////////
74
75 public double conflict() {
76     return theConflict;
77 }
78
79 public B fuse(B left, B right, RefereeFunctionDefault<Prop> theRefereeFunction ←
80 ) {
81     ArrayList<B> bbaTab= new ArrayList<B>();
82     bbaTab.add(left);
83     bbaTab.add(right);
84     return fuse(bbaTab, theRefereeFunction);
85 }
86
87 public B fuse(ArrayList<B> bbaIn, RefereeFunctionDefault<Prop> ←
88 theRefereeFunction) {
89     int nbIn;
90     int k,l;
91     double Norm;
92     nbIn=bbaIn.size();
93     if(nbIn<1) return null;
94     Iterator[] j=new Iterator[nbIn];
95     ArrayList<Assignment<Prop>> assignIn = new ArrayList<Assignment<Prop>>();
96     BBASources.clear();
97     for(k=0;k<nbIn;k++) {
98         assignIn.add(null);
99         BBASources.add(bbaIn.get(k));
100     } // Chercher mieux ?
101     //
102     double[] propEval= new double[l+nbIn];
103     propEval[nbIn]=1.;
104     ArrayList<Assignment<Prop>> refOut;
105     Assignment<Prop> aTmpAssign;
106     B bbaResult= instance();
107     bbaResult.clear();
108     for(k=0;k<nbIn;k++) j[k]=bbaIn.get(k).bbaTreeVA.iterator();
109     for(k=nbIn-1;k<nbIn;) {
110         if(j[k].hasNext()) {
111             aTmpAssign=(Assignment<Prop>) j[k].next();
112             assignIn.set(k, aTmpAssign);
113             propEval[k]=propEval[k+1]*aTmpAssign.value;
114             if(k==0) {
115                 refOut=theRefereeFunction.refereeFunction(assignIn, BBASources) ←
116                 ;
117                 for(l=0;l<refOut.size();l++)
118                     bbaResult.add(refOut.get(l).attribute,
119                                 propEval[0]*refOut.get(l).value);
120             } else {
121                 k--;
122             }
123         } else {
124             j[k]=bbaIn.get(k).bbaTreeVA.iterator();
125             k++;
126         }
127     }
128     bbaResult.update_notification();
129     Norm=0.;
130     if(theZero==null)
131         theZero=bbaResult.bbaTreeA.first().attribute.instanceNsize(). ←
132         zero();
133     theConflict=bbaResult.remove(theZero);
134     for (Iterator<Assignment<Prop>> it = bbaResult.bbaTreeA.iterator();
135          it.hasNext(); ) {
136         Assignment<Prop> currentPair=it.next();
137         Norm+=currentPair.value;
138     }
139     clear();
140     for (Iterator<Assignment<Prop>> it = bbaResult.bbaTreeA.iterator();
141          it.hasNext(); ) {
142         Assignment<Prop> currentPair=it.next();
143         currentPair.value/=Norm;
144     }

```

```
141         add(currentPair);
142     }
143     update_notification();
144
145     return (B) this;
146 }
147
148 }
```

4 License

RefereeToolbox is released under the GNU GENERAL PUBLIC LICENSE:

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://www.gnu.org/licenses/gpl.html>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as

changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the

public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified it, and giving a relevant date.
- b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".
- c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.
- d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

- a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.
- b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.
- c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.
- d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.
- e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions.

Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or
- f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a

patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may

not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM

IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17. Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>
```

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see [<\protect\vrule width0pt\protect\href{http://www.gnu.org/licenses/}>](http://www.gnu.org/licenses/)

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type 'show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type 'show c' for details.
```

The hypothetical commands 'show w' and 'show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see [<\protect\vrule width0pt\protect\href{http://www.gnu.org/licenses/}>](http://www.gnu.org/licenses/)<http://www.gnu.org/licenses/faq/>

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read [<\protect\vrule width0pt\protect\href{http://www.gnu.org/philosophy/why-not-lgpl.html}>](http://www.gnu.org/philosophy/why-not-lgpl.html)<http://www.gnu.org/philosophy/why-not-lgpl.html>